

# Fujitsu Enterprise Postgres 18 for Kubernetes

## Reference Guide

Linux



# Preface

---

## Purpose of this document

This document is a reference, and explains parameter.

## Intended readers

This document is aimed at people who manage and operate.

Readers of this document are also assumed to have general knowledge of:

- Linux
- Kubernetes
- Containers
- Operators

## Structure of this document

This document is structured as follows:

### [Chapter 1 Custom Resource Parameters](#)

Explains the parameter.

### [Appendix A Default Metrics Queries](#)

Explains the Default Metrics Queries

### [Appendix B Default Alert Rules](#)

Explains the Default Alert Rules

### [Appendix C Operator Operation Event Notification](#)

Explains the Operator Operation Event Notification

## Abbreviations

The following abbreviations are used in this manual:

| Full Name                                                                 | Abbreviations |
|---------------------------------------------------------------------------|---------------|
| Fujitsu Enterprise Postgres for Kubernetes<br>Fujitsu Enterprise Postgres | FEP           |
| Transparent Data Encryption                                               | TDE           |
| Custom Resource                                                           | CR            |
| Custom Resource Definition                                                | CRD           |
| Persistent Volume                                                         | PV            |

## Abbreviations of manual titles

The following abbreviations are used in this manual as manual titles:

| Full Manual Title                                       | Abbreviations |
|---------------------------------------------------------|---------------|
| Fujitsu Enterprise Postgres for Kubernetes User's Guide | User's Guide  |

## Trademarks

- Linux is a registered trademark or trademark of Mr. Linus Torvalds in the U.S. and other countries.

- Red Hat and all Red Hat-based trademarks and logos are trademarks or registered trademarks of Red Hat, Inc. in the United States and other countries.
- S/390 is a registered trademark of International Business Machines Corporation ("IBM") in the U.S. and other countries.

Other product and company names mentioned in this manual are the trademarks or registered trademarks of their respective owners.

## **Export restrictions**

If this document is to be exported or provided overseas, confirm legal requirements for the Foreign Exchange and Foreign Trade Act as well as other laws and regulations, including U.S. Export Administration Regulations, and follow the required procedures.

## **Issue date and version**

|                            |
|----------------------------|
| Edition 1.0: December 2025 |
|----------------------------|

## **Copyright**

Copyright 2021-2025 Fujitsu Limited

# Contents

---

|                                                                     |     |
|---------------------------------------------------------------------|-----|
| Chapter 1 Custom Resource Parameters.....                           | 1   |
| 1.1 FEPCluster Parameter.....                                       | 1   |
| 1.2 Custom Resource Parameters.....                                 | 46  |
| 1.2.1 FEPCluster Custom Resource Parameters.....                    | 46  |
| 1.2.2 FEP Cluster Configuration .....                               | 47  |
| 1.2.3 FEPConfig Child Custom Resource Parameters.....               | 47  |
| 1.2.4 FEPUUser Child Custom Resource Parameters.....                | 49  |
| 1.2.5 FEPVOLUME Child Custom Resource Parameters.....               | 51  |
| 1.2.5.1 Create Volumes.....                                         | 51  |
| 1.2.5.2 Delete Volumes.....                                         | 52  |
| 1.2.6 FEPCert Child Custom Resource Parameters.....                 | 53  |
| 1.2.6.1 Create/ Update Certificates .....                           | 53  |
| 1.2.6.2 Delete Certificates.....                                    | 53  |
| 1.2.7 FEPBackup Child Custom Resource Parameters.....               | 55  |
| 1.2.8 FEPRestore Custom Resource Parameters.....                    | 55  |
| 1.2.9 FEPPgpool2 Custom Resource Parameters.....                    | 65  |
| 1.2.10 FEPAction Custom Resource Parameters.....                    | 70  |
| 1.2.10.1 FEPAction Specific Operation Details.....                  | 72  |
| 1.2.11 FEPExporter Custom Resource.....                             | 78  |
| 1.2.12 FEPAutoscale Custom Resource.....                            | 81  |
| 1.2.13 FEPUUpgrade Custom Resource.....                             | 81  |
| 1.2.14 FEPLogging Custom Resources.....                             | 82  |
| 1.2.15 FEP Custom Resources - spec.fep.pgBadger.....                | 84  |
| 1.2.16 FEP Custom Resources - spec.fep.pgAuditLog.....              | 85  |
| 1.2.16.1 Details of pgAuditLog.endpoint.authentication.....         | 85  |
| 1.2.16.2 CR example for customized pgaudit ConfigMap.....           | 86  |
| 1.2.16.3 CR example when uploading logs to Azure Blob.....          | 86  |
| 1.2.16.4 CR example for uploading logs to S3.....                   | 87  |
| Appendix A Default Metrics Queries.....                             | 88  |
| Appendix B Default Alert Rules.....                                 | 99  |
| Appendix C Operator Operation Event Notification.....               | 102 |
| C.1 FEPCluster Event Notification on Custom Resource Changes.....   | 102 |
| C.2 FEPExporter Event Notification on Custom Resource Changes.....  | 108 |
| C.3 Event Notification When FEPLogging Custom Resource Changes..... | 109 |

# Chapter 1 Custom Resource Parameters

This chapter explains the parameter.

## 1.1 FEPCluster Parameter

Equivalent Kubernetes command: `kubectl apply -f FEPClusterCR.yaml`

This operation will create a FEPCluster with supplied information in FEPClusterCR.yaml.

Initial configuration and subsequent changes to FEP Cluster are done through FEP Cluster CR.

| Field                   | Default   | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| metadata.name           | new-fep   | Name for the Cluster. FEP server container will use this value for Patroni scope.<br>e.g. new-fep                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| spec.fep.autoPodRestart | <omitted> | Optional<br><br>This parameter affects the behaviour when value(s) of CPU, memory and/or image for FEP and/or optional Backup container are updated in FEPCluster CR.<br><br>If it is NOT defined and set to true, operator will automatically create an action CR to make values effective by restarting all pods in an orderly fashion to minimise outage.<br><br>If it is set to false, automatic restart of PoDs will NOT happen. To make the changes effective, user must restart pods by creating action CR with type 'pod_restart' and arguments 'ALL'                                                              |
| spec.fep.fepVersion     | <omitted> | Optional<br><br>When deploying a new FEP cluster, this parameter controls which FEP major version will be used for the deployment.<br><br>If not specified, Operator will use latest FEP version supported by the Operator.<br><br>When fepVersion is defined but not spec.fep.image.image, Operator will deploy the specific version of FEP.<br><br>When both fepVersion and image are defined, Operator will use the image and discard the value of fepVersion.<br><br>Current support value: 14, 15, 16, 17, 18<br><br>Note: Changing fepVersion from one version to another version is not supported after deployment. |

| Field                                    | Default                                                                                                                                                          | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.customAnnotation.allDeployments | {}<br>(*)                                                                                                                                                        | Contents under this are optional. User can remove {} and add multiple key-value pairs. All of these pair will be added to annotations of FEP statefulSet and FEP Pods. If left at default, no annotation is added to Pods and statefulSets                                                                                                                                                                                                                        |
| spec.fep.image.image                     | <omitted>                                                                                                                                                        | FEP server container image to be used<br><br>quay.io/fujitsu/fujitsu-enterprise-postgres-18-server:ubi9-18-1.0<br><br>It is optional<br><br>Image line is omitted by default.<br><br>This key has a higher precedence than fepVersion. If both fepVersion and image are omitted, Operator will use the latest FEP version that it supports. If both fepVersion and image are specified, Operator will use the specified image and ignore the value in fepVersion. |
| spec.fep.image.pullPolicy                | IfNotPresent                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| spec.fep.mcSpec.limits                   | cpu: 500m<br>memory: 700Mi<br><br>(If spec.fep.databaseSize is medium)<br>cpu: 2<br>memory: 4Gi<br>(If spec.fep.databaseSize is large)<br>cpu: 4<br>memory: 16Gi |                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| spec.fep.mcSpec.requests                 | cpu: 200m<br>memory: 512Mi<br><br>(If spec.fep.databaseSize is medium)<br>cpu: 1<br>memory: 2Gi<br>(If spec.fep.databaseSize is large)<br>cpu: 2<br>memory: 8Gi  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| spec.fep.databaseSize                    |                                                                                                                                                                  | Specifiable values: small, medium, large<br><br>The operator defines the values for cpu, memory, and postgresql.conf, matching the specified values.<br>If the target parameter is defined, it is not overwritten.<br><br>Can be set only when creating                                                                                                                                                                                                           |

| Field                           | Default | Details                                                                                                                                                                                                     |
|---------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                 |         | FEPCluster custom resource.<br>After you create a FEPCluster custom resource, you customize it by editing each parameter.                                                                                   |
| spec.fep.sysExtraLogging        | false   | To turn extra debugging on, set value to true<br><br>It can be turned on/off at any time                                                                                                                    |
| spec.fep.sysExtraEvent          | false   | Options<br><br>To turn on event notification for custom resource changes, set the value to true. You can turn it on or off at any time.                                                                     |
| spec.fep.instances              | 1       | Number of nodes in the cluster, including both Master and Replicas.<br><br>In Example CR, it is kept at 1 for certification.<br><br>However, user can change it to 3 for 1 master and 2 replicas.           |
| spec.fep.servicePort            | 27500   | TCP port for FEP master service                                                                                                                                                                             |
| spec.fep.syncMode               | off     | Replication Mode:<br><br>off - async replication<br><br>on - sync replication                                                                                                                               |
| spec.fep.standby.enable         | false   | This parameter enables the hot standby configuration. Enabled at true.                                                                                                                                      |
| spec.fep.standby.method         |         | Specifies the method for achieving a hot standby configuration.<br><br>archive-recovery - Uses continuous recovery.<br><br>streaming - Uses streaming replication.                                          |
| spec.fep.standby.pgBackrestConf |         | Required for both continuous recovery and streaming replication methods. You must specify the backup storage on which the production environment is backed up. AWS S3 and Azure Blob Storage are available. |
| spec.fep.standby.streaming.host |         | Specify this option to use the streaming replication method. Specify the external IP of the LoadBalancer you created in "Defining a Streaming Replication Method" in the User's Guide.                      |
| spec.fep.standby.streaming.port |         | Specify this option to use the streaming replication method. Specify the port defined in the LoadBalancer you created in "Defining a Streaming Replication Method" in the User's Guide.                     |
| spec.fep.forceSsl               | true    | Controls the use of SSL only for communication between FEPCluster                                                                                                                                           |

| Field                                                  | Default             | Details                                                                                                                                                                                                    |
|--------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                        |                     | containers. The changes are reflected in pg_hba.conf.<br><br>Changing this parameter is not reflected in pg_hba.conf if the automatic certificate generation feature is enabled.                           |
| spec.fep.locale                                        | <omitted><br>(*)    | Optional<br><br>Can only be specified when creating a FEPCluster.<br><br>Database Cluster Locale Settings:<br>ja_JP - Japanese locale<br>Default - C                                                       |
| spec.fep.monitoring                                    |                     | This is an Optional section. This defines whether monitoring enabled(true) or disabled(false) , MTLS enabled or disabled & Basic authentication enabled or not                                             |
| spec.fep.monitoring.enable                             | false               | If set true, the operator will create FEPExporter with given spec                                                                                                                                          |
| spec.fep.monitoring.fepExporter                        |                     | This is Optional section. Exporter spec section applied only if enable: true                                                                                                                               |
| spec.fep.monitoring.fepExporter.authSecret             |                     | This is Optional section. Base Authentication secret to provide username & encrypted password of user                                                                                                      |
| spec.fep.monitoring.fepExporter.authSecret.secretName  | ( created by user ) | Mandatory<br><br>Name of secret that contains username and password                                                                                                                                        |
| spec.fep.monitoring.fepExporter.authSecret.userKey     | ( created by user ) | Mandatory<br><br>Key of username in specified secret                                                                                                                                                       |
| spec.fep.monitoring.fepExporter.authSecret.passwordKey | ( created by user ) | Mandatory<br><br>Key of password in specified secret                                                                                                                                                       |
| spec.fep.monitoring.fepExporter.tls                    |                     | This is optional section. FEPExporter MTLS specs. Mandatory if tls specs defined for Prometheus specs                                                                                                      |
| spec.fep.monitoring.fepExporter.tls.certificateName    | ( created by user ) | Mandatory.This points to Kubernetes TLS secret that contains the certificate of FepExporter. Prometheus will use this for certificate authentication. The certificate itself is stored in the key tls.crt. |
| spec.fep.monitoring.fepExporter.tls.caName             | ( created by user ) | Mandatory This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt.                                               |

| Field                                                 | Default             | Details                                                                                                                                                                                                                          |
|-------------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.monitoring.fepExporter.customLabel           |                     | Optional<br>List of key value pair to be added to Prometheus ServiceMonitor label. The following label will always be added to ServiceMonitor, regardless if a value is specified here or not.<br>fepsmgrp: sm-fep-exporter      |
| spec.fep.monitoring.prometheus                        |                     | This is Optional section. Prometheus specs are mandatory if tls specs defined for FEPEXporter                                                                                                                                    |
| spec.fep.monitoring.prometheus.tls                    |                     | Prometheus MTLS specs                                                                                                                                                                                                            |
| spec.fep.monitoring.prometheus.tls.certificateName    | ( created by user ) | This is an Optional parameter. These points to Kubernetes TLS secret that contains the certificate of Prometheus. FEPEXporter will use this for certificate authentication. The certificate itself is stored in the key tls.crt. |
| spec.fep.monitoring.prometheus.tls.caName             | ( created by user ) | This is an Optional parameter. This point to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt.                                                 |
| spec.fep.externalMonitoring.cloudWatch                |                     | This is an Optional section.<br>Define this option when linking with CloudWatch.                                                                                                                                                 |
| spec.fep.externalMonitoring.cloudWatch.enable         | true                | Optional<br>A value of true forwards Fujitsu Enterprise Postgres metrics to CloudWatch.<br>Specify false to cancel log transfer.                                                                                                 |
| spec.fep.externalMonitoring.cloudWatch.schedule       | "0-59/10 * * * *"   | You can specify how often to transfer. Specified as a Cron value.                                                                                                                                                                |
| spec.fep.externalMonitoring.cloudWatch.namespace      |                     | Specifies the CloudWatch Namespace to which metrics are forwarded.<br>Required if spec.fep.externalMonitoring.cloudWatch is specified                                                                                            |
| spec.fep.externalMonitoring.cloudWatch.defaultMetrics | true                | Specify true to capture and forward the metrics described in "Metrics Collected by CloudWatch" in the User's Guide.<br>Specify false to forward only custom metrics to CloudWatch.                                               |
| spec.fep.externalMonitoring.cloudWatch.customMetrics  |                     | Optional<br>If you want to forward custom metrics, specify the ConfigMap name where you defined the custom metrics.                                                                                                              |
| spec.fep.externalMonitoring.cloudWatch.dimensionName  |                     | Optional                                                                                                                                                                                                                         |

| Field                                                                       | Default  | Details                                                                                                                                                                                                     |
|-----------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                             |          | <p>If adding a Dimension, specify a name of your choice.</p> <p>If dimensionValue is omitted, this value is ignored.</p>                                                                                    |
| spec.fep.externalMonitoring.cloudWatch.dimensionValue                       |          | <p>Optional</p> <p>If adding a Dimension, specify any value.</p> <p>If dimensionName is omitted, this value is ignored.</p>                                                                                 |
| spec.fep.externalMonitoring.cloudWatch.authentication.cloudWatchCredentials |          | <p>Specify a secret name that defines a credentials for a role that has permission to forward metrics to CloudWatch.</p> <p>Required if spec.fep.externalMonitoring.cloudWatch is specified</p>             |
| spec.fep.externalMonitoring.cloudWatch.authentication.cloudWatchConfig      |          | <p>Specify a ConfigMap name that defines the config information for a role that has permission to forward metrics to CloudWatch.</p> <p>Required if spec.fep.externalMonitoring.cloudWatch is specified</p> |
| spec.fep.externalMonitoring.cloudWatch.databases                            | postgres | <p>Specifies the databases from which to collect metrics, in list format.</p> <p>The default is to collect metrics from the postgres database.</p>                                                          |
| spec.fep.podAntiAffinity                                                    | false    | Defines that all the pods should not run on same worker node                                                                                                                                                |
| spec.fep.podDisruptionBudget                                                | false    | Allows to maintain minimum number of pods of an application even when some nodes are voluntarily drained for say, maintenance                                                                               |
| spec.fep.replicationSlots                                                   |          | List of Patroni permanent replication slots.                                                                                                                                                                |
| spec.fep.replicationSlots.demo_subscription1                                |          | The 'demo_subscription1' is the slot name. This name cannot be same as any pod name (e.g., new-fep-sts-01) in the cluster. Otherwise, the slot will not be created.                                         |
| spec.fep.replicationSlots.type                                              | logical  | Must be 'logical' for logical replication                                                                                                                                                                   |
| spec.fep.replicationSlots.database                                          | postgres | Specify the database name for logical replication                                                                                                                                                           |
| spec.fep.replicationSlots.plugin                                            | pgoutput | FEP supports 'pgoutput' by default.                                                                                                                                                                         |
| spec.fep.usePodName                                                         |          | <p>Optional</p> <p>Setting this key to true will make internal POD communication, both Patroni and Postgres to use hostname,</p>                                                                            |

| Field                                    | Default             | Details                                                                                                                                                                                                                                                                                                                        |
|------------------------------------------|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                          |                     | instead of IP address. This is important for TLS as the hostname of the POD is predictable and can be used to create Server Certificate, whereas IP address is unpredictable and cannot be used to create Certificate. There is no negative effect setting this key to true even if TLS (i.e. Server Certificate) is not used. |
| spec.fep.patroni.tls.certificateName     | ( created by user ) | Optional<br>This point to Kubernetes TLS secret that contains the certificate for Patroni. The certificate itself is stored in the key tls.crt. This field is optional.<br><br>When this key is set, the Operator will ignore the value in systemCertificates                                                                  |
| spec.fep.patroni.tls.caName              | ( created by user ) | Optional<br>This points to Kubernetes configmap that contains additional CA for Patroni to verify client. The CA is stored in the key ca.crt. This field is optional.                                                                                                                                                          |
| spec.fep.postgres.tls.certificateName    | ( created by user ) | Optional<br>This points to Kubernetes TLS secret that contains the certificate for Postgres. The certificate itself is stored in the key tls.crt. This field is optional. When this key is set, Operator will ignore the value in systemCertificates                                                                           |
| spec.fep.postgres.tls.caName             | ( created by user ) | Optional<br>This point to Kubernetes configmap that contains additional CA for Postgres to verify client. The CA is stored in the key ca.crt. This field is optional.                                                                                                                                                          |
| spec.fep.postgres.tls.privateKeyPassword | ( created by user ) | Optional<br>This points to Kubernetes secret that contains the password for the above private key. This field is optional.                                                                                                                                                                                                     |
| spec.fep.pgAuditLog.auditLogPath         |                     | Use this value for log_directory in pgaudit.conf<br><br>If pgAuditLog.auditLogPath is not defined:<br><br>use '/database/log/audit'<br><br>or '/database/userdata/data/log' when log volume is not defined .                                                                                                                   |
| spec.fep.pgAuditLog.schedules            |                     | Schedule to upload auditlog                                                                                                                                                                                                                                                                                                    |
| spec.fep.pgAuditLog.schedules.upload     |                     | Upload schedule in crontab format                                                                                                                                                                                                                                                                                              |
| spec.fep.pgAuditLog.endpoint.protocol    | http                | Optional<br><br>Default: http<br>Supported values:                                                                                                                                                                                                                                                                             |

| Field                                              | Default | Details                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                    |         | <ul style="list-style-type: none"> <li>- 'http'</li> <li>- 's3'</li> <li>- 'blob'</li> </ul>                                                                                                                                                                                                                                                                                                                                                       |
| spec.fep.pgAuditLog.endpoint.url                   |         | Webserver URL to upload the auditlog files                                                                                                                                                                                                                                                                                                                                                                                                         |
| spec.fep.pgAuditLog.endpoint.customCertificateName |         | Optional Secret that contains the certificate to setup communication with Web server                                                                                                                                                                                                                                                                                                                                                               |
| spec.fep.pgAuditLog.endpoint.insecure              | false   | Optional equivalent to curl -insecure option                                                                                                                                                                                                                                                                                                                                                                                                       |
| spec.fep.pgAuditLog.endpoint.authentication        |         | <p>Optional</p> <p>This item is the secret name for endpoint authentication.</p> <p>The end user needs to provide this secret to use upload feature.</p> <p>This secret is used for authentication of each protocol accordingly.</p> <p>Refer to "<a href="#">1.2.16.1 Details of pgAuditLog.endpoint.authentication</a>" for details.</p> <p>If this is not specified, a default secret &lt;cluster-name&gt;-pgauditlog-auth will be created.</p> |
| spec.fep.pgAuditLog.endpoint.fileUploadParameter   | file    | Optional<br>The file upload parameter defined by the web server                                                                                                                                                                                                                                                                                                                                                                                    |
| spec.fep.pgAuditLog.endpoint.azureBlobName         |         | <p>Only take effect when protocol is 'blob'</p> <p>Optional</p> <p>The blob name of pgaudit log file.</p> <p>Default:<br/>[cluster name]-sts-[pod index]-pgauditlog.zip</p>                                                                                                                                                                                                                                                                        |
| spec.fep.pgAuditLog.endpoint.azureContainerName    |         | <p>Required with protocol is 'blob'</p> <p>This item is the container name of the Azure Storage account</p>                                                                                                                                                                                                                                                                                                                                        |
| spec.fep.pgAuditLog.config                         |         | <p>Optional</p> <p>Default: none</p> <p>This item requires a ConfigMap with this name to exist in the same namespace of the FEPCluster.</p> <p>The ConfigMap will be used as pgAudit config file.</p> <p>The ConfigMap need to have a key 'pgaudit.conf'.</p>                                                                                                                                                                                      |
| spec.fep.pgAuditLog.enable                         |         | <p>Optional</p> <p>Default: false</p> <p>When set to 'true', the pgaudit extension is enabled automatically.</p>                                                                                                                                                                                                                                                                                                                                   |
| spec.fep.pgBadger.schedules.create                 |         | The 'create' schedule to create report and upload it to endpoint                                                                                                                                                                                                                                                                                                                                                                                   |

| Field                                            | Default | Details                                                                                                                                                                                                                                                                                    |
|--------------------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.pgBadger.schedules.cleanup              |         | The 'cleanup' schedule to delete the report left in container                                                                                                                                                                                                                              |
| spec.fep.pgBadger.options.incremental            | false   | Default: false; When set to true: create incremental report in pgbadger                                                                                                                                                                                                                    |
| spec.fep.pgBadger.endpoint.authentication        |         | a secret to contain authentication info to access endpoint<br>support basic auth only                                                                                                                                                                                                      |
| spec.fep.pgBadger.endpoint.customCertificateName |         | Client certificate reference in customCertificate CR                                                                                                                                                                                                                                       |
| spec.fep.pgBadger.endpoint.fileUploadParameter   | file    | The file upload parameter defined by the web server                                                                                                                                                                                                                                        |
| spec.fep.pgBadger.endpoint.insecure              | false   | equivalent to curl -insecure option                                                                                                                                                                                                                                                        |
| spec.fep.pgBadger.endpoint.url                   |         | Web server url to upload the report file                                                                                                                                                                                                                                                   |
| spec.ldap2pg.enable                              | true    | Setting this to "true" will enable ldap2pg to execute periodically according to schedule defined.<br><br>Setting this to "false" will remove the cronjob that execute the ldap2pg.                                                                                                         |
| spec.ldap.caConfigMapRef                         |         | If LDAP server certificate is signed by a private CA, this key should point to a configmap that has the chain of certificates that ldap2pg and FEP should trust.<br><br>Operator expects the key name in the configmap be ca.crt.                                                          |
| spec.ldap.ldapconfSecretRef                      |         | Name of secret that contains the ldap.conf<br><br>When spec.ldap is defined but spec.ldap.ldapconfSecretRef is not defined, operator will create a default secret <fep-cluster>-ldapconf.<br><br>Operator expects the key name in the secret be ldap.conf.                                 |
| spec.ldap2pg.ldap2pgyamlConfigMapRef             |         | Name of configmap that contains the ldap2pg.yml<br><br>When spec.ldap2pg is defined but spec.ldap2pg.ldap2pgyamlConfigMapRef is not defined, Operator will create a default configmap <fep-cluster>-ldap2pgyaml.<br><br>FEP Operator expects the key name in the configmap be ldap2pg.yml. |
| spec.ldap2pg.mode                                | check   | Whether ldap2pg should run in "check" mode or "real" mode. If not defined, ldap2pg will run in check mode.                                                                                                                                                                                 |

| Field                                        | Default   | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.ldap2pg.schedule                        |           | <p>Schedule to execute ldap2pg in a crontab format.</p> <p>If defined, Operator will create a cronjob using fep-cronjob container and remotely execute ldap2pg on fep-patroni container on a regular basis.</p> <p>If the schedule is not provided, Operator will set the schedule to 5/* * * *.</p>                                                                                                                                                                              |
| spec.ldap2pg.skipPrivileges                  | false     | <p>Options</p> <p>Configure synchronization of role attributes and permissions between ldap2pg and FEPCluster.</p> <p>Specify false if you want to synchronize role attributes with permissions, or true if you do not.</p> <p>If true, the behavior is the same as the --skip-privileges (-P) option of the ldap2pg command.</p>                                                                                                                                                 |
| spec.fep.feputils.image                      | <omitted> | <p>FEPUtills container image to use, quay.io/fujitsu/fujitsu-enterprise-postgres-18-utils:ubi9-18-1.0</p> <p>Optional.</p> <p>Omitted by default. In this case, the image URL is obtained from the operator container environment.</p> <p>If you specify an image, the operator will use that image to deploy the Utils container.</p> <p>When fepChildCrVal.storage.autoresize.enable is true, use this image to expand the pvc-auto-resize container of the fep-tuning Pod.</p> |
| spec.fep.fepcronjob.image                    | <omitted> | <p>FEPCronjob container image to use, quay.io/fujitsu/fujitsu-enterprise-postgres-cronjob:ubi9-18-1.0</p> <p>Optional.</p> <p>Omitted by default. In this case, the image URL is obtained from the operator container environment.</p> <p>If you specify an image, the operator will use that image to deploy the Cronjob container.</p>                                                                                                                                          |
| spec.fep.autoTuning.prometheus.prometheusUrl |           | <p>Required if fepChildCrVal.storage.autoresize.enable is true.</p> <p>Specifies the URL of the Prometheus for which you want to retrieve metrics.</p>                                                                                                                                                                                                                                                                                                                            |

| Field                                                 | Default | Details                                                                                                                                                                                                                    |
|-------------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.autoTuning.prometheus.authSecret             |         | Optional<br>Basic authentication secret that provides the user name and encrypted password                                                                                                                                 |
| spec.fep.autoTuning.prometheus.authSecret.secretName  |         | Username and password, or the name of the secret that contains the token                                                                                                                                                   |
| spec.fep.autoTuning.prometheus.authSecret.userKey     |         | Key of the Secret given the user name                                                                                                                                                                                      |
| spec.fep.autoTuning.prometheus.authSecret.passwordKey |         | Key of the Secret with the password specified                                                                                                                                                                              |
| spec.fep.autoTuning.prometheus.authSecret.tokenKey    |         | Key of the Secret given the token                                                                                                                                                                                          |
| spec.fep.autoTuning.prometheus.authSecret.proxyKey    |         | Key of the Secret specified by the proxy                                                                                                                                                                                   |
| spec.fep.autoTuning.prometheus.tls                    |         |                                                                                                                                                                                                                            |
| spec.fep.autoTuning.prometheus.tls.certificateName    |         | Refers to the Kubernetes TLS secret that contains the certificate and private key. Prometheus uses this for certificate authentication. The certificate and private key itself are stored in the tls.crt and tls.key keys. |
| spec.fep.autoTuning.prometheus.tls.caName             |         | Refers to the Kubernetes ConfigMap containing the additional CA that the client uses to verify the server certificate. The CA is stored in the ca.crt key.                                                                 |
| spec.fep.autoTuning.prometheus.maxRetry               |         | Specifies the maximum number of retries when a query to Prometheus fails.<br><br>If not specified, a maximum of 60 retries are attempted.                                                                                  |
| spec.fep.velero.enable                                | false   | Optional<br>Specifies whether the Velero DR feature is used (true) or not (false).<br><br>This is omitted by default. In this case, the Velero DR feature is not available.                                                |
| spec.fep.velero.labels                                |         | Optional<br>If the Velero DR feature is used, specify the label to be given to the resource to be backed up by Velero.<br><br>You can specify multiple labels.<br><br>If omitted, backup-group: fep-backup is given.       |
| spec.fep.velero.backup                                |         | Specifies the object storage information that stores the backup data and archive wal for FEPCluster to be built in a DR environment.                                                                                       |

| Field                                      | Default      | Details                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                            |              | Otherwise, FEPCluster built in a DR environment will fail to back up to object storage.                                                                                                                                                                                                                                                                                                                                          |
| spec.fep.velero.backup.pgbackrestParams    |              | <p>" " When nothing is specified, and the parameter set in pgbackrest.conf is described from the line below.<br/>(Descriptions vary depending on the provider used)</p> <p>If you use the same object storage as in production, specify a different object storage path (repo*-path) than fepChildCrVal.backup.pgbackrestParams.</p> <p>If you specify the same object storage path, you will receive an event notification.</p> |
| spec.fep.velero.backup.pgbackrestKeyParams |              | <p>Optional</p> <p>" " is fixed, and the following line describes the parameters to be set in pgbackrest.conf. The value described by this parameter is masked with *****.</p>                                                                                                                                                                                                                                                   |
| spec.fep.velero.backup.caName              |              | <p>Optional</p> <p>Set to use a CA file other than the system default. Specifies the name of the Configmap you created.</p> <p>If you use a different CA file than the production environment, give the CA file a different name and set it here. It must also be deployed in the DR environment.</p>                                                                                                                            |
| spec.fep.velero.backup.repoKeySecretName   |              | <p>Optional</p> <p>Specifies the name of the Kubernetes Secret generated from the object storage key file. Specify in array format.</p> <p>If you use a different secret from the production environment, give the secret a different name and set it here. It must also be deployed in the DR environment.</p>                                                                                                                  |
| spec.fep.velero.restore.image.image        |              | <p>Optional</p> <p>Image of the container to perform the restore. It is omitted by default. In this case, the URL for image is obtained from the operator container environment.</p>                                                                                                                                                                                                                                             |
| spec.fep.velero.restore.image.pullPolicy   | IfNotPresent | <p>Specifies the pull policy for the image.</p> <ul style="list-style-type: none"> <li>- Always</li> <li>- IfNotPresent</li> </ul>                                                                                                                                                                                                                                                                                               |

| Field                                       | Default                    | Details                                                                                                                                                                                                                                      |
|---------------------------------------------|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.velero.restore.mcSpec.limit        | cpu: 200m<br>memory: 300Mi | Specifies the maximum number of resources to allocate to the restore execution container.                                                                                                                                                    |
| spec.fep.velero.restore.mcSpec.request      | cpu: 100m<br>memory: 200Mi | Specifies the lower number of resources to allocate to the restore execution container.                                                                                                                                                      |
| spec.fep.velero.restore.restoreTargetRepo   | 1                          | Specifies the backup data used to restore FEPCluster to the DR environment and the object storage information where the archive wal is stored.<br><br>This is the number of the repo in <code>fepChildCrVal.backup.pgbackrestParams</code> . |
| spec.fep.fixedStats.scheduleN               |                            | Schedule a locked statistics.<br>Specify an integer for N.                                                                                                                                                                                   |
| spec.fep.fixedStats.scheduleN.fixSchedule   |                            | Time to start locked statistics.<br>schedule in cron format<br>The date and time are in UTC time.                                                                                                                                            |
| spec.fep.fixedStats.scheduleN.unfixSchedule |                            | Options<br>Time to unpin locked statistics. Returns to regular statistics. If not specified, it is not cleared.<br>schedule in cron format<br>The date and time are in UTC time.                                                             |
| spec.fep.fixedStats.scheduleN.targetDb      |                            | Specify the database for which you want to locked statistics.                                                                                                                                                                                |
| spec.fep.fixedStats.scheduleN.fixedObject   |                            | Options<br>If the scope to be locked is smaller than the database, specify that object.<br>Specify <code>schema.table.column</code> .<br>The minimum range is the column and the maximum range is the schema.                                |
| spec.fep.fixedStats.endpoint.protocol       |                            | Specify the object storage vendor where statistics are stored. s3, blob, gcs can be specified. Also, if you want to directly import a file on the container, specify local.                                                                  |
| spec.fep.fixedStats.endpoint.authentication |                            | Specify this option if the protocol is s3, blob, gcs.<br><br>Authentication for accessing object storage Specify a secret file that contains confidential information.                                                                       |
| spec.fep.fixedStats.scheduleN.url           |                            | Specify this option if the protocol is s3, gcs.                                                                                                                                                                                              |

| Field                                            | Default      | Details                                                                                                                                                                                    |
|--------------------------------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                  |              | Specify the URL from which to download the statistics binary file.                                                                                                                         |
| spec.fep.fixedStats.scheduleN.azureBlobName      |              | Specify this if the protocol is a blob. Name of the blob containing the statistics binary file.                                                                                            |
| spec.fep.fixedStats.scheduleN.azureContainerName |              | Specify this if the protocol is a blob. This item is the container name of the Azure storage account.                                                                                      |
| spec.fep.fixedStats.scheduleN.file               |              | Specify this if the protocol is a local. Specify the name of the file deployed on the fep-patropni container.                                                                              |
| spec.fep.fixedStats.scheduleN.update             | false        | Set this setting to true if you want to download statistics to be locked from object storage.                                                                                              |
| spec.fep.fixedStats.image                        |              | The CronJob image to use. If not specified, the operator uses the latest version supported by the operator.                                                                                |
| spec.fep.fixedStats.pullPolicy                   | IfNotPresent |                                                                                                                                                                                            |
| spec.fep.fixedStats.scheduleN.enable             |              | Options<br>You can specify whether scheduled statistics are to be locked or released. Executed if omitted or true, not if false.                                                           |
| spec.fep.freezingTuples.enable                   | false        | Options<br>When true is specified, enables periodic execution of freezing operations.                                                                                                      |
| spec.fep.freezingTuples.scheduleN                |              | Options<br>Specifies the schedule for the freeze operation. You can specify multiple names in dictionary format.<br>Specify an integer for N.                                              |
| spec.fep.freezingTuples.scheduleN.start          | 0 1 * * *    | Specifies the date and time for starting processing in cron format.<br>If omitted, the default values are applied.                                                                         |
| spec.fep.freezingTuples.scheduleN.executionTime  | 3600         | Options<br>Specified value: string<br>Units: s, m, h, d<br>Specifies the duration of the processing. If no unit is specified, s is assumed.<br>If omitted, the default values are applied. |
| spec.fep.backupStats.enable                      | false        | You can set statistics to be backed up.<br>If set to false, no backup is performed.<br>If set to true, backup is performed.                                                                |

| Field                                         | Default      | Details                                                                                                                                                                                                                                                                               |
|-----------------------------------------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                               |              | <p>If spec.fep.backupStats.enable is not defined as false when FEPCluster is first built, it is set to true.</p> <p>If spec.fep.backupStats.schedule1 is not defined when FEPCluster is first built, a backup with default settings is defined in the FEPCluster custom resource.</p> |
| spec.fep.backupStats.image                    |              | The CronJob image to use. If not specified, the operator uses the latest version supported by the operator.                                                                                                                                                                           |
| spec.fep.backupStats.pullPolicy               | IfNotPresent |                                                                                                                                                                                                                                                                                       |
| spec.fep.backupStats.scheduleN                |              | <p>Schedule a backup of the statistics.</p> <p>Specify an integer for N.</p>                                                                                                                                                                                                          |
| spec.fep.backupStats.scheduleN.backupSchedule |              | <p>Time to start taking statistics backups.</p> <p>schedule in cron format</p> <p>The date and time are in UTC time.</p>                                                                                                                                                              |
| spec.fep.backupStats.scheduleN.targetDb       |              | <p>Optional</p> <p>Specify the database to be backed up. If omitted, runs for all databases.</p>                                                                                                                                                                                      |
| spec.fep.backupStats.scheduleN.fixedObject    |              | <p>Optional</p> <p>If the backup target is less than the database, specify the object.</p> <p>Specify schema.table.column.</p> <p>The minimum range is the column and the maximum range is the schema.</p>                                                                            |
| spec.fep.backupStats.scheduleN.comment        |              | <p>Optional</p> <p>Comments that can be defined when backing up statistics.</p> <p>If omitted, FepFixedStatsBackup: scheduleN is set.</p> <p>Do not use the following phrases in comments.</p> <p>FepFixedStats</p>                                                                   |
| spec.fep.backupStats.scheduleN.retention      |              | <p>Options</p> <p>At the same time as a scheduled backup, you can delete backups that are stored in the target database for a specified number of days or earlier.</p> <p>Specify an integer.</p> <p>If omitted, no deletion is performed.</p>                                        |
| spec.fep.backupStats.scheduleN.enable         |              | <p>Options</p> <p>You can specify whether scheduled statistics are to be locked or released.</p> <p>Executed if omitted or true, not if false.</p>                                                                                                                                    |

| Field                                                              | Default | Details                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.multiMasterReplication                                    | -       | Options<br>Define the multi-master replication configuration.                                                                                                                                                                                                                                                      |
| spec.fep.hostName                                                  |         | If you created an SVC to accept connections from outside your deployed Kubernetes cluster, specify the hostname.                                                                                                                                                                                                   |
| spec.fep.port                                                      |         | This is the port used to connect to the deployed Kubernetes from outside.                                                                                                                                                                                                                                          |
| spec.fep.multiMasterReplication.enable                             | false   | Enable the construction of a multi-master replication configuration.<br>Once enabled by setting this to true, the feature cannot be disabled.                                                                                                                                                                      |
| spec.fep.multiMasterReplication.configMapName                      |         | Specify the ConfigMap name defining the FEPCluster or database for bidirectional replication.                                                                                                                                                                                                                      |
| spec.fep.multiMasterReplication.replicationHosts[]                 |         | Specify the information for the FEPCluster(s) for bidirectional replication in array format.<br>Only one array can be specified.                                                                                                                                                                                   |
| spec.fep.multiMasterReplication.replicationHosts[].hostName        |         | Specify the connectable hostname.                                                                                                                                                                                                                                                                                  |
| spec.fep.multiMasterReplication.replicationHosts[].port            | 27500   | Options<br>Specify the port of the host that can be connected to.                                                                                                                                                                                                                                                  |
| spec.fep.multiMasterReplication.replicationHosts[].pgAdminPassword |         | Specifies the password for the postgres user at the replication destination.<br>After applying to the FEPCluster, this parameter is masked with *.                                                                                                                                                                 |
| spec.fepChildCrVal.customCertificates                              |         | Optional<br>An array of elements for defining a certificate. It consists of the following parameters:<br><ul style="list-style-type: none"> <li>- username</li> <li>- certificateName</li> <li>- caName</li> </ul> Used to setup SSL connection between publisher and subscriber clusters for logical replication. |
| spec.fepChildCrVal.customCertificates.userName                     |         | Optional<br>This should be the username of the publisher database. When this parameter is specified, an empty folder is created under FEP Server Container- /tmp/custom_certs/<username>. The custom certificates are mounted in this empty folder.                                                                |

| Field                                                 | Default                                                                            | Details                                                                                                                                                                                                                                                                                                                                                |
|-------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                       |                                                                                    | However, if this parameter is not specified, the section is ignored and folder is not created; hence the certificates are not mounted without it.                                                                                                                                                                                                      |
| spec.fepChildCrVal.customCertificates.certificateName | ( created by user )                                                                | Optional<br>This points to Kubernetes TLS secret that contains the custom certificate. The certificate itself is stored in the key tls.crt.                                                                                                                                                                                                            |
| spec.fepChildCrVal.customCertificates.caName          | ( created by user )                                                                | Optional<br>This points to Kubernetes configmap that contains CA certificate to verify server. The CA is stored in the key ca.crt.                                                                                                                                                                                                                     |
| spec.fepChildCrVal.backup                             |                                                                                    | Optional<br>This section is defined to enable febackup sidecar for cluster backup feature.                                                                                                                                                                                                                                                             |
| spec.fepChildCrVal.backup.image.image                 | <omitted>                                                                          | FEP backup container image to be used<br>quay.io/fujitsu/fujitsu-enterprise-postgres-18-backup:ubi9-18-1.0<br><br>It is optional.<br><br>Image line is omitted by default. In such a case, it will pick up URL of image from operator container environment.<br><br>If you specify the image, Operator will take that image to deploy backup container |
| spec.fepChildCrVal.backup.image.pullPolicy            | IfNotPresent                                                                       |                                                                                                                                                                                                                                                                                                                                                        |
| spec.fepChildCrVal.backup.mcSpec.limits               | cpu: 0.2<br>memory: "300Mi"                                                        |                                                                                                                                                                                                                                                                                                                                                        |
| spec.fepChildCrVal.backup.mcSpec.requests             | cpu: 0.1<br>memory: "200Mi"                                                        |                                                                                                                                                                                                                                                                                                                                                        |
| spec.fepChildCrVal.backup.type                        |                                                                                    | Optional<br>Specifiable value: local<br><br>Apply the settings for taking a backup to the PV to the custom resource.<br><br>Can only be set the first time the FEPCluster custom resource is applied. You cannot add or change settings after applying.                                                                                                |
| spec.fepChildCrVal.backup.pgbackrestParams            | (If spec.fepChildCrVal.backup.type is local)<br>[global]<br>repo1-retention-full=7 | Specifies the object storage information that stores the backup data and archive wal.                                                                                                                                                                                                                                                                  |

| Field                                         | Default                                                                                                                            | Details                                                                                                                                                                                                                         |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                               | repo1-retention-full-type=time<br>log-path=/database/log/backup                                                                    | " " When nothing is specified, and the parameter set in pgbackrest.conf is described from the line below.<br><br>The value described by this parameter is masked with *****. (Descriptions vary depending on the provider used) |
| spec.fepChildCrVal.backup.pgbackrestKeyParams |                                                                                                                                    | Optional<br><br>" " is fixed, and the following line describes the parameters to be set in pgbackrest.conf. The value described by this parameter is masked with *****.                                                         |
| spec.fepChildCrVal.backup.caName              |                                                                                                                                    | Optional<br><br>Set to use a CA file other than the system default.<br><br>Specifies the name of the Configmap you created.                                                                                                     |
| spec.fepChildCrVal.backup.repoKeySecretName   |                                                                                                                                    | Optional<br><br>Specifies the name of the Kubernetes Secret generated from the object storage key file. Specify in array format.                                                                                                |
| spec.fepChildCrVal.backup.schedule.num        | 0<br><br>(If spec.fepChildCrVal.backup.type is local)<br>2                                                                         | Number of schedules to set<br><br>The maximum number of backup schedules is 5.                                                                                                                                                  |
| spec.fepChildCrVal.backup.scheduleN.schedule  | (If spec.fepChildCrVal.backup.type is local)<br><br>schedule1:<br>schedule: "15 0 * * 0"<br>schedule2:<br>schedule: "15 0 * * 1-6" | Backup schedule in cron format.<br><br>The date and time is UTC time.                                                                                                                                                           |
| spec.fepChildCrVal.backup.scheduleN.type      | (If spec.fepChildCrVal.backup.type is local)<br><br>schedule1:<br>type: full<br>schedule2:<br>type: incr                           | full: Perform a full backup (Back up the contents of the database cluster).<br><br>incr — Perform an incremental backup (Back up only the database cluster files that were changed to the last backup migration).               |
| spec.fepChildCrVal.backup.scheduleN.repo      | 1                                                                                                                                  | Optional<br><br>Gets a backup in the specified repository.<br><br>The range is 1 to 256.                                                                                                                                        |
| spec.fepChildCrVal.customPgAudit              | [output]<br><br>logger = 'auditlog'<br><br>log_directory = '/database/log/audit'<br><br>log_truncate_on_rotation = on              | PgAudit file content                                                                                                                                                                                                            |

| Field                             | Default                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                   | log_filename = 'pgaudit-%a.log'<br>log_rotation_age = 1d<br>log_rotation_size = 0<br>[rule]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| spec.fepChildCrVal.customPgHba    | # define pg_hba custom rules here to be merged with default rules.<br><br># TYPE DATABASE USER ADDRESS METHOD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Entries to be inserted into pg_hba.conf                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| spec.fepChildCrVal.customPgParams | # define custom postgresql.conf parameters below to override defaults.<br><br># Current values are as per default FEP deployment<br>shared_preload_libraries='pgx_datamasking,pg_prewarm,pg_stat_statements,fsep_operator_security'<br>session_preload_libraries='pg_prewarm'<br>max_prepared_transactions = 100<br>max_worker_processes = 30<br>max_connections = 100<br>work_mem = 1MB<br>maintenance_work_mem = 12MB<br>shared_buffers = 128MB<br>effective_cache_size = 384MB<br>checkpoint_completion_target = 0.8<br># tcp parameters<br>tcp_keepalives_idle = 30<br>tcp_keepalives_interval = 10<br>tcp_keepalives_count = 3<br># logging parameters in default fep installation<br># if log volume is not defined, log_directory should be<br># changed to '/database/userdata/data/log'<br>log_directory = '/database/log'<br>log_filename = 'logfile-%a.log'<br>log_file_mode = 0600<br>log_truncate_on_rotation = on<br>log_rotation_age = 1d<br>log_rotation_size = 0<br>log_checkpoints = on<br>log_line_prefix = '%e %t [%p]: [%l-1] user=%u,db=%d,app=%a,client=%h' | Postgres configuration in postgresql.conf<br><br>If the FEP server container utilizes images with a FEPBaseVersion less than 15, exclude fsep_operator_security from the configuration.<br><br>If spec.fep.databaseSize is defined, the default value will be changed as shown below.<br><br>shared_buffers = 30% of spec.fep.mcSpec.limits.memory<br><br>work_mem = 30% of spec.fep.mcSpec.limits.memory / max_connections / 2<br><br>effective_cache_size = 75% of spec.fep.mcSpec.limits.memory<br><br>maintenance_work_mem = 10% of spec.fep.mcSpec.limits.memory / (1 + autovacuum_max_workers) |

| Field                                                              | Default                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Details                                                                                                       |
|--------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
|                                                                    | log_lock_waits = on<br>log_autovacuum_min_duration = 60s<br>logging_collector = on<br>pgaudit.config_file='/opt/app-root/src/pgaudit-cfg/pgaudit.conf'<br>log_replication_commands = on<br>log_min_messages = WARNING<br>log_destination = stderr<br># wal_archive parameters in default fep installation<br>archive_mode = on<br>archive_command = 'pgbackrest --stanza=backupstanza --config=/database/userdata/pgbackrest.conf archive-push %p'<br>wal_level = replica<br>max_wal_senders = 12<br>wal_keep_segments = 64<br>track_activities = on<br>track_counts = on<br>password_encryption = 'md5' |                                                                                                               |
| spec.fep.vectorTransformation.enable                               | false                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Setting to true activates the feature of model management in the database.                                    |
| spec.fep.vectorTransformation.modelRepository.modelOwner.name      | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Set the model owner's name.                                                                                   |
| spec.fep.vectorTransformation.modelRepository.modelOwner.password  | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Set the model owner's password.                                                                               |
| spec.fep.vectorTransformation.modelRepository.modelUser.name       | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Set the model user's name.                                                                                    |
| spec.fep.vectorTransformation.modelRepository.modelUser.password   | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Set the model user's password.                                                                                |
| spec.fep.vectorTransformation.modelRepository.modelLoader.name     | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Set the load user's name.                                                                                     |
| spec.fep.vectorTransformation.modelRepository.modelLoader.password | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Set the load user's password.                                                                                 |
| spec.fep.vectorTransformation.inferenceServer                      | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Parameters related to the inference server.                                                                   |
| spec.fep.vectorTransformation.inferenceServer.image                | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Required when spec.fep.vectorTransformation.enable is true<br>Specify the name of the built inference server. |
| spec.fep.vectorTransformation.inferenceServer.imagePullsecret      | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Required when spec.fep.vectorTransformation.enable is true                                                    |

| Field                                                                                             | Default                  | Details                                                                                                                                                    |
|---------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                   |                          | Specify the Pullsecret to access the repository where the built inference server is published.                                                             |
| spec.fep.vectorTransformation.inferenceServer.connectionTls.enable                                | false                    | Set to true when using mTLS.                                                                                                                               |
| spec.fep.vectorTransformation.inferenceServer.connectionTls.certificate.grpcCaName                | -                        | Specifies the TLS secret used for gRPC connections.                                                                                                        |
| spec.fep.vectorTransformation.inferenceServer.connectionTls.certificate.grpcCertificateName       | -                        | Specify the Secret name containing the CA certificate used to verify the server certificate chain for gRPC connections.                                    |
| spec.fep.vectorTransformation.inferenceServer.connectionTls.certificate.grpcPrivateKey            | -                        | Specifies the Kubernetes secret containing the password for the private key used for gRPC connections.                                                     |
| spec.fep.vectorTransformation.inferenceServer.connectionTls.certificate.tritonGrpcCaName          | -                        | Specifies the TLS secret used for gRPC connections configured on the Triton server.                                                                        |
| spec.fep.vectorTransformation.inferenceServer.connectionTls.certificate.tritonGrpcCertificateName | -                        | Specify the Secret name containing the CA certificate used to verify the server certificate chain for gRPC connections configured on the Triton server.    |
| spec.fep.vectorTransformation.inferenceServer.connectionTls.certificate.tritonGrpcPrivateKey      | -                        | Specify the secret name containing the CA certificate used to verify the server certificate chain for the gRPC connection configured on the Triton server. |
| spec.fep.vectorTransformation.inferenceServer.mcSpec.limits                                       | cpu:500m<br>memory:1Gi   | Specifies the resource limit for the inference server.                                                                                                     |
| spec.fep.vectorTransformation.inferenceServer.mcSpec.limits.requests                              | cpu:200m<br>memory:512Mi | Specifies the minimum resources required by the inference server.                                                                                          |
| spec.fep.vectorTransformation.inferenceServerPorts.grpcPort                                       | -                        | Required when spec.fep.vectorTransformation.enable is true.<br><br>Specifies the port number for gRPC connections.                                         |
| spec.fep.vectorTransformation.inferenceServerPorts.metricsPort                                    | -                        | Required when spec.fep.vectorTransformation.enable is true.<br><br>Specifies the port number for acquiring metrics.                                        |
| spec.fepChildCrVal.storage.dataVol                                                                |                          | Mandatory volume                                                                                                                                           |
| spec.fepChildCrVal.storage.dataVol.size                                                           | 2Gi<br>(**)              | Size of data volume.<br><br>Data volume must be specified                                                                                                  |
| spec.fepChildCrVal.storage.dataVol.storageClass                                                   | <omitted><br>(*)         | StorageClass for data volume:<br><br>When this line is omitted, the PV created will use default storage class in the Kubernetes cluster                    |

| Field                                                 | Default                                                                                                                                 | Details                                                                                                                                                 |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepChildCrVal.storage.dataVol.accessModes        | <omitted><br>(*)                                                                                                                        | accessModes for data volume:<br>Specified as an array of accessModes<br>e.g. [ReadWriteMany]<br>If omitted, it will be treated as [ReadWriteOnce]       |
| spec.fepChildCrVal.storage.walVol                     |                                                                                                                                         | Mandatory volume                                                                                                                                        |
| spec.fepChildCrVal.storage.walVol.size                | 1200Mi<br>(**)<br><br>(If spec.fepChildCrVal.storage.dataSize is defined)<br>5Gi                                                        | Size of WAL volume.<br>WAL volume must be specified                                                                                                     |
| spec.fepChildCrVal.storage.walVol.storageClass        | <omitted><br>(*)                                                                                                                        | StorageClass for WAL volume:<br>When this line is omitted, the PV created will use default storage class in the Kubernetes cluster                      |
| spec.fepChildCrVal.storage.walVol.accessModes         | <omitted><br>(*)                                                                                                                        | accessModes for WAL volume:<br>Specified as an array of accessModes<br>e.g. [ReadWriteMany]<br>If omitted, it will be treated as [ReadWriteOnce]        |
| spec.fepChildCrVal.storage.tablespaceVol              |                                                                                                                                         | Optional volume                                                                                                                                         |
| spec.fepChildCrVal.storage.tablespaceVol.size         | 512Mi<br>(**)<br><br>(If spec.fepChildCrVal.storage.dataSize is defined)<br>The value specified in spec.fepChildCrVal.storage.dataSize. | Size of tablespace volume.<br>This volume is optional and can be omitted                                                                                |
| spec.fepChildCrVal.storage.tablespaceVol.storageClass | <omitted><br>(*)                                                                                                                        | StorageClass for tablespace volume:<br>When this line is omitted, the PV created will use default storage class in the Kubernetes cluster               |
| spec.fepChildCrVal.storage.tablespaceVol.accessModes  | <omitted><br>(*)                                                                                                                        | accessModes for tablespace volume:<br>Specified as an array of accessModes<br>e.g. [ReadWriteMany]<br>If omitted, it will be treated as [ReadWriteOnce] |
| spec.fepChildCrVal.storage.archiveWalVol              |                                                                                                                                         | Mandatory if backup section is defined.<br>Optional otherwise                                                                                           |
| spec.fepChildCrVal.storage.archiveWalVol.size         | 1Gi<br>(**)                                                                                                                             | Size of archivewal volume.<br>This volume is optional and can be omitted                                                                                |

| Field                                                  | Default                                                                                                                                        | Details                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                        | (If spec.fepChildCrVal.storage.dataSize is defined and sepc.fepChildCrVal.backup.type is local)<br>(spec.fepChildCrVal.storage.dataSize/10)*14 |                                                                                                                                                                                                                                                                                                                                                                     |
| spec.fepChildCrVal.storage.archive walVol.storageClass | <omitted><br>(*)                                                                                                                               | StorageClass for Archived WAL volume:<br><br>When this line is omitted, the PV created will use default storage class in the Kubernetes cluster<br><br>When the number of instance is more than 1 and backup is not done on S3, both archivewalVol and backupVol must be hosted on Shared storage such as NFS with respective storageClass                          |
| spec.fepChildCrVal.storage.archive walVol.accessModes  | <omitted><br>(*)                                                                                                                               | accessModes for Archived WAL volume:<br><br>Specified as an array of accessModes e.g. [ReadWriteMany]<br><br>If omitted, it will be treated as [ReadWriteOnce]<br><br>When the number of instance is more than 1 and backup is not done on S3, both archivewalVol and backupVol must be hosted on Shared storage such as NFS with accessMode set to [ReadWriteMany] |
| spec.fepChildCrVal.storage.logVol                      |                                                                                                                                                | Optional volume                                                                                                                                                                                                                                                                                                                                                     |
| spec.fepChildCrVal.storage.logVol.size                 | 1Gi<br>(**)<br><br>(If spec.fepChildCrVal.storage.dataSize is defined)<br>5Gi                                                                  | Size of log volume.<br><br>This volume is optional and can be omitted                                                                                                                                                                                                                                                                                               |
| spec.fepChildCrVal.storage.logVol.storageClass         | <omitted><br>(*)                                                                                                                               | StorageClass for log volume:<br><br>When this line is omitted, the PV created will use default storage class in the Kubernetes cluster                                                                                                                                                                                                                              |
| spec.fepChildCrVal.storage.logVol.accessModes          | <omitted><br>(*)                                                                                                                               | accessModes for log volume:<br><br>Specified as an array of accessModes e.g. [ReadWriteMany]<br><br>If omitted, it will be treated as [ReadWriteOnce]                                                                                                                                                                                                               |
| spec.fepChildCrVal.storage.backupVol                   |                                                                                                                                                | Mandatory if backup section is defined.<br><br>Optional otherwise                                                                                                                                                                                                                                                                                                   |
| spec.fepChildCrVal.storage.backupVol.size              | 2Gi                                                                                                                                            | Size of backup volume.                                                                                                                                                                                                                                                                                                                                              |

| Field                                             | Default                                                                                                                                               | Details                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                   | (**)<br><br>(If spec.fepChildCrVal.storage.dataSize is defined and sepc.fepChildCrVal.backup.type is local)<br>spec.fepChildCrVal.storage.dataSize*14 | This volume is optional and can be omitted                                                                                                                                                                                                                                                                                                                  |
| spec.fepChildCrVal.storage.backupVol.storageClass | <omitted><br>(*)                                                                                                                                      | StorageClass for backup volume:<br><br>When this line is omitted, the PV created will use default storage class in the Kubernetes cluster<br><br>When the number of instance is more than 1 and backup is not done on S3, both archivalVol and backupVol must be hosted on Shared storage such as NFS with respective storageClass                          |
| spec.fepChildCrVal.storage.backupVol.accessModes  | <omitted><br>(*)                                                                                                                                      | accessModes for backup volume:<br><br>Specified as an array of accessModes e.g. [ReadWriteMany]<br><br>If omitted, it will be treated as [ReadWriteOnce]<br><br>When the number of instance is more than 1 and backup is not done on S3, both archivalVol and backupVol must be hosted on Shared storage such as NFS with accessMode set to [ReadWriteMany] |
| sepc.fepChildCrVal.storage.dataSize               |                                                                                                                                                       | Specify the amount of data at the data storage destination.<br>The operator defines the size of dataVol, walVol, logVol, tablespaceVol, archivalVol, and backupVol based on the specified value.<br><br>If you specify individual volumes, specify the size of each volume definition.                                                                      |
| sepc.fepChildCrVal.storage.accessModes            |                                                                                                                                                       | Specify the accessModes for each volume if you want to specify them in a batch.<br>If you want to set them individually, specify the accessModes for each volume definition.                                                                                                                                                                                |
| sepc.fepChildCrVal.storage.storageClass           |                                                                                                                                                       | Specify the storageClass for each volume if you want to specify them in a batch.<br>If you want to set them individually, specify the storageClass for each volume definition.                                                                                                                                                                              |
| spec.fepChildCrVal.storage.autoresize             |                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                             |

| Field                                                 | Default                  | Details                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepChildCrVal.storage.autoresize.enable          | false                    | Optional<br>Specified value: boolean<br>true to enable auto-extension for PVCs.                                                                                                                                                                                                                                                                                               |
| spec.fepChildCrVal.storage.autoresize.mcSpec.limits   | cpu: 50m<br>memory: 60Mi | Optional<br>Specifies the resource limit that can be allocated to pvc-auto-resize container.                                                                                                                                                                                                                                                                                  |
| spec.fepChildCrVal.storage.autoresize.mcSpec.requests | cpu: 10m<br>memory: 5Mi  | Optional<br>Specifies the resources to assign that can be allocated to pvc-auto-resize container.                                                                                                                                                                                                                                                                             |
| spec.fepChildCrVal.storage.autoresize.interval        | 30                       | Optional<br>Units: s<br>Specifies the interval between metric checks.<br>If 0 or less is specified, the PVC is not extended.                                                                                                                                                                                                                                                  |
| spec.fepChildCrVal.storage.autoresize.threshold       | 80                       | Optional<br>Specified value: integer<br>Unit:%<br>Specifies the storage utilization threshold.<br>Extends the PVC when this value is exceeded.<br>When 0 is specified, storage utilization is not checked.<br>The xxxVol.threshold applies to all storage that is not defined.                                                                                                |
| spec.fepChildCrVal.storage.autoresize.increaseType    | percent                  | Optional<br>Specified value: percent, size<br>Specifies how the PVC extension is estimated when the threshold is exceeded.<br>When percent is specified<br>Expands the PVC by the specified percentage of its original capacity.<br>If size is specified<br>Extends the PVC by the specified amount (Gi).<br>Applies to all storage where xxxVol.increaseType is not defined. |
| spec.fepChildCrVal.storage.autoresize.increase        | 25                       | Optional<br>Specified value: integer<br>Units:% or Gi                                                                                                                                                                                                                                                                                                                         |

| Field                                              | Default | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                    |         | <p>Specifies the extension amount for the PVC.</p> <p>The units depend on the value specified for increaseType.</p> <p>If a value less than or equal to 0 is specified, no extension is performed.</p> <p>This applies to all storage where xxxVol.increase is not defined.</p>                                                                                                                                                                                                |
| spec.fepChildCrVal.storage.autoresize.storageLimit |         | <p>Optional</p> <p>Specified value: integer</p> <p>Units: Gi</p> <p>Specifies the maximum value by which the PVC can be extended.</p> <p>If not specified, the extension is unrestricted. If you do not specify this value, we recommend that you verify that the storage class being used has a namespace quota.</p> <p>Do not extend the PVC when less than or equal to disk space is specified.</p> <p>Applies to all storage where xxxVol.storageLimit is not defined.</p> |
| spec.fepChildCrVal.storage.xxxVol                  |         | xxx is the contents of data, wal, log, tablespace, archivewal, backup                                                                                                                                                                                                                                                                                                                                                                                                          |
| spec.fepChildCrVal.storage.xxxVol.threshold        |         | <p>Optional</p> <p>Specified value: integer</p> <p>Unit:%</p> <p>Specifies the storage utilization threshold.</p> <p>Extends the PVC when this value is exceeded.</p> <p>When 0 is specified, storage utilization is not checked.</p> <p>If not specified, it follows the value specified in autoresize.threshold.</p>                                                                                                                                                         |
| spec.fepChildCrVal.storage.xxxVol.increaseType     |         | <p>Optional</p> <p>Specified value: percent, size</p> <p>Specifies how the PVC extension is estimated when the threshold is exceeded.</p> <p>When percent is specified</p> <p>Expands the PVC by the specified percentage of its original capacity.</p> <p>If size is specified</p>                                                                                                                                                                                            |

| Field                                                                        | Default | Details                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------------------------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                              |         | <p>Extends the PVC by the specified amount (Gi).</p> <p>If not specified, the value specified by <code>autoresize.increaseType</code>.</p>                                                                                                                                                                                      |
| <code>spec.fepChildCrVal.storage.xxxVol.increase</code>                      |         | <p>Optional</p> <p>Specified value: integer</p> <p>Units: % or Gi</p> <p>Specifies the extension amount for the PVC.</p> <p>The units depend on the value specified for <code>increaseType</code>.</p> <p>If not specified, the value specified by <code>autoresize.increase</code>.</p>                                        |
| <code>spec.fepChildCrVal.storage.xxxVol.storageLimit</code>                  |         | <p>Optional</p> <p>Specified value: integer</p> <p>Units: Gi</p> <p>Specifies the maximum capacity by which the PVC can be extended.</p> <p>Do not expand if the specification is less than or equal to the disk capacity.</p> <p>If not specified, it follows the value specified by <code>autoresize.storageLimit</code>.</p> |
| <code>spec.fepChildCrVal.storage.inferenc<br/>eVol.size</code>               | -       | <p>Required when <code>spec.fep.vectorTransformation.enable.enable</code> is true</p> <p>Specifies the size of the model to mount.</p>                                                                                                                                                                                          |
| <code>spec.fepChildCrVal.storage.inferenc<br/>eVol.storageClass</code>       | -       | <p>Required when <code>spec.fep.vectorTransformation.enable.enable</code> is true</p> <p>Specifies the name of the storage class to mount.</p>                                                                                                                                                                                  |
| <code>spec.fepChildCrVal.storage.inferenc<br/>eVol.accessMode</code>         | -       | <p>Required when <code>spec.fep.vectorTransformation.enable.enable</code> is true</p> <p>Specifies the access mode for the storage to mount.</p>                                                                                                                                                                                |
| <code>spec.fepChildCrVal.storage.modelRe<br/>positoryVol.size</code>         | -       | <p>Required when <code>spec.fep.vectorTransformation.enable.enable</code> is true</p> <p>Specifies the size of the model to mount.</p>                                                                                                                                                                                          |
| <code>spec.fepChildCrVal.storage.<br/>modelRepositoryVol.storageClass</code> | -       | <p>Required when <code>spec.fep.vectorTransformation.enable.enable</code> is true</p>                                                                                                                                                                                                                                           |

| Field                                                    | Default         | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                          |                 | Specifies the name of the storage class to mount.                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| spec.fepChildCrVal.storage.modelRepositoryVol.accessMode | -               | <p>Required when spec.fep.vectorTransformation.enable.enable is true</p> <p>Specifies the access mode for the storage to mount.</p>                                                                                                                                                                                                                                                                                                                                                    |
| spec.fepChildCrVal.sysUsers.pgAdminPassword              | <omitted>       | <p>Password for user "postgres"</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), symbols (~! @ # \$% ^ &amp; * () - = &lt; &gt; . , ? ; :   / +)</p> <p>If this parameter is omitted, the Operator automatically generates a password.</p> <p>If the FEP server container uses an image with a FEPBaseVersion less than 15, be sure to specify this parameter.</p>                                                                          |
| spec.fepChildCrVal.sysUsers.pgdb                         | mydb<br>(*)     | <p>Database to be created during provisioning</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), and underscores (_)</p> <p>However, you cannot start with a number.</p> <p>Upper case letters are treated as lower case letters.</p> <p>Maximum string length</p> <p>63 characters</p>                                                                                                                                                       |
| spec.fepChildCrVal.sysUsers.pguser                       | mydbuser<br>(*) | <p>Database user to be created during provisioning</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), and underscores (_)</p> <p>However, you cannot start with a number.</p> <p>Upper case letters are treated as lower case letters.</p> <p>Maximum string length</p> <p>63 characters</p> <p>This database user is the owner of the database defined in "spec.fepChildCrVal.sysUsers.pgdb" and has the role of database administrator.</p> |

| Field                                            | Default         | Details                                                                                                                                                                                                                                                                                                                     |
|--------------------------------------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                  |                 | <p>This user has the following privileges:.</p> <p>NOSUPERUSER,<br/>NOREPLICATION,<br/>NOBYPASSRLS, CREATEDB,<br/>INHERIT, LOGIN, CREATEROLE</p> <p>(NOCREATEROLE when<br/>spec.fepChildCrVal.sysUsers.pgSecurityUser is defined)</p> <p>They also belong to the following roles:.</p> <p>pg_monitor, pg_signal_backend</p> |
| spec.fepChildCrVal.sysUsers.pgpassword           | mydbpassword    | <p>Password for database user pguser</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), symbols (~! @ # \$% ^ &amp; * () - = &lt; &gt; . ? ; :  /+)</p>                                                                                                                            |
| spec.fepChildCrVal.sysUsers.pgrepuser            | repluser<br>(*) | <p>Database user for replication</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), and underscores (_)</p> <p>However, you cannot start with a number.</p> <p>Maximum string length</p> <p>63 characters</p>                                                                      |
| spec.fepChildCrVal.sysUsers.pgreppassword        | repluserpwd     | Alphanumeric characters                                                                                                                                                                                                                                                                                                     |
| spec.fepChildCrVal.sysUsers.tdepassword          | tde-passphrase  | TDE keystore passphrase                                                                                                                                                                                                                                                                                                     |
| spec.fepChildCrVal.sysUsers.pgRewindUser         | rewind_user     | <p>Database user for Rewind</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), and underscores (_)</p> <p>However, you cannot start with a number.</p> <p>Maximum string length</p> <p>63 characters</p>                                                                           |
| spec.fepChildCrVal.sysUsers.pgRewindUserPassword | rewind_password | <p>Password for database user rewinduser</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), symbols (~! @ # \$% ^ &amp; * () - = &lt; &gt; . ? ; :  /+)</p>                                                                                                                        |
| spec.fepChildCrVal.sysUsers.pgMetricsUser        |                 | <p>Optional</p> <p>user for FEPEXporter connection. Can be defined afterwards</p> <p>Available character types</p>                                                                                                                                                                                                          |

| Field                                             | Default | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                   |         | <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), and underscores (_)</p> <p>However, you cannot start with a number.</p> <p>Upper case letters are treated as lower case letters.</p> <p>Maximum string length</p> <p>63 characters</p>                                                                                                                                                                                                                          |
| spec.fepChildCrVal.sysUsers.pgMetricsUserPassword |         | <p>Optional</p> <p>Password for metrics user. Can be defined afterwards</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), symbols (~! @ # \$% ^ &amp; * () - = &lt; &gt; , . ? ; :  /+)</p>                                                                                                                                                                                                                                  |
| spec.fepChildCrVal.sysUsers.pgSecurityUser        |         | <p>Options</p> <p>Username of the security administrator user. Can be defined later.</p> <p>This parameter is optional, but cannot be changed or deleted after it has been defined.</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), and underscores (_)</p> <p>However, you cannot start with a number.</p> <p>Upper case letters are treated as lower case letters.</p> <p>Maximum string length</p> <p>63 characters</p> |
| spec.fepChildCrVal.sysUsers.pgSecurityPassword    |         | <p>Options</p> <p>Defines the password for the sensitive administrator user.</p> <p>This parameter is optional but required when "pgSsecurityUser" is defined.</p> <p>Available character types</p> <p>Alphanumeric characters (A-Z, a-z), numbers (0 -9), symbols (~! @ # \$% ^ &amp; * () - = &lt; &gt; , . ? ; :  /+)</p>                                                                                                                                           |
| spec.fepChildCrVal.sysUsers.passwordValid         |         | <p>Options</p> <p>Manage password expiration for database users.</p> <p>Sets the expiration date for database user passwords defined in the FEPCluster custom resource below.</p>                                                                                                                                                                                                                                                                                      |

| Field                                                               | Default | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                     |         | <ul style="list-style-type: none"> <li>- pgpassword, pgSecurityPassword</li> </ul> <p>In addition, if <code>shared_preload_libraries</code> in <code>customPgParams</code> is set to <code>"fsep_operator_security"</code> and the <code>"CREATE ROLE"</code> or <code>"ALTER ROLE"</code> command is used to update the password of a database user with login privileges and the expiration time is not defined or is longer than the specified expiration time, the operation will fail.</p> <p>Updates the password expiration date for database users with login privileges that have not expired when the specified expiration date is updated.</p> |
| <code>spec.fepChildCrVal.sysUsers.passwordValid.days</code>         |         | <p>Options</p> <p>Specifies the number of days the database role is valid.</p> <p>Specify an integer value greater than or equal to 0.</p> <p>If any other value is entered, it is treated as 0 (no expiration date is set).</p> <p>The 'days' option is not available when using the Cloud-based Secret Management feature.</p> <p>When you take advantage of the Cloud-based Secret Management feature, the database user password expiration can be managed by a rotation policy provided by an external secret store service.</p>                                                                                                                     |
| <code>spec.fepChildCrVal.sysUsers.pgAdminTls.certificateName</code> |         | <p>This points to Kubernetes TLS secret that contains the certificate of Postgres user "postgres". Patroni will use this for certificate authentication. The certificate itself is stored in the key <code>tls.crt</code>. This field is optional.</p>                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>spec.fepChildCrVal.sysUsers.pgAdminTls.caName</code>          |         | <p>This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key <code>ca.crt</code>. This field is optional.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>spec.fepChildCrVal.sysUsers.pgAdminTls.sslMode</code>         | prefer  | <p>Specify the type of TLS negotiation with the server.</p> <ul style="list-style-type: none"> <li>- disable</li> <li>- allow</li> <li>- prefer</li> <li>- require</li> <li>- verify-ca</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

| Field                                                            | Default | Details                                                                                                                                                                                                                                  |
|------------------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                  |         | - verify-full                                                                                                                                                                                                                            |
| spec.fepChildCrVal.sysUsers.pgrep1<br>UserTls.certificateName    |         | This points to Kubernetes TLS secret that contains the certificate of Postgres user "repluser". Patroni will use this for certificate authentication. The certificate itself is stored in the key tls.crt. This field is optional.       |
| spec.fepChildCrVal.sysUsers.pgrep1<br>UserTls.caName             |         | This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt. This field is optional.                                                               |
| spec.fepChildCrVal.sysUsers.pgrep1<br>UserTls.sslMode            | prefer  | Specify the type of TLS negotiation with the server.<br><br><ul style="list-style-type: none"> <li>- disable</li> <li>- allow</li> <li>- prefer</li> <li>- require</li> <li>- verify-ca</li> <li>- verify-full</li> </ul>                |
| spec.fepChildCrVal.sysUsers.pgRew<br>indUserTls.certificateName  |         | This points to Kubernetes TLS secret that contains the certificate of Postgres user "rewinduser". Patroni will use this for certificate authentication. The certificate itself is stored in the key tls.crt. This field is optional.     |
| spec.fepChildCrVal.sysUsers.pgRew<br>indUserTls.caName           |         | This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt. This field is optional.                                                               |
| spec.fepChildCrVal.sysUsers.pgRew<br>indUserTls.sslMode          | prefer  | Specify the type of TLS negotiation with the server.<br><br><ul style="list-style-type: none"> <li>- disable</li> <li>- allow</li> <li>- prefer</li> <li>- require</li> <li>- verify-ca</li> <li>- verify-full</li> </ul>                |
| spec.fepChildCrVal.sysUsers.pgMetr<br>icsUserTls.certificateName |         | Optional<br>This points to Kubernetes TLS secret that contains the certificate of Postgres user defined by pgMetricsUser. FEPEXporter will use this for certificate authentication. The certificate itself is stored in the key tls.crt. |

| Field                                                     | Default | Details                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepChildCrVal.sysUsers.pgMetricsUserTls.caName       |         | Optional<br>This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt.                                                                                                                                                                                                                                                                     |
| spec.fepChildCrVal.sysUsers.pgMetricsUserTls.sslMode      | prefer  | Optional<br>Specify the type of TLS negotiation when FEPEXporter connects to FEP server.<br><br><ul style="list-style-type: none"> <li>- disable</li> <li>- allow</li> <li>- prefer</li> <li>- require</li> <li>- verify-ca</li> <li>- verify-full</li> </ul>                                                                                                                                                                      |
| spec.fepChildCrVal.sysUsers.vectorizerPassword            |         | Optional<br>Specifies the password for "vectorizerrole," which will be created as the database role used by the automatic vector converter to perform vector conversions in the background.<br><br>Available character types<br><br>Alphanumeric characters (A-Z, a-z), numbers (0-9), symbols (~! @ # \$% ^ & * () - = < > . , ? ; :   / +)<br><br>If this parameter is omitted, the Operator automatically generates a password. |
| spec.fepChildCrVal.sysUsers.vectorizerTls.certificateName |         | This points to Kubernetes TLS secret that contains the certificate of Postgres user "vectorizerrole". Patroni will use this for certificate authentication. The certificate itself is stored in the key tls.crt. This field is optional.                                                                                                                                                                                           |
| spec.fepChildCrVal.sysUsers.vectorizerTls.caName          |         | This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt. This field is optional.                                                                                                                                                                                                                                                         |
| spec.fepChildCrVal.sysUsers.vectorizerTls.sslMode         | prefer  | Specify the type of TLS negotiation with the server.<br><br><ul style="list-style-type: none"> <li>- disable</li> <li>- allow</li> <li>- prefer</li> <li>- require</li> <li>- verify-ca</li> </ul>                                                                                                                                                                                                                                 |

| Field                                                      | Default | Details                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                            |         | - verify-full                                                                                                                                                                                                                                                                                      |
| spec.fepChildCrVal.sysTde                                  | (*)     | Optional<br>If the user selects a file-based TDE, you do not need to define it.<br>Required when implementing TDE with a key management system (KMS).                                                                                                                                              |
| spec.fepChildCrVal.sysTde.tdeType                          | (*)     | Optional<br>The parameter itself is optional, but required when spec.fepChildCrVal.sysTde is defined. Specify tdek.                                                                                                                                                                                |
| spec.fepChildCrVal.sysTde.tdek                             |         | Optional<br>Defines the connection information to the KMS.<br>Required when tdek is specified for spec.fepChildCrVal.sysTde.tdeType.                                                                                                                                                               |
| spec.fepChildCrVal.sysTde.tdek.targetKmsName               |         | Specify one of the key management system names defined in kmsDefinition[*].name as the name of the key management system to use as the keystore.                                                                                                                                                   |
| spec.fepChildCrVal.sysTde.tdek.targetKeyId                 |         | Specifies the key ID (Identifier attribute in KMIP) attached to the encryption key in KMS.<br>When you update this parameter, the Operator automatically updates the master key.                                                                                                                   |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition               |         | Specifies KMS connection information.<br>Specify in array format. You can specify connection information for multiple KMS.                                                                                                                                                                         |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].name       | (*)     | The name given to the KMS (key management system name) specified in spec.fepChildCrVal.sysTde.tdek.targetKmsName.<br>The KMS name must be a string of no more than 63 characters beginning with a-z, consisting of a-z, numbers (0-9), and underscores. Upper and lower case letters are the same. |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].type       | (*)     | Specifies the type of KMS.<br>You can specify either kmip, awskms, or azurekeyvault.                                                                                                                                                                                                               |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].address    | (*)     | Specifies the host name or IP address of the KMIP server.                                                                                                                                                                                                                                          |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].port       | (*)     | Specifies the port of KMIP server.                                                                                                                                                                                                                                                                 |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].authMethod | (*)     | Specifies the authentication method in KMIP server.                                                                                                                                                                                                                                                |

| Field                                                                         | Default | Details                                                                                                                                                                              |
|-------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                               |         | Currently, the only possible value is cert.                                                                                                                                          |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].sslpassphrase                 |         | Optional<br>Specifies the passphrase of the client certificate private key file when connecting to KMIP server. This can be omitted if no passphrase is set in the private key file. |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].cert                          |         | Optional<br>Specifies the name of the Secret/ ConfigMap containing the certificate file, etc., when cert is specified as authMethod.                                                 |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].cert.certificateName          | (*)     | Specifies the TLS Secret name that contains the client certificate and private key for TLS communication with KMIP server.                                                           |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].cert.caName                   | (*)     | Specifies the ConfigMap name that contains the file name of the SSL Certificate Authority certificate. Used to verify the server certificate of the connection destination.          |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].profile                       |         | Specify a profile that uses AWS KMS. For more information about profile, see the official AWS documentation.                                                                         |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].awsKmsCredentials             |         | Specify a Secret that contains credentials (access key id and secret access key) to AWS KMS.                                                                                         |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].awsKmsConfig                  |         | Specify a ConfigMap that contains configuration information for the AWS KMS CLI.                                                                                                     |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].appid                         |         | Enter the application ID when using Azure Key Vault. You can get this when you create a service principal.                                                                           |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].tenantid                      |         | Specify tenantid when using Azure Key Vault. You can get this when you create a service principal.                                                                                   |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].encAlgorithm                  |         | Specifies when using Azure Key Vault. See the appendix for the algorithms you can select, refer to "Available Algorithms" in the User's Guide.                                       |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].azureKeyVaultClientPassphrase |         | Used to authenticate to Azure Key Vault. Specifies the secret that contains the client Secret (password).                                                                            |
| spec.fepChildCrVal.sysTde.tdek.kmsDefinition[*].azureKeyVaultClientCert       |         | Used to authenticate to Azure Key Vault. Specifies the Secret that contains the client certificate.                                                                                  |
| spec.fepChildCrVal.systemCertificates.key                                     |         | Use spec.fep.postgres.tls specification instead.                                                                                                                                     |

| Field                                                            | Default                        | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------------------------------|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepChildCrVal.systemCertificates.crt                        |                                | Use spec.fep.postgres.tls specification instead.                                                                                                                                                                                                                                                                                                                                                                                                                                |
| spec.fepChildCrVal.systemCertificates.cacrt                      |                                | Use spec.fep.postgres.tls specification instead.                                                                                                                                                                                                                                                                                                                                                                                                                                |
| spec.fepChildCrVal.autoscale.scaleout.policy                     | off                            | Specifies whether to use the automatic scale out feature and the metric to base on.<br><br>Specify one of the following:<br><ul style="list-style-type: none"> <li>- cpu_utilization (if based on CPU utilization)</li> <li>- connection_number (if based on number of connections)</li> <li>- off (without automatic scale out)</li> </ul> If omitted, off is assumed.                                                                                                         |
| spec.fepChildCrVal.autoscale.scaleout.threshold                  | 40                             | Specifies an integer as the threshold for performing scale out.<br><ul style="list-style-type: none"> <li>- When cpu_utilization is specified for policy<br/>Specifies the average CPU utilization as a percentage for the threshold. If this option is omitted, 40 (40%) is assumed.</li> <li>- When connection_number is specified for policy<br/>Specifies the average value of the number of connections as a threshold. If you omit this option, 40 is assumed.</li> </ul> |
| spec.fepChildCrVal.autoscale.scaleout.metricName                 | pg_capacity_connection_average | Specify this parameter if policy is connection_number. Ignored if policy is cpu_utilization.<br><br>The custom metrics server must publish the average number of connections in the FEP cluster under this name.<br><br>If omitted, pg_capacity_connection_average is assumed.                                                                                                                                                                                                  |
| spec.fepChildCrVal.autoscale.scaleout.stabilizationWindowSeconds | 0                              | This parameter controls the stability of scaling (variation in the number of replicas). Scale out is not performed unless the metric exceeds the threshold for more than the number of seconds specified for this parameter.<br><br>If omitted, 0 is assumed.                                                                                                                                                                                                                   |
| spec.fepChildCrVal.autoscale.limits.maxReplicas                  | 2                              | Maximum number of replicas (0 to 15)<br><br>(Value out of range)<br><br>Do not perform auto scale out                                                                                                                                                                                                                                                                                                                                                                           |
| spec.fepChildCrVal.restore                                       |                                | Optional<br><br>Defines to restore specified backup data stored in object storage.                                                                                                                                                                                                                                                                                                                                                                                              |

| Field                                          | Default                    | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------------------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepChildCrVal.restore.pgbackrestParams    |                            | <p>Optional</p> <p>" " is fixed, and the following line describes the parameters to be set in pgbackrest.conf.</p> <p>Specifies the object storage where the backup data is stored.</p> <p>If you need to use a root certificate other than the default, specify the following:</p> <pre>repo1-storage-ca-path =/pgbackrest/storage-certs/filename</pre> <p>The CA file is registered in ConfigMap and the ConfigMap name is listed in spec.fepChildCrVal.restore.caName.</p> |
| spec.fepChildCrVal.restore.pgbackrestKeyParams |                            | <p>Optional</p> <p>" " is fixed, and the following line describes the parameters to be set in pgbackrest.conf. The value described by this parameter is masked with *****. Specify the parameter you want to mask, such as a password.</p>                                                                                                                                                                                                                                    |
| spec.fepChildCrVal.restore.caName              |                            | <p>Optional</p> <p>Set to use a CA file other than the system default.</p> <p>Specifies the name of the ConfigMap created, in list format.</p> <p>The ConfigMap specified is mounted in /pgbackrest/storage-certs.</p>                                                                                                                                                                                                                                                        |
| spec.fepChildCrVal.restore.repoKeySecretName   |                            | <p>Optional</p> <p>Specifies the name of the Kubernetes Secret generated from the object storage key file.</p> <p>Specify in array format. The specified Secret will be mounted in /pgbackrest/storage-key.</p>                                                                                                                                                                                                                                                               |
| spec.fepChildCrVal.restore.mcSpec.limits       | cpu: 200m<br>memory: 300Mi | <p>Optional</p> <p>CPU and memory allocated to the container performing the restore</p>                                                                                                                                                                                                                                                                                                                                                                                       |
| spec.fepChildCrVal.restore.mcSpec.requests     | cpu: 100m<br>memory: 200Mi | <p>Optional</p> <p>CPU and memory allocated to the container performing the restore</p>                                                                                                                                                                                                                                                                                                                                                                                       |
| spec.fepChildCrVal.restore.restoretype         | latest                     | <p>Optional</p> <p>Select the type of restore (latest or PITR).</p>                                                                                                                                                                                                                                                                                                                                                                                                           |
| spec.fepChildCrVal.restore.restoredate         |                            | <p>Optional</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

| Field                                                       | Default                    | Details                                                                                                                                                                     |
|-------------------------------------------------------------|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                             |                            | Specifies the date to restore when spec.fepChildCrVal.restore.restoretype is "PITR".                                                                                        |
| spec.fepChildCrVal.restore.restoretime                      |                            | Optional<br>Specifies the time to restore when spec.fepChildCrVal.restore.restoretype is "PITR".                                                                            |
| spec.fepChildCrVal.restore.image                            |                            | Optional<br>Image of the container to perform the restore<br>It is omitted by default. In this case, the URL for image is obtained from the operator container environment. |
| spec.fepChildCrVal.restore.imagePullPolicy                  | IfNotPresent               | Optional                                                                                                                                                                    |
| spec.fepChildCrVal.upgrade                                  |                            | Optional<br>When this field is defined, a major version upgrade is performed.<br>However, if spec.fepChildCrVal.restore is defined, the FEPCluster build stops.             |
| spec.fepChildCrVal.upgrade.sourceCluster                    |                            | Specifies the FEPClusterCR name from which to migrate data.<br>Required if spec.fepChildCrVal.upgrade is defined.                                                           |
| spec.fepChildCrVal.upgrade.mcspec.limits                    | cpu: 200m<br>memory: 300Mi | Optional<br>Specifies the maximum number of resources to allocate to the upgrade execution container.                                                                       |
| spec.fepChildCrVal.upgrade.mcspec.requests                  | cpu: 100m<br>memory: 200Mi | Optional<br>Specifies the lower limit of resources allocated to the upgrade execution container.                                                                            |
| spec.fepChildCrVal.upgrade.image                            |                            | Optional<br>By default, the URL of image is obtained from the operator container environment.                                                                               |
| spec.fepChildCrVal.upgrade.imagePullPolicy                  | IfNotPresent               | Optional<br>Specifies the pull policy for the container image.<br>- Always<br>- IfNotPresent<br>- Never                                                                     |
| spec.fepChildCrVal.upgrade.sourcePgAdminTls.certificateName |                            | Optional                                                                                                                                                                    |

| Field                                                                          | Default       | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                |               | <p>If you do not define <code>spec.fepChildCrVal.sysUsers.pgAdminTls.certificateName</code> for the data source, it points to the Kubernetes TLS secret that contains the certificate for the Postgres user "postgres" in the data source.</p> <p>If the data source FEP has set the authentication method for the upgrade execution container to "cert", then the upgrade execution container uses the certificate defined as secret.</p>                         |
| <code>spec.fepChildCrVal.upgrade.destination.pgAdminTls.certificateName</code> |               | <p>Optional</p> <p>If you have not defined the <code>spec.fepChildCrVal.sysUsers.pgAdminTls.certificateName</code> of the newly created FEPCluster, it points to the Kubernetes TLS secret that contains the certificate of the Postgres user "postgres" in the data source.</p> <p>If you create a new FEP with the "cert" authentication method for the upgrade execution container, the upgrade execution container uses the certificate defined as secret.</p> |
| <code>spec.fepChildCrVal.upgrade.storage</code>                                |               | <p>Optional</p> <p>Defines the storage for storing dump files.</p>                                                                                                                                                                                                                                                                                                                                                                                                 |
| <code>spec.fepChildCrVal.upgrade.storage.storageClass</code>                   |               | <p>Optional</p> <p>If omitted, the default storage class for your environment is used.</p>                                                                                                                                                                                                                                                                                                                                                                         |
| <code>spec.fepChildCrVal.upgrade.storage.size</code>                           | 2Gi           | <p>Optional</p> <p>Specifies the size of the storage to store the dump file.</p>                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>spec.fepChildCrVal.upgrade.storage.accessModes</code>                    | ReadWriteOnce | <p>Optional</p> <p><code>accessModes</code> for store the dump file</p> <p>Specified as an array of <code>accessModes</code> e.g. <code>[ReadWriteMany]</code></p> <p>If omitted, it will be treated as <code>[ReadWriteOnce]</code></p>                                                                                                                                                                                                                           |
| <code>spec.fep.remoteLogging.enable</code>                                     |               | Set to true to forward logs from fluentbit to fluentd                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>spec.fep.remoteLogging.image</code>                                      |               | <p>Optional</p> <p>Fluentbit image to be used. If not specified, Operator will use the latest version that is supported by the Operator.</p>                                                                                                                                                                                                                                                                                                                       |
| <code>spec.fep.remoteLogging.pullPolicy</code>                                 | IfNotPresent  | Optional                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

| Field                                              | Default | Details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.remoteLogging.fluentdName                 |         | Optional<br>The name of the FEPLogging CR to which logs are transferred.<br>Specify this option to use the FEPLogging function to transfer logs.                                                                                                                                                                                                                                                                                                                                                                               |
| spec.fep.remoteLogging.tls.certificateName         |         | Optional<br>Kubernetes secret name which holds fluentbit certificate. FEPLogging will use this for certificate authentication. The certificate itself is stored in the key tls.crt.                                                                                                                                                                                                                                                                                                                                            |
| spec.fep.remoteLogging.tls.caName                  |         | Optional<br>Kubernetes configmap which holds cacert of Fluentd to which fluentbit will use to perform MTLs.                                                                                                                                                                                                                                                                                                                                                                                                                    |
| spec.fep.remoteLogging.mcSpec.limits.cpu           | 50m     | Optional<br>CPU allocation limit for fluentbit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| spec.fep.remoteLogging.mcSpec.limits.memory        | 60Mi    | Optional<br>Memory allocation limit for fluentbit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| spec.fep.remoteLogging.mcSpec.requests.cpu         | 10m     | Optional<br>CPU allocation request for fluentbit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| spec.fep.remoteLogging.mcSpec.requests.memory      | 5Mi     | Optional<br>Memory allocation request for fluentbit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| spec.fep.remoteLogging.fluentbitParams.memBufLimit | 5MB     | Optional<br>Defines the Mem_Buf_Limit in Fluentbit. This will affect all sections that use this parameter.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| spec.fep.remoteLogging.fluentbitConfigSecretRef    |         | Optional<br>Specifies the name of the secret containing fluent-bit.yaml when using the log transfer feature with remote logging.<br><br>If fluentbitConfigSecretRef is not defined, or if fluentbitConfigSecretRef is defined but the referenced secret does not exist, the operator creates a default Secret <fep-cluster>-fluent-bit-conf and updates this parameter with <fep-cluster>-fluent-bit-conf.<br><br>If the referenced secret exists, the named secret is mounted to fep-logging-fluent-bit under/fluent-bit/etc. |
| spec.fep.remoteLogging.awsCredentialSecretRef      |         | Optional                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

| Field                                                          | Default | Details                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                |         | <p>Specify the name of the Secret that contains authentication information to the AWS service.</p> <p>Authentication information stores configuration files and authentication information files.</p> <p>The configuration file must be named "config" and the credentials file must be named "credentials".</p> <p>If the referenced secret exists, the named secret is mounted to fep-logging-fluent-bit under/fluent-bit/aws.</p> |
| spec.fepChildCrVal.secretStore.csi.providerName                |         | <p>Optional</p> <p>Provider name. Can be one of the following:</p> <p>Azure/AWS/GCP/Vault.</p> <p>Must be "Azure" or "azure" in case of azure provider</p>                                                                                                                                                                                                                                                                           |
| spec.fepChildCrVal.secretStore.csi.azureProvider.credentials   |         | <p>Optional</p> <p>Secret created by User that contains the required credentials to connect to Azure keyvault</p>                                                                                                                                                                                                                                                                                                                    |
| spec.fepChildCrVal.secretStore.csi.azureProvider.tenantid      |         | <p>Optional</p> <p>Tenant id where keyvault is created</p>                                                                                                                                                                                                                                                                                                                                                                           |
| spec.fepChildCrVal.secretStore.csi.azureProvider.keyvaultName  |         | <p>Optional</p> <p>Name of the keyvault where secrets are stored</p>                                                                                                                                                                                                                                                                                                                                                                 |
| spec.fepChildCrVal.secretStore.csi.azureProvider.fepSecrets    |         | <p>Optional</p> <p>List of the parameters and their corresponding secret created in the Vault</p> <p>Eg:<br/>&lt;fep parameter name&gt;: &lt;secret in keyvault&gt;</p>                                                                                                                                                                                                                                                              |
| spec.fepChildCrVal.secretStore.csi.azureProvider.fepCustomCert |         | <p>Optional</p> <p>Only defined when logical replication feature is enabled</p>                                                                                                                                                                                                                                                                                                                                                      |
| spec.fepChildCrVal.secretStore.csi.awsProvider.region          |         | <p>Optional</p> <p>AWS Region where EKS cluster is created</p>                                                                                                                                                                                                                                                                                                                                                                       |
| spec.fepChildCrVal.secretStore.csi.awsProvider.roleName        |         | <p>Optional</p> <p>Role Name for the IAM trust policy</p>                                                                                                                                                                                                                                                                                                                                                                            |
| spec.fepChildCrVal.secretStore.csi.awsProvider.fepSecrets      |         | <p>Optional</p>                                                                                                                                                                                                                                                                                                                                                                                                                      |

| Field                                                          | Default    | Details                                                                                                                                                                |
|----------------------------------------------------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                |            | List of the parameters and their corresponding secret created in the Vault<br><br>Eg:<br><fep parameter name>: <secret in keyvault>                                    |
| spec.fepChildCrVal.secretStore.csi.awsProvider.fepCustomCert   |            | Optional<br><br>Only defined when logical replication feature is enabled                                                                                               |
| spec.fepChildCrVal.secretStore.csi.gcpProvider.credentials     |            | Optional<br><br>Secret created by User that contains the required credentials to connect to GCP Secret Manager                                                         |
| spec.fepChildCrVal.secretStore.csi.gcpProvider.fepSecrets      |            | Optional<br><br>List of the parameters and their corresponding secret created in the Vault<br><br>Eg:<br><fep parameter name>: <secret in keyvault>                    |
| spec.fepChildCrVal.secretStore.csi.gcpProvider.fepCustomCert   |            | Optional<br><br>Only defined when logical replication feature is enabled                                                                                               |
| spec.fepChildCrVal.secretStore                                 |            | Optional<br><br>Not required to be defined if user opts to store all secrets in kubernetes environment                                                                 |
| spec.fepChildCrVal.secretStore.csi.vaultProvider.roleName      |            | Optional<br><br>roleName created by user in the Vault                                                                                                                  |
| spec.fepChildCrVal.secretStore.csi.vaultProvider.vaultAddress  |            | Optional<br><br>Address of the vault that is accessible from the FEP environment                                                                                       |
| spec.fepChildCrVal.secretStore.csi.vaultProvider.fepSecrets    |            | Optional<br><br>List of the parameters and their corresponding secret created in the Vault<br><br>Eg:<br><fep parameter name> : </path/to/secret/secretName> in vault> |
| spec.fepChildCrVal.secretStore.csi.vaultProvider.fepCustomCert |            | Optional<br><br>Only defined when logical replication feature is enabled                                                                                               |
| spec.fep.measurement.recallForVector.enable                    | false      | When specified as true, enables vector database recall measurement.                                                                                                    |
| spec.fep.measurement.recallForVector.schedule                  | 15 0 1 * * | Optional                                                                                                                                                               |

| Field                                               | Default | Details                                                                                                                                                                                                                                                                                                                      |
|-----------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                     |         | The date and time to start the measurement, in Cron format.                                                                                                                                                                                                                                                                  |
| spec.fep.measurement.recallForVector.parallelJobs   | 5       | <p>Optional</p> <p>Specifies the number of jobs to be executed concurrently.</p> <p>Increasing the number of parallelisms reduces the measurement time, but increases the system load on the database container. Adjust this parameter based on system load and measurement completion time.</p>                             |
| spec.fep.measurement.recallForVector.maxDuration    | 0       | <p>Optional</p> <p>Units: s, m, h, d</p> <p>If you do not specify a unit, it is s (seconds).</p> <p>Specifies the end time of the measurement. If the measurement is not completed during the end period, the measurement is terminated.</p> <p>If 0 is specified, it does not stop until all measurements are complete.</p> |
| spec.fep.measurement.recallForVector.sampleSize     | 100     | <p>Optional</p> <p>Specifies the number of samples to use for the recall measurement.</p> <p>The larger the number of samples, the more accurate the recall is, but the more time it takes to measure.</p> <p>Adjust this parameter based on estimation error and calculation time.</p>                                      |
| spec.fep.measurement.recallForVector.topK           | 5       | <p>Optional</p> <p>SELECT the top K items for which the recall is to be calculated.</p> <p>We recommend that you use the same value as LIMIT when performing a search on a vector database.</p>                                                                                                                              |
| spec.fep.measurement.recallForVector.alertThreshold | 0       | <p>Optional</p> <p>If the recall falls below this threshold, an alert is issued to the AlertManager. The value can be between 0 and 1. If 0 is specified, no alert is created.</p>                                                                                                                                           |
| spec.fep.measurement.recallForVector.targets[]      |         | <p>Specifies what the recall is measured for.</p> <p>You can specify multiple values in array format.</p> <p>At least one database object must be specified when enabling vector database recall measurement.</p>                                                                                                            |

| Field                                                                            | Default | Details                                                                                                                                                                      |
|----------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fep.measurement.recallForVect<br>or.targets[].database                      |         | The name of the database to measure recall.                                                                                                                                  |
| spec.fep.measurement.recallForVect<br>or.targets[].tableConfigs[]                |         | Specifies the table information to retrieve.<br><br>You can specify multiple values in array format.                                                                         |
| spec.fep.measurement.recallForVect<br>or.targets[].tableConfigs[].schemaObject   |         | For objects whose recall is to be measured, specify the schema, table, and column separated by dots(.).                                                                      |
| spec.fep.measurement.recallForVect<br>or.targets[].tableConfigs[].distanceMetric | cosine  | Optional<br><br>Specifies the distance calculation method (cosine, inner_product, l2). Choose the same distance calculation that the embedded model uses during training.    |
| spec.globalEnvSec                                                                |         | Specifies the name of the Kubernetes secret that contains variables common to all containers. The defined key-value pairs are added to all containers running on FEPCluster. |
| spec.fep.fepEnvSec                                                               |         | Specifies the name of the Kubernetes secret that contains key/value pairs specific to the fep-patroni container.                                                             |
| spec.fep.feputils.fepUtilsEnvSec                                                 |         | Specifies the name of the Kubernetes secret that contains key-value pairs specific to fep-utils sidecar.                                                                     |
| spec.fep.remoteLogging.fluentBitEnvSec                                           |         | Specifies the name of the Kubernetes secret that contains key-value pairs specific to the fep-logging-fluent-bit sidecar.                                                    |
| spec.fep.monitoring.fepExporter.fepExporterEnvSec                                |         | Specifies the name of the Kubernetes secret that contains key-value pairs specific to the prometheus-fep-exporter sidecar.                                                   |
| spec.fepChildCrVal.backup.fepBackupEnvSec                                        |         | Specifies the name of the Kubernetes secret that contains key-value pairs specific to febackup sidecar.                                                                      |

## Note

- (\*) - These parameters can be specified only at creation time and should not be changed. Any change to these parameters will be ignored and will not have any effect on FEP cluster functioning.
- (\*\*)- The storage volumes size can be increased provided underlying storage supports the operation. Optional volumes can be specified only at initial FEP cluster creation. If an optional volume is added later, operator will ignore it and no action will be taken.
- User should do or remove unsupported CR changes manually.
- spec.fep.postgres.tls CR specification should be used instead of spec.fepChildCrVal.systemCertificates. The lateral spec can still be used, however spec.fep.postgres.tls gives better flexibility to control MTLS access of the cluster.

- Either `spec.fep.postgres.tls` specification (old specification ) or `spec.fepChildCrVal.systemCertificates` should be used. They should not be used interchangeable.
- Server certificate specified under `spec.fep.postgres.tls` can be rotated by changing the secret and executing reload ( e.g. using `FEPAction` ); however for others specified in the CR, it is required to do restart of the PoDs
- When `spec.ldap.caConfigMapRef` is defined, and the referenced configmap exist, the named configmap will be mounted on `fep-patroni` under `/tls/ldap`.
- When the referenced secret `spec.ldap.ldapconfSecretRef` exists, the named secret will be mounted on `fep-patroni` under `/etc/openldap`. The environment variable `LDAPCONF=/etc/openldap/ldap.conf` will be exported to the `fep-patroni` container. If this key is not defined, Operator will create and mount default secret `<fep-cluster>-ldapconf` with the following content.
- When the referenced configmap `spec.ldap2pg.ldap2pgyamlConfigMapRef` exists, the named configmap will be mounted on `fep-patroni` under `/tmp/.config`. If the secret does not exist, Operator will create that named secret with the following content.

While in running state - following value will dynamically appear in the `FEPCluster` to reflect the cluster status

| Field name                                    | Details                                                                                                                                                                                                |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>status.fepStatus.fepClusterReady</code> | Will be true or false to reflect if the whole cluster is ready. Kubernetes cluster information is fetched to check number of instances 'READY' & 'RUNNING' is equal to number of Configured instances. |



## Note

"`fepClusterReady`" flag will be set at first `FEPCluster` creation time only. `fepClusterReady` flag does not participate in the next reconciliation loop)

Setting up the database vector transformation feature is automated by applying the `FEPCluster` YAML as follows. This automatically creates the system administrator (user who loads) for the ONNX model, the owner user (user who imports), and the user (user who executes). Set the name and password for each user.

For detailed usage instructions regarding the in-database vector transformation, refer to the Fujitsu Enterprise Postgres Knowledge Data Management Feature User's Guide.

Changing the enable setting and reapplying the cluster will result in the inference pod being deleted and the vector transformation feature within the database being disabled when changing from True to False. When changing from False to True, a new inference pod will be created and the setting will be enabled. The database will restart when enabled.

```
fep:
vectorTransformation:
  enable: true
  modelRepository:
  modelOwner:
    name: model-owner
    password: password-modelOwner
  modelUser:
    name: model-user
    password-modelUser
  modelLoader:
    name: model-admin
    password: password-modelAdmin
```

To create an inference server, configure the following parameters on the cluster to generate the inference server pod. The pod name is automatically determined based on the database server name. For example, if the database server is named "new-fep", the pod becomes "inference-new-fep". Additionally, configure persistent storage for the inference server. CSI can also be configured for storage. For details, refer to the User's Guide section "Deploying `FEPClusters` with Cloud-based Secret Management". For the inference server, configure the service for communication between the database server and the inference server pods. You can also choose to encrypt communications using mutual TLS (mTLS). To use it, set `connectionTls.enable` to True. If you do not specify the `connectionTls.certificate` parameter, certificates will be automatically generated. When using a created Secret, specify its name as shown in the following sample file. For details,

refer to the User's Guide section "Configuration FEP to Perform MTLS". Regarding the resources used by the inference server, calculate them based on the Fujitsu Enterprise Postgres Knowledge Data Management Feature User's Guide and set them as parameters.

```
vectorTransformation:
  inference_server: # Inference server information
    image: repostitory.io/triton-inference-server
    imagePullsecret: quay-pull-secret
    connectionTls:
      enable: true
      certificate:
        grpcCaName: grpc-cacert
        grpcCertificateName: grpc-cert
        grpcPrivateKey: grpc-key-password
        tritonGrpcCaName: triton-grpc-cacert
        tritonGrpcCertificateName: triton-grpc-cert
        tritonGrpcPrivateKey: triton-grpc-key-password
    inferenceServerPorts:
      grpcPort: 8001
      metricsPort: 8002
storage: # Storage mounted by inference server and model registry
  inferenceVol:
    size: 50Gi
    storageClass: inferece-storage
    accessMode: ReadWriteOnce
  modelRepositoryVol:
    size: 50Gi
    storageClass: inference-storage
    accessMode: ReadWriteOnce
```

## 1.2 Custom Resource Parameters

This section explains the Custom Resource Parameters.

### 1.2.1 FEPCluster Custom Resource Parameters

| Category   | Details                                                                                                                                                                 |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CRD Name   | FEPCluster                                                                                                                                                              |
| Definition | ///                                                                                                                                                                     |
| Operations | Create: kubectl create -f fepcluster.yaml<br>Delete: kubectl delete fepcluster <clusername><br>Update: kubectl apply -f fepcluster.yaml<br>List: kubectl get fepcluster |

FEPCluster CR Example

```
apiVersion: fep.fujitsu.io/v2
kind: FEPCluster
metadata:
  name: new-fep
  namespace: new-fep
spec:
  fep:
  ///
    wuC4
    -----END CERTIFICATE-----
```

It should also be noted that all the passwords / passphrase and certificates will be masked after the creation of the CR. This includes

- Also, initial pgAdminPassword: admin-password
- pgpassword: mydbpassword
- pgreplpassword: repluserpwd
- tdepassphrase: tde-passphrase
- pgRewindPassword: rewind\_password (Optional - if defined)
- pgMetricsPassword: metrics\_password (Optional - if defined)
- pgSecurityPassword (if defined)
- sslpassphrase under sysTde.tdek.kmsDefinition (if defined)
- certificate.key
- certificate.crt
- certificate.cacrt

Values of child CRs at the time of initial deployment of cluster, are stored in FEPCluster under fepChildCrVals, e.g. for Server certificates, Configuration of FEP, User details.

All fields for FEPCluster CR and its child CRs should be managed through FEPCluster CR only. Operator will reflect the changes to respective child CR to be processed. The fields that not allowed to change will not be reflected from parent to child CR and hence will not have any affect.

## 1.2.2 FEP Cluster Configuration

Configuration of all aspects of FEP Cluster is done through FEPCluster CR only.

All fields for FEPCluster CR and its child CRs should be managed through FEPCluster CR only. Operator will reflect the changes to respective child CR to be processed. The fields that not allowed to change will not be reflected from parent to child CR and hence will not have any affect. Refer to "[1.1 FEPCluster Parameter](#)" for details.

All child CRs are marked as internal objects in RedHat OCP and will not appear on console. However, it can be checked on command line using oc or kubectl commands.

Following table shows Child CRs of FEPCluster CR and respective sections in parent CR related to given child CR.

Configuration changes are made in these sections will update allowable fields only in corresponding child CR.

| Child CR Name | Relevant sections in FEP Cluster CR                                                                     |
|---------------|---------------------------------------------------------------------------------------------------------|
| FEPBackup     | spec.fepChildCrVal.backup                                                                               |
| FEPCert       | spec.fepChildCrVal.systemCertificates                                                                   |
| FEPConfig     | spec.fepChildCrVal.customPgAudit<br>spec.fepChildCrVal.customPgHba<br>spec.fepChildCrVal.customPgParams |
| FEPUser       | spec.fepChildCrVal.sysUsers                                                                             |
| FEPVolume     | spec.fepChildCrVal.storage                                                                              |

## 1.2.3 FEPConfig Child Custom Resource Parameters

| Field              | Default                 | Details                                                       |
|--------------------|-------------------------|---------------------------------------------------------------|
| metadata.name      | <same-as-in-FEPCluster> | This value is inherited from parent FEPCluster CR             |
| metadata.namespace | <same-as-in-FEPCluster> | This value is inherited from parent FEPCluster CR             |
| spec.customPgAudit | All line specified in   | Audit rules can be updated in this section. Requires restart. |

| Field                 | Default                                                                        | Details                                                                                                                         |
|-----------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
|                       | spec.fepChildCrVal.customPgAudit<br>of FEPCluster CR                           | Note: initial values inherited once only at start. Changes to FEPCluster directly                                               |
| spec.customPgHba      | All line specified in<br>spec.fepChildCrVal.customPgHba<br>of FEPCluster CR    | pg_hba rules can be added in this section<br>Note: Inherited once at start. Changes to FEPCluster directly                      |
| spec.customPgParams   | All line specified in<br>spec.fepChildCrVal.customPgParams<br>of FEPCluster CR | All postgres parameters are listed here to overwrite defaults.<br>Note: Inherited once at start. Changes to FEPCluster directly |
| spec.replicationSlots |                                                                                | Optional: Details of replication slots if defined in FEPCluster                                                                 |

Example of FEPCluster CR created

```

apiVersion: fep.fujitsu.io/v1
kind: FEPCluster
metadata:
  name: new-fep-19ncfg
  namespace: cfg-expt
spec:
  sysExtraLogging: false
  customPgAudit: |
    # define pg audit custom params here to override defaults.
    # if log volume is not defined, log_directory should be
    # changed to '/database/userdata/data/log'
    [output]
    logger = 'auditlog'
    log_directory = '/database/log/audit'
    log_truncate_on_rotation = on
    log_filename = 'pgaudit-%a.log'
    log_rotation_age = 1d
    log_rotation_size = 0
    [rule]

  customPgHba: |
    # define pg_hba custom rules here to be merged with default rules.
    # TYPE      DATABASE      USER      ADDRESS      METHOD
  customPgParams: |+
    # define custom postgresql.conf parameters below to override defaults.
    # Current values are as per default FEP deployment
    shared_preload_libraries='pgx_datamasking,pgaudit,pg_prewarm,pg_stat_statements'
    session_preload_libraries='pg_prewarm'
    max_prepared_transactions = 100
    max_worker_processes = 20
    max_connections = 100
    work_mem = 1MB
    maintenance_work_mem = 20MB
    shared_buffers = 128MB
    effective_cache_size = 384MB
    checkpoint_completion_target = 0.8
    pgx_global_metacache = 10MB
    temp_buffers = 10MB

```

```

# tcp parameters
tcp_keepalives_idle = 30
tcp_keepalives_interval = 10
tcp_keepalives_count = 3

# logging parameters in default fep installation
# if log volume is not defined, log_directory should be
# changed to '/database/userdata/data/log'    log_directory = '/database/log'
log_filename = 'logfile-%a.log'
log_file_mode = 0600
log_truncate_on_rotation = on
log_rotation_age = 1d
log_rotation_size = 0
log_checkpoints = on
log_line_prefix = '%e %t [%p]: [%l-1] user=%u,db=%d,app=%a,client=%h'
log_lock_waits = on
log_autovacuum_min_duration = 60s
logging_collector = on
pgaudit.config_file= '/opt/app-root/src/pgaudit-cfg/pgaudit.conf'
log_replication_commands = on
log_min_messages = WARNING
log_destination = stderr

# wal_archive parameters in default fep installation
archive_mode = on
wal_level = replica
max_wal_senders = 10
wal_keep_segments = 64
wal_sender_timeout = 60s
track_activities = on
track_counts = on

```

## 1.2.4 FEPUser Child Custom Resource Parameters

| Field                | Default                                                      | Details                                                                                                                                                                    |
|----------------------|--------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| metadata.name        | <same-as-in-FEPCluster>                                      | This value is inherited from parent FEPCluster CR                                                                                                                          |
| metadata.namespace   | <same-as-in-FEPCluster>                                      | This value is inherited from parent FEPCluster CR                                                                                                                          |
| spec.pgAdminPassword | spec.fepChildCrVal.users.pgAdminPassword<br>of FEPCluster CR | postgres superuser password. Masked once secret is created/changed<br><br>Note: initial values inherited once only at start. Changes to FEPUser directly                   |
| spec.pgdb            | spec.fepChildCrVal.users.pgdb<br>of FEPCluster CR            | Name of a user database<br><br>Note: Created once only at start. Cannot be changed                                                                                         |
| spec.pgpassword      | spec.fepChildCrVal.users.pgpassword<br>of FEPCluster CR      | Password for superuser for user database pgdb. Masked once secret is created/changed<br><br>Note: initial values inherited once only at start. Changes to FEPUser directly |
| spec.pguser          | spec.fepChildCrVal.users.pguser<br>of FEPCluster CR          | Name of a user database<br><br>Note: Created once only at start. Cannot be changed                                                                                         |
| spec.pgrepluser      | spec.fepChildCrVal.users.pgrepluser<br>of FEPCluster CR      | Name of a database user for replication                                                                                                                                    |

| Field                     | Default                                                     | Details                                                                                                   |
|---------------------------|-------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| spec.pgreplpassword       | spec.fepChildCrVal.users.pgreplpassword<br>of FEPCluster CR | Password for pgrepluser                                                                                   |
| spec.tdepassphrase        | spec.fepChildCrVal.users.tdepassphrase<br>of FEPCluster CR  | Passphrase for encrypting/decrypting keystore file which contains the TDE encryption key                  |
| spec.pgRewindUser         | rewind_user                                                 | Database user for Rewind                                                                                  |
| spec.pgRewindUserPassword | rewind_password                                             | Password for database user rewinduser                                                                     |
| spec.pgMetricsUser        | spec.fepChildCrVal.sysUsers.pgMetricsUser                   | Optional<br>Refer to " <a href="#">1.2.1 FEPCluster Custom Resource Parameters</a> " for details.         |
| spec.pgMetricsPassword    | spec.fepChildCrVal.sysUsers.pgMetricsPassword               | Optional<br>Refer to " <a href="#">1.2.1 FEPCluster Custom Resource Parameters</a> " for details.         |
| spec.pgAdminTls           | spec.fepChildCrVal.sysUsers.pgAdminTls                      | Optional section<br>Refer to " <a href="#">1.2.1 FEPCluster Custom Resource Parameters</a> " for details. |
| spec.pgrepluserTls        | spec.fepChildCrVal.sysUsers.pgrepluserTls                   | Optional section<br>Refer to " <a href="#">1.2.1 FEPCluster Custom Resource Parameters</a> " for details. |
| spec.pgRewindUserTls      | spec.fepChildCrVal.sysUsers.pgRewindUserTls                 | Optional section<br>Refer to " <a href="#">1.2.1 FEPCluster Custom Resource Parameters</a> " for details. |
| spec.pgMetricsUserTls     | spec.fepChildCrVal.sysUsers.pgMetricsUserTls                | Optional section<br>Refer to " <a href="#">1.2.1 FEPCluster Custom Resource Parameters</a> " for details. |

Example of FEPUser CR created

```

apiVersion: fep.fujitsu.io/v1
kind: FEPUser
metadata:
  name: new-fep-19n
  namespace: testswatiprject
spec:
  pgAdminPassword: '*****'
  pgdb: mydb
  pgpassword: '*****'
  pgreplpassword: '*****'
  pgrepluser: repluser
  pguser: mydbuser
  tdepassphrase: '*****'
  sysExtraLogging: false
  pgRewindUser: rewind_user
  pgRewindUserPassword: rewind_password
  pgAdminTls:
    certificateName: admin-client-certs-secret
    caName: admin-ssl-rootcert-configmap
    sslMode: prefer

```

```

pgrepluserTls:
  certificateName: repluser-client-certs-secret
  caName: repluser-ca-name-configmap
  sslMode: prefer
pgRewindUserTls:
  certificateName: rewinduser-client-certs-secret
  caName: rewinduser-ca-name-configmap
  sslMode: prefer

```



## Note

- Password and Passphrase are masked in output from CR. The original values can still be found in the respective Kubernetes secrets and configmaps.
- TDE is enabled by default with given tdepassphrase and must have a value.
- TDE is enabled by using the key tdepassphrase with the desired passphrase. Do not remove this key once TDE is enabled. Otherwise, the database may go into a crash loop. If the Cluster is running on Async Replication and a failover/switchover occurred during the crash loop, there could be data lost. The team is looking at preventing the deletion of this passphrase from Operator even if customer tries to remove it in customer resource.
- Database users and their passwords managed by the FEPUUser CR should not be changed in the SQL interface. Inconsistencies with the information managed by the operator can cause problems with operator operation. If you make changes in the SQL interface, use the SQL interface again to restore the original state.

## 1.2.5 FEPVolume Child Custom Resource Parameters

### 1.2.5.1 Create Volumes

Volumes for the cluster nodes(pods) are initially created in accordance with the values set in `fehChildCrVal`' storage section of the parent FEPCluster CR.

The parent FEPCluster CR creates a child FEPVolume CR with the respective startup values and the relevant controller(FEPColume Controller) takes care of creating the required volumes. After initial FEPCluster create, new volume cannot be added later and storageClass or accessModes can not be changed.

Only size of an initially created volume can be changed if and only if underlying storageClass supports dynamic change of size.

Below is the schema of the FEPVolume CR:

| Field         | Mandatory | Sub-Field                           | Default                                                                                | Description                                                                                                                             |
|---------------|-----------|-------------------------------------|----------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| archivewalVol | No        | size<br>storageClass<br>accessModes | 1Gi<br>Defaults to platform default if omitted<br>Defaults to ReadWriteOnce if omitted | Size of the volume,expandable later<br>SC is only set at start<br>Access mode is only set at start<br>Additional details in section 3.2 |
| backupVol     | No        | size<br>storageClass<br>accessModes | 2Gi<br>Defaults to platform default if omitted<br>Defaults to ReadWriteOnce if omitted | -do-                                                                                                                                    |
| dataVol       | Yes       | size<br>storageClass                | 2Gi                                                                                    | -do-                                                                                                                                    |

| Field         | Mandatory | Sub-Field                           | Default                                                                                           | Description |
|---------------|-----------|-------------------------------------|---------------------------------------------------------------------------------------------------|-------------|
|               |           | accessModes                         | Defaults to platform default if omitted<br><br>Defaults to ReadWriteOnce if omitted               |             |
| logVol        | No        | size<br>storageClass<br>accessModes | 1Gi<br><br>Defaults to platform default if omitted<br><br>Defaults to ReadWriteOnce if omitted    | -do-        |
| tablespaceVol | No        | size<br>storageClass<br>accessModes | 512Mi<br><br>Defaults to platform default if omitted<br><br>Defaults to ReadWriteOnce if omitted  | -do-        |
| walVol        | Yes       | Size<br>storageClass<br>accessModes | 1200Mi<br><br>Defaults to platform default if omitted<br><br>Defaults to ReadWriteOnce if omitted | -do-        |

### 1.2.5.2 Delete Volumes

Equivalent Kubernetes command: `kubectl delete FEPVolume <cr_name>`

This operation will remove all the PVCs and possibly PVs depending on the default reclaimPolicy of the storageclass used per volume.

With right backup and restore integration by customer, they may not need volumes to be persisted.



#### Note

Do not delete this CR unless the Cluster has been removed.

Example of FEPVolume CR created

```

apiVersion: fep.fujitsu.io/v1
kind: FEPVolume
metadata:
  name: new-fep-19n
  namespace: testswatiprject
spec:
  archivewalVol:
    size: 1Gi
  backupVol:
    size: 2Gi
  dataVol:
    size: 2Gi
  logVol:
    size: 1Gi
  tablespaceVol:
    size: 512Mi

```

```
walVol:
  size: 1Gi
selectedVolList:
- name: data
- name: tablespace
- name: wal
- name: log
sysExtraLogging: false
```

## 1.2.6 FEPCert Child Custom Resource Parameters

### 1.2.6.1 Create/ Update Certificates

Certificate secret for the FEP cluster is initially created in accordance with the values set in `fepChildCrVal`' `certs` section of the parent FEPCluster CR.

Below is the schema of the FEPCert CR:

| Field | Default                                                     | Description                                      |
|-------|-------------------------------------------------------------|--------------------------------------------------|
| cacrt | Defaults to dummy self signed crt from parent FEPCluster CR | Can be replaced with customer's own CA cert      |
| crt   | Defaults to dummy self signed crt from parent FEPCluster CR | Can be replaced with customer's own trusted cert |
| key   | Defaults to dummy key from parent FEPCluster CR             | Can be replaced with customer's own key          |

By default, Operator will create Kubernetes secrets to store the CA Cert, Server Cert and Key file. These files are exposed under the mount point `/fep-certs` in the container. The default FEPCluster template will also set the following postgres parameters in `postgresql.conf`.

```
ssl = on
ssl_cert_file = '/fep-certs/fep.crt'
ssl_key_file = '/fep-certs/fep.key'
ssl_ca_file = '/fep-certs/ca.crt'
```

It should also be possible to change the certificates by end user, by changing ALL key, crt and cacrt. However, user will need to restart the cluster to let change take effect.

### 1.2.6.2 Delete Certificates

Equivalent Kubernetes command: `kubectl delete FEPCert <cr_name>`

This operation will remove the secret containing the TLS Certificates and keys for the cluster.

Below is an example CR for certificates to be used by FEP server container

```
apiVersion: fep.fujitsu.io/v1
kind: FEPCert
metadata:
  name: new-fep
  namespace: ansible-operator-poc
spec:
  key: |-
    -----BEGIN RSA PRIVATE KEY-----
    MIIeowIBAAKCAQEA4AI33yvHZws+jta6qpV6wzJqF8odIfTIpCfbrVcUUtLfkJ1I
    2e4SceTKi603C/I1XuvWlpng5I065+fQQLO06z1/AuQT78YUn/Wlm9x1aHVsv4AN
    B5JWwqD0jrRT3o7nRPGXfilabP0rGE2mJJcVR9nExJ3IeaktgT3sb8YlXvtchyYp
    mjdbfxabTz07ig0+6/cwKoRRxOK8Uf7f5euE0cI/490J6r5Rs4lgD8sIQNCUFlTF
    YvmAH7gcdssSFBt8NP1UATHesofmlW0DKCJWNhTLOht+s6L/1zwTHLjPG2pdKG6W
    dgmu5H2pDml8CDNLdv98Aj7i+I5SRKKcVP1nuQIDAQABaoIBAfpQYK10zw/+BA0b
```

```
yMIUpdctIMb/54CR/xR0mVw1DbSjigNVPjHUQvB8Y1B2FAITQ0bgJ006bAv0QdWN
Rb0/v/yYiNJDFjaIaIAH10/2+owrXbFaZqgpVDJhB+e1xaZr2x7XGxm+p925k30
16pvIRY+I8JRKvZiV1VZHwL/R3J0tPr++xMZtLVjVOI+f+ySjQ+TzHuAjm49EKxj
cEmmJ28b7QcziXsvKy00f+zbqLIBKXQdZAFU5eEr1BSDRXdRW+Kf0XIVftuy4BJZ
voKT+VgHEvF/qysswL4+6IA06tpuYnnM0Y2d3s0GowPkTcQK0MekYKzL/WmtCjNs
9hodJtECgYEA5EWyhE0f4u0Ke5TDp697UCUvXLo0R58FDe/S8XNVScn29jj0kqIg
0Moqo9xAkJTNTzqn5Uudt1x/pgM2Nx1PLFijrc0zQLX3So002ryDd9wNi7YKtN16
KJqa536WeZu20EbuAZ+S3GALVy1RPeTNPnU0mKnF06DjDUGzLNCZy10CgYEA+zfw
952DWuz1U0Z4wvAEqqcgUKXPKrkTXV/iUnjkDkrLYVr0ZofDNTXrdH1+UedFmaOC
cieZn6DNhcdz5tKtyysGMH3g/qs9PfoGungvcXsy0Egk0413x1jc8TTCLqXZXyAQ
HMsx51n+R58oncPtzySU0r9qQ6PbC2CstTbFJA0CgYEAjGESu1iAB/jknfEzjXjG
PdhQUxb8VyE864Az21ah9t/kJzFyIAziAeqZ5GE7t247AGFTBRTHH18e1Qoemi3P
Wbc9GVtBfs11IYbcIDpUIyrKPEP805QEXtoNLxXTFgAjRGKiVY87spjCAJ+W2Zh0
e/1it5GYXfgQCYQA2yuBmOUCgYANRkR2YR1axaCk+N1Su60tdmdPu6M5x7PNQE70
OtMaKjua9lppvIzFGADMDutueoEEAE7ZR1xnwfb6PDLUpJdIYAqgr1YfPt8qkjaZ
Tv56yZ7CwL0pbF8m6nwqRrZoDp1wwraEvvvxFKFKGY/k3kCHlpTakdjEodjn3gDi
RnWeVQKBGcEneMSzuiei5LRppRtRaJw/Bt1l8qlPMLX3W7dxQ3cLwpmLon0m51Fp
PIZ44zYK8R6fu4+/sSrlfaIg86Ugeufp6YNxyNR0KxUGza5vDIu50ftwWtBeg+UK
Z8lLWNdX6ppWmjmf3H1DrkBBauYMUkZ4UxUYtelgHERMePIxwb
-----END RSA PRIVATE KEY-----
```

crt: |-

```
-----BEGIN CERTIFICATE-----
MIIDUTCCAjmGAWIBAgIRAMocw3qMoHrD6qRvMppMkMwDQYJKoZIhvcNAQELBQAw
NzEQMA4GA1UECgwHRnVqaxRzdTEjMCEGA1UEAwwaRkVQIFJvb3QgQ0EgZm9yIET1
YmVybmV0ZXNwHhcnMjEwMjA2MDQzMjM2WhcnMjYwMjA1MDQzMjM2WjA/MRAwDgYD
VQQKEwdGdWppdHN1MSswKQYDVQDEYyJGVUpJVFNVIEVudGVyCHJpc2UgUG9zZGdy
ZXNMcGU2VydmVyMIIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEA4AI3yVH
Zws+jta6qpV6wzJqF8odIfTIpCfbrVcUUTLFKJ1I2e4SceTKi603C/I1XuvWlpng
5I065+fQQL006z1/AuQT78YUn/WlM9x1aHVsV4ANB5JWwQD0jrRT3o7nRP6Xfila
bP0rGE2mJJcVR9nEXJ3IeaktgT3sb8Y1XvtchyYpmjdbfxabTz07ig0+6/cwKORR
xOK8Uf7f5euE0ci/490J6r5Rs4lgD8sIQNCUFLTFYvmAH7gcdssSFBt8NPLUATHE
soFmlW0DKCJWNHtLOht+s6L/1zwTHLjPG2pdkG6wdgmu5H2pDml8CDNLDv98Aj7i
+I5SRKKcVPLnuQIDAQAB0AwTjAdBgNVHSUEfjAUBggrBgEFBQcDAQYIKwYBBQUH
AwIwDAYDVROTAQH/BAIwADAFBgNVHSMEDAwgBQcwrrU00u+FhIUUvdrDRCQRsi6
ZjANBgkqhkiG9w0BAQsFAAOCAQEAm5dxBoI9pSc0CvRachg4CprdrDSJb9K6yB30
nCAxnM47iHeXnY3WlnI388kHu8DU704ba1tJbGs3KY9KzioPk43pU12jwk01onoF
+mTDjx/Ef1cYWA9r5q/LtgTa6Q2sxv402x67QW82aAnax034dV5zWCPiVaoovZBV
HRT+BgcG3r2vD1RGKK2nl1aYJtWh01SZubam+VttdZ/vbM9o0JctxmImstBXjkY
KteePdQtLL5o03JhyXWyrShCq+HMMkf2KgyY8gvydGcP4eLQdBwCw40LcnVq6UjT
0kKjycJEKngMvAdemq1ZWHGaiYB7hyT6GhgIcHUJ2cKrPgbEh1Q==
-----END CERTIFICATE-----
```

cacrt: |-

```
-----BEGIN CERTIFICATE-----
MIIDTzCCAjegAWIBAgIUySSQ8I74US5g+1+Z7ChuaDgkZnEwDQYJKoZIhvcNAQEL
BQAwNzEQMA4GA1UECgwHRnVqaxRzdTEjMCEGA1UEAwwaRkVQIFJvb3QgQ0EgZm9y
IET1YmVybmV0ZXNwHhcnMjEwMjA2MDM1MjI4WhcnMzEwMjA0MDM1MjI4WjA3MRAw
DgYDVQKQDAdGdWppdHN1MSMwIQYDVQKQDBpGRVAgUm9vdCBDQSBmb3IgS3ViZXJu
ZXRlc3CCASiWdQYJKoZIhvcNAQEBBQADggEPADCCAQoCggEBAMs97gUF0xkUzCgL
7MiIdju9ySr/ziwjcYU7jA9ML+SLmftMs3HtcYbAmSntqI+MDBSR/FAJT0oytuT
pV+mCFcGj2YAjDpliHPeNcUpbryy4YMChF3+MovkIWGcksx05rhiWhGmoBYpA48P
4Xe8SP1zqMzhFvNeKzyiUhvjutS2Y1Ss381sTaurFPx64vQ2PaC54XzdwMptXtpb
tYmWSzCpJWwxZ61F3vitdA2w0tnBWNyctAd0+RIM/fvArxiIqseAux9t0uogm5to
lRIhvekuxOpXBPeqtIYQ4j9XUW2JH8vUDnzPkPvjrq+A3Ug80yyfGvRw7+VYXozu
c4aP7PQCAwEAAnTFEwHQYDVRO0BBYEFBzCutQ7S74WeHs5V2sNEJBGyLpmMB8G
A1UdIwQYMBaAFBzCutQ7S74WeHs5V2sNEJBGyLpmMA8GA1UdEwEB/wQFMAMBaf8w
DQYJKoZIhvcNAQELBQADggEBAMDwD85RAawEBptFgLzKw+9xEUy1vcZaonAuA1qc
T342XTueyAugxkC11HwdCGgGS34VycfMGqj4AW6pA2ez4tLrbOps4DmV4sw8uBL
8pgRDgfly3ob9FEg2wa0hmrwx9jh5Bt4vySUE2785uPAqaspT2UNTbXs85Bui1T
sKiD2Rtil6an281Z81wyVVI6Jm2D4MG0mbsiGcTPLctdg/UljvDYymXlAvd4vNhl
k9hDa13TgDqJKgKdTiCmZONQdpEVgFc00h9AEUy5AuLqxHq60dLfZ6ESGP1MI7Lm
i4PzYbCnBmOe+7TnHcPSyrnehs66Ik+oifRd82eYS7vKjFw=
-----END CERTIFICATE-----
```



## Note

This approach of specifying FEPCerts is getting deprecated. Should follow Secrets as referred in section to configure Certs for Server, Patroni and Users.

### 1.2.7 FEPBackup Child Custom Resource Parameters

| Field                   | Default           | Details                                                                                                                                                                                                       |
|-------------------------|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| apiVersion              | fep.fujitsu.io/v1 | Fixed                                                                                                                                                                                                         |
| kind                    | FEPBackup         | Fixed                                                                                                                                                                                                         |
| metadata.name           | <clustername>     | Enter the CR name.                                                                                                                                                                                            |
| spec.pgbackrestParams   | " "               | " " It is fixed, and the parameter set in pgbackrest.conf is described from the line below.                                                                                                                   |
| spec.schedule.num       | Integer           | Number of schedules to set<br>The maximum number of backup schedules is 5.                                                                                                                                    |
| spec.scheduleN.schedule | -                 | Write the date and time of the Nth schedule in cron format.<br>The date and time is UTC time.                                                                                                                 |
| spec.scheduleN.type     | full/incr         | full: Perform a full backup (Back up the contents of the database cluster).<br>incr — Perform an incremental backup (Back up only the database cluster files that were changed to the last backup migration). |
| spec.preScript          | " "               | This parameter must specify a default value.                                                                                                                                                                  |
| spec.postScript         | " "               | This parameter must specify a default value.                                                                                                                                                                  |

Example of FEPBackup CR created

```
apiVersion: fep.fujitsu.io/v1
kind: FEPBackup
metadata:
  name: fepcluster-backup
spec:
  schedule:
    num : 2
  schedule1:
    schedule : "0 0 1 * *"
    type : "full"
  schedule2:
    schedule : "0 0 1-6 * *"
    type : "incr"
  preScript: " "
  postScript: " "
  pgbackrestParams: |
    # define custom pgbackrest.conf parameters below to override defaults.
    [global]
    repo1-retention-full = 30
    repo1-retention-full-type = time
  ...
```

### 1.2.8 FEPRestore Custom Resource Parameters

| Field                                                   | Default                     | Details                                                                                                                                                                                                                                                                                                                             |
|---------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| apiVersion                                              | fep.fujitsu.io/v1           | Fixed                                                                                                                                                                                                                                                                                                                               |
| kind                                                    | FEPRestore                  | Fixed                                                                                                                                                                                                                                                                                                                               |
| metadata.name                                           | -                           | Enter the CR name.                                                                                                                                                                                                                                                                                                                  |
| spec.fepVersion                                         |                             | Optional<br>To use FEPRestore image of given version. Possible values: 14, 15, 16, 17 & 18                                                                                                                                                                                                                                          |
| spec.image                                              | <current-released-image>    | FEP restore container image to be used<br>quay.io/fujitsu/fujitsu-enterprise-postgres-18-restore:ubi9-18-1.0<br>It is optional.<br>Image is left blank by default. In such a case, it will pick up URL of image from operator container environment.<br>If you specify the image, Operator will take that image to deploy container |
| spec.imagePullPolicy                                    | IfNotPresent                |                                                                                                                                                                                                                                                                                                                                     |
| spec.mcSpec.limits                                      | cpu: 0.2<br>memory: "300Mi" |                                                                                                                                                                                                                                                                                                                                     |
| spec.mcSpec.requests                                    | cpu: 0.1<br>memory: "200Mi" |                                                                                                                                                                                                                                                                                                                                     |
| spec.fromFEPcluster                                     | <from_clustername>          | The name of the FEPcluster from which to restore                                                                                                                                                                                                                                                                                    |
| spec.toFEPcluster                                       | <to_clustername>            | Specifies the name of the FEP cluster to restore to.<br>When restoring to an existing cluster, do not specify the line of this parameter.                                                                                                                                                                                           |
| spec.restoretype                                        | latest/PITR                 | latest - Restore Latest State<br>PITR - Date-Time Restore                                                                                                                                                                                                                                                                           |
| spec.restoredate                                        | -                           | If spec.restoretype is PITR, specify the day of PITR (UTC) in YYYY-MM-DD format<br>Be sure to use single quotes.<br>Example) '2020-11-25'                                                                                                                                                                                           |
| spec.restoretime                                        | -                           | If spec.restoretype is PITR, specifies the PITR time (UTC) in HH: MM: SS format<br>Be sure to use single quotes.<br>Example) '02:50:43'                                                                                                                                                                                             |
| spec.restoreTargetRepo                                  |                             | Optional<br>If you are using multiple repositories, specify the repository from which to restore.<br>If not specified, "1" is substituted.                                                                                                                                                                                          |
| spec.changeParams.fepChildCrVal.backup.pgbackrestParams |                             | Optional<br>Specify this to change the spec.fepChildCrVal.backup.pgbackrestParams setting in FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                       |

| Field                                                            | Default | Details                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------------------------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.changeParams.fepChildCrVal.backup.pgbackrestKeyParams       |         | Optional<br>Specify this to change the spec.fepChildCrVal.backup.pgbackrestKeyParams setting in FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                          |
| spec.changeParams.fepChildCrVal.backup.caName                    |         | Optional<br>Specify if you want to change the spec.fepChildCrVal.backup.caName setting of FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                                |
| spec.changeParams.fepChildCrVal.backup.repoKeySecretName         |         | Optional<br>Specify if you want to change the spec.fepChildCrVal.backup.repoKeySecretName setting of FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                     |
| spec.changeParams.fepChildCrVal.storage.backupVol                |         | Optional<br>Specify this to change the spec.fepChildCrVal.storage.backupVol setting in FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                                   |
| spec.changeParams.fepChildCrVal.storage.archivewalVol            |         | Optional<br>Specify this option to change the spec.fepChildCrVal.storage.archivewalVol setting for FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                       |
| spec.changeParams.fepChildCrVal.storage.dataVol                  |         | Optional<br>Specify this to change the spec.fepChildCrVal.storage.dataVol setting for FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                                    |
| spec.changeParams.fepChildCrVal.storage.walVol                   |         | Optional<br>Specify this to change the spec.fepChildCrVal.storage.walVol setting for FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                                     |
| spec.changeParams.fepChildCrVal.storage.logVol                   |         | Optional<br>Specify this to change the spec.fepChildCrVal.storage.logVol setting for FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                                     |
| spec.changeParams.fepChildCrVal.storage.tablespaceVol            |         | Optional<br>Specify this to change the spec.fepChildCrVal.storage.tablespaceVol setting for FEPClusterCR when restoring to a new DB cluster.                                                                                                                                                                                                                              |
| spec.changeParams.fep.monitoring.fepExporter.tls.certificateName |         | Optional<br>Specify this to change the spec.fep.monitoring.fepExporter.tls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |

| Field                                                           | Default | Details                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.changeParams.fep.monitoring.fepExporter.tls.caName         |         | Optional<br><br>Specify this to change the spec.fep.monitoring.fepExporter.tls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.         |
| spec.changeParams.fep.monitoring.prometheus.tls.certificateName |         | Optional<br><br>Specify this to change the spec.fep.monitoring.prometheus.tls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |
| spec.changeParams.fep.monitoring.prometheus.tls.caName          |         | Optional<br><br>Specify this to change the spec.fep.monitoring.prometheus.tls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.          |
| spec.changeParams.fep.remoteLogging.tls.certificateName         |         | Optional<br><br>Specify this to change the spec.fep.remoteLogging.tls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.         |
| spec.changeParams.fep.remoteLogging.tls.caName                  |         | Optional<br><br>Specify this to change the spec.fep.remoteLogging.tls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                  |
| spec.changeParams.fep.patroni.tls.certificateName               |         | Optional<br><br>Specify this to change the spec.fep.patroni.tls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.               |
| spec.changeParams.fep.patroni.tls.caName                        |         | Optional                                                                                                                                                                                                                                                                                                                                                                     |

| Field                                                               | Default | Details                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                     |         | Specify this to change the spec.fep.patroni.tls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                                       |
| spec.changeParams.fep.patroni.tls.privateKeyPassword                |         | Optional<br><br>Specify this to change the spec.fep.patroni.tls.privateKeyPassword setting of FEPClusterCR when restoring to a new database cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.     |
| spec.changeParams.fep.postgres.tls.certificateName                  |         | Optional<br><br>Specify this to change the spec.fep.postgres.tls.certificateName setting of FEPClusterCR when restoring to a new database cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.       |
| spec.changeParams.fep.postgres.tls.caName                           |         | Optional<br><br>Specify this to change the spec.fep.postgres.tls.caName setting of FEPClusterCR when restoring to a new database cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                |
| spec.changeParams.fep.postgres.tls.privateKeyPassword               |         | Optional<br><br>Specify this to change the spec.fep.postgres.tls.privateKeyPassword setting of FEPClusterCR when restoring to a new database cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.    |
| spec.changeParams.fepChildCrVal.sysUsers.pgAdminTls.certificateName |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgAdminTls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |
| spec.changeParams.fepChildCrVal.sysUsers.pgAdminTls.caName          |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgAdminTls.caName                                                                                                                                                                                                                                                                                         |

| Field                                                                  | Default | Details                                                                                                                                                                                                                                                                                                                                                                             |
|------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                        |         | setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                                                                                                      |
| spec.changeParams.fepChildCrVal.sysUsers.pgAdminTls.sslMode            |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgAdminTls.sslMode setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                 |
| spec.changeParams.fepChildCrVal.sysUsers.pgAdminTls.privateKeyPassword |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.sysUsers.pgAdminTls.privateKeyPassword setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |
| spec.changeParams.fepChildCrVal.sysUsers.pgrepluserTls.certificateName |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgrepluserTls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.      |
| spec.changeParams.fepChildCrVal.sysUsers.pgrepluserTls.caName          |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgrepluserTls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.               |
| spec.changeParams.fepChildCrVal.sysUsers.pgrepluserTls.sslMode         |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgrepluserTls.sslMode setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.              |

| Field                                                                        | Default | Details                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.changeParams.fepChildCrVal.sysUsers.pgrepluserTls.privateKeyPassword    |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.sysUsers.pgrepluserTls.privateKeyPassword setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.    |
| spec.changeParams.fepChildCrVal.sysUsers.pgMetricsUserTls.certificateName    |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgMetricsUserTls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.         |
| spec.changeParams.fepChildCrVal.sysUsers.pgMetricsUserTls.caName             |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgMetricsUserTls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                  |
| spec.changeParams.fepChildCrVal.sysUsers.pgMetricsUserTls.sslMode            |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgMetricsUserTls.sslMode setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                 |
| spec.changeParams.fepChildCrVal.sysUsers.pgMetricsUserTls.privateKeyPassword |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.sysUsers.pgMetricsUserTls.privateKeyPassword setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |
| spec.changeParams.fepChildCrVal.sysUsers.pgRewindUserTls.certificateName     |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgRewindUserTls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore                                                                                                                               |

| Field                                                                       | Default | Details                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                             |         | destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                                                                                                                                                                                                                                                                     |
| spec.changeParams.fepChildCrVal.sysUsers.pgRewindUserTls.caName             |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgRewindUserTls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                  |
| spec.changeParams.fepChildCrVal.sysUsers.pgRewindUserTls.sslMode            |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.pgRewindUserTls.sslMode setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                 |
| spec.changeParams.fepChildCrVal.sysUsers.pgRewindUserTls.privateKeyPassword |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.sysUsers.pgRewindUserTls.privateKeyPassword setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |
| spec.changeParams.fepChildCrVal.sysUsers.vectorizerTls.certificateName      |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.vectorizerTls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.           |
| spec.changeParams.fepChildCrVal.sysUsers.vectorizerTls.caName               |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.vectorizerTls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                    |
| spec.changeParams.fepChildCrVal.sysUsers.vectorizerTls.sslMode              |         | Optional<br><br>Specify to change the spec.fepChildCrVal.sysUsers.vectorizerTls.sslMode                                                                                                                                                                                                                                                                                                  |

| Field                                                                     | Default | Details                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                           |         | setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.                                                                                                         |
| spec.changeParams.fepChildCrVal.sysUsers.vectorizerTls.privateKeyPassword |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.sysUsers.vectorizerTls.privateKeyPassword setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |
| spec.changeParams.fepChildCrVal.secretStore.azureProvider.fepSecrets      |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.secretStore.azureProvider.fepSecrets setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.      |
| spec.changeParams.fepChildCrVal.secretStore.awsProvider.fepSecrets        |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.secretStore.awsProvider.fepSecrets setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.        |
| spec.changeParams.fepChildCrVal.secretStore.csi.gcpProvider.fepSecrets    |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.secretStore.csi.gcpProvider.fepSecrets setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.    |
| spec.changeParams.fepChildCrVal.secretStore.csi.vaultProvider.fepSecrets  |         | Optional<br><br>Specify this to change the spec.fepChildCrVal.secretStore.csi.vaultProvider.fepSecrets setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.  |

| Field                                                           | Default | Details                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.changeParams.fep.autoTuning.prometheus.tls.certificateName |         | Optional<br><br>Specify this to change the spec.fep.autoTuning.prometheus.tls.certificateName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself. |
| spec.changeParams.fep.autoTuning.prometheus.tls.caName          |         | Optional<br><br>Specify this to change the spec.fep.autoTuning.prometheus.tls.caName setting of FEPClusterCR when restoring to a new DB cluster. If the restore source FEP cluster uses an automatically generated certificate and the restore destination FEP cluster also uses an automatically generated certificate, do not specify this parameter line itself.          |

Example of FEPRestore CR created

```

apiVersion: fep.fujitsu.io/v1
kind: FEPRestore
metadata:
  name: feprestore
spec:
  mcSpec:
    limits:
      cpu: 200m
      memory: 300Mi
    requests:
      cpu: 100m
      memory: 200Mi
  fromFEPcluster: fepcluster1
  toFEPcluster: fepcluster2
  restoreType: latest
  imagePullPolicy: IfNotPresent

```

Example of Point-In-Time-Recovery using FEPRestore CR

```

apiVersion: fep.fujitsu.io/v1
kind: FEPRestore
metadata:
  name: feprestore
spec:
  mcSpec:
    limits:
      cpu: 300m
      memory: 700Mi
    requests:
      cpu: 200m
      memory: 512Mi
  fromFEPcluster: fepclusterA
  toFEPcluster: fepclusterB
  restoreType: PITR
  restoreDate: 2020-11-25

```

```
restoretime: 02:50:43
imagePullPolicy: IfNotPresent
```



## Note

Upon successful completion, custom resources in FEPRestore are automatically deleted.

You can specify spec.changeParams in the FEPRestore custom resource to modify the definition from the source to build a new FEPCluster and restore the data.

This allows you to mount another storage in the new cluster, for example, to expand the PVC size, even if you are using storage that does not support PVC extensions.

Example of a FEPRestore Custom Resource for Modifying the Storage Class and Storage Capacity of a FEPCluster "source-cluster"

```
apiVersion: fep.fujitsu.io/v1
kind: FEPRestore
metadata:
  name: feprestore
spec:
  mcSpec:
    limits:
      cpu: 300m
      memory: 700Mi
    requests:
      cpu: 200m
      memory: 512Mi
  fromFEPcluster: source-cluster
  toFEPcluster: new-cluster
  restoretype: latest
  changeParams:
    fepChildCrVal:
      storage:
        dataVol:
          size: 50 Gi
          storageClass: new-storage
```

## 1.2.9 FEPPgpool2 Custom Resource Parameters

Equivalent Kubernetes command: `kubectl create FEPPgpool2`

This operation will create a PGPool2 with supplied information.

| Field              | Default                  | Details                                                                                                                        |
|--------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| apiVersion         | fep.fujitsu.io/v1        | Fixed                                                                                                                          |
| kind               | FEPPgpool2               | Fixed                                                                                                                          |
| metadata.name      | -                        | List the name of the FEP Pgpool2 container.                                                                                    |
| metadata.namespace | -                        | Specify the namespace of the environment where you want to deploy the operator.                                                |
| spec.fepVersion    |                          | Optional<br>To use FEPPgpool2 image of given version. Possible values: 14, 15, 16, 17 & 18                                     |
| spec.image         | <current-released-image> | FEPPgpool2 container image to be used<br>quay.io/fujitsu/fujitsu-enterprise-postgres-18-pgpool2:ubi9-18-1.0<br>It is optional. |

| Field                | Default                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Details                                                                                                                                                                                               |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Image is left blank by default. In such a case, it will pick up URL of image from operator container environment.<br><br>If you specify the image, Operator will take that image to deploy container. |
| spec.count           | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | List the number of FEP Pgpool2 containers to create.                                                                                                                                                  |
| spec.serviceport     | 9999                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Describes the TCP port for connecting to the FEP Pgpool2 container.                                                                                                                                   |
| spec.statusport      | 9898                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Identifies the TCP port for connecting to the PCP process.                                                                                                                                            |
| spec.limits.cpu      | 400m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | List the number of CPUs (restriction) to allocate to resources.limits.cpu.                                                                                                                            |
| spec.limits.memory   | 512Mi                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Specifies the memory size (restriction) to allocate to resources.limits.memory.                                                                                                                       |
| spec.requests.cpu    | 200m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | List the number of CPUs (request) to allocate to resources.requests.cpu.                                                                                                                              |
| spec.requests.memory | 256Mi                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Specifies the memory size (request) to allocate to resources.requests.memory                                                                                                                          |
| spec.fepclustername  | new-fep                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Enter the FEPCluster name to connect to.                                                                                                                                                              |
| spec.customhba       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | If you want to use pool_hba.conf, describe what pool_hba.conf should contain from the line below.                                                                                                     |
| spec.customparams    | listen_addresses = '*'<br>pcp_listen_addresses = '*'<br>num_init_children = 32<br>reserved_connections = 0<br>enable_pool_hba = off<br>allow_clear_text_frontend_auth = off<br>authentication_timeout = 80<br>backend_weight0 = 1<br>backend_weight1 = 1<br>backend_flag0 = 'ALWAYS_PRIMARY'<br>backend_flag1 = 'DISALLOW_TO_FAILOVER'<br>connection_cache = on<br>max_pool = 4<br>listen_backlog_multiplier = 2<br>serialize_accept = off<br>child_life_time = 300<br>client_idle_limit = 0<br>child_max_connections = 0<br>connection_life_time = 0 | " " and the Pgpool-II parameters. Refer to " <a href="#">Pgpool-II parameters</a> " for detail.                                                                                                       |

| Field | Default                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Details |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
|       | reset_query_list = 'ABORT;<br>DISCARD ALL'<br><br>client_min_messages = info<br>log_min_messages = debug1<br>log_statement = on<br>log_per_node_statement = on<br>log_client_messages = on<br>log_hostname = on<br>log_connections = on<br>log_line_prefix = '%t: pid %p: '<br>load_balance_mode = on<br>ignore_leading_white_space =<br>on<br>white_function_list = "<br>black_function_list =<br>'currval,lastval,nextval,setval'<br>black_query_pattern_list = "<br>database_redirect_preference_<br>list = "<br>app_name_redirect_preferenc<br>e_list = "<br>allow_sql_comments = off<br>disable_load_balance_on_writ<br>e = 'transaction'<br>statement_level_load_balance<br>= on<br>sr_check_period = 0<br>sr_check_user = 'postgres'<br>delay_threshold = 0<br>log_standby_delay = 'none'<br>ssl = on<br>ssl_ciphers =<br>'HIGH:MEDIUM:+3DES:!<br>aNULL'<br>ssl_prefer_server_ciphers = off<br>ssl_ecdh_curve = 'prime256v1'<br>ssl_dh_params_file = "<br>relcache_expire = 0<br>relcache_size = 256<br>check_temp_table = catalog<br>check_unlogged_table = on<br>enable_shared_relcache = off |         |

| Field                      | Default                                                                                             | Details                                                                                                                                                                                                                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                            | relcache_query_target =<br>primary<br><br>wd_port0 = 9000<br><br>failover_on_backend_error =<br>off |                                                                                                                                                                                                                                         |
| spec.custompcp             | " "                                                                                                 | If you use the pcp command, " " and the contents of pcp.conf from the line below.                                                                                                                                                       |
| spec.customsslkey          | " "                                                                                                 | If you want to do it, " " and the Beethoven key content in the line below.                                                                                                                                                              |
| spec.customsslcert         | " "                                                                                                 | If you want to do it, " " and the contents of the public x 509 certificate from the line below.                                                                                                                                         |
| spec.customsslcert         | " "                                                                                                 | If you want to do it, " " and the following lines describe the contents of the CA root certificate in PEM format.                                                                                                                       |
| spec.customlogsize         | 100 Mi                                                                                              | Specifies the persistent volume size for log output.                                                                                                                                                                                    |
| spec.storageclassname      |                                                                                                     | Specifies the storage class for log output.<br><br>NFS storage is not available if you enable the following parameters:<br><br>- enable_shared_relcache<br><br>- memory_cache_enabled                                                   |
| spec.clientAuthMethod      |                                                                                                     | Optional<br><br>Specifies the method for client authentication.<br><br>Define "scram" to use scram-sha-256 authentication.<br>Otherwise, the client authentication method is still md5.                                                 |
| spec.scram.pgpoolkeySecret |                                                                                                     | Optional<br><br>Describes the name of the secret that stores the key for use in encryption/decryption.<br><br>Can only be specified at creation time.<br><br>If you change the contents of the specified secret, a restart is required. |
| spec.scram.userinfoSecret  |                                                                                                     | Optional<br><br>Write the name of the secret that contains the user name you added and the password that corresponds to that user.<br><br>Can only be specified at creation time.                                                       |

## Pgpool-II parameters

The parameters that can be specified are shown in the table below. For details on the parameters, refer to the Pgpool-II manual.

| Category            | Parameter name (Specified format) | Restart required after change |
|---------------------|-----------------------------------|-------------------------------|
| Connection settings | listen_addresses (string)         | Y                             |
|                     | pcp_listen_addresses (string)     | Y                             |
|                     | num_init_children (integer)       | Y                             |
|                     | reserved_connections (integer)    | Y                             |

| Category                            | Parameter name (Specified format)          | Restart required after change |
|-------------------------------------|--------------------------------------------|-------------------------------|
| Authentication settings             | enable_pool_hba (boolean)                  |                               |
|                                     | allow_clear_text_frontend_auth (boolean)   |                               |
|                                     | authentication_timeout (integer)           |                               |
| Backend settings                    | backend_weight0 (floating point)           |                               |
|                                     | backend_weight1 (floating point)           |                               |
|                                     | backend_flag0                              |                               |
|                                     | backend_flag1                              |                               |
| Connection pooling                  | connection_cache (boolean)                 | Y                             |
|                                     | max_pool (integer)                         | Y                             |
|                                     | listen_backlog_multiplier (integer)        | Y                             |
|                                     | serialize_accept (boolean)                 | Y                             |
|                                     | child_life_time (integer)                  | Y                             |
|                                     | client_idle_limit (integer)                |                               |
|                                     | child_max_connections (integer)            | Y                             |
|                                     | connection_life_time (integer)             | Y                             |
|                                     | reset_query_list (string)                  |                               |
| Error reporting and log acquisition | client_min_messages (enum)                 |                               |
|                                     | log_min_messages (enum)                    |                               |
|                                     | log_statement (boolean)                    |                               |
|                                     | log_per_node_statement (boolean)           |                               |
|                                     | log_client_messages (boolean)              |                               |
|                                     | log_hostname (boolean)                     |                               |
|                                     | log_connections (boolean)                  |                               |
|                                     | log_error_verbosity (enum)                 |                               |
|                                     | log_line_prefix (string)                   |                               |
| Load sharing settings               | load_balance_mode (boolean)                | Y                             |
|                                     | ignore_leading_white_space (boolean)       |                               |
|                                     | white_function_list (string)               |                               |
|                                     | black_function_list (string)               |                               |
|                                     | black_query_pattern_list (string)          |                               |
|                                     | database_redirect_preference_list (string) |                               |
|                                     | app_name_redirect_preference_list (string) |                               |
|                                     | allow_sql_comments (boolean)               |                               |
|                                     | disable_load_balance_on_write (string)     | Y                             |
|                                     | statement_level_load_balance (boolean)     |                               |
| Health check                        | connect_timeout (integer)                  |                               |
| Streaming replication check         | sr_check_period (integer)                  |                               |
|                                     | sr_check_user (string)                     |                               |
|                                     | sr_check_password (string)                 |                               |

| Category                  | Parameter name (Specified format)   | Restart required after change |
|---------------------------|-------------------------------------|-------------------------------|
|                           | sr_check_database (string)          |                               |
|                           | delay_threshold (integer)           |                               |
|                           | log_standby_delay (string)          |                               |
| Secure Socket Layer (SSL) | ssl (boolean)                       | Y                             |
|                           | ssl_ciphers (string)                | Y                             |
|                           | ssl_prefer_server_ciphers (boolean) | Y                             |
|                           | ssl_ecdh_curve (string)             | Y                             |
|                           | ssl_dh_params_file (string)         | Y                             |
| Other parameters          | relcache_expire (integer)           | Y                             |
|                           | relcache_size (integer)             | Y                             |
|                           | enable_shared_relcache (boolean)    | Y                             |
|                           | relcache_query_target (enum)        |                               |
|                           | check_temp_table (enum)             |                               |
|                           | check_unlogged_table (boolean)      |                               |

## 1.2.10 FEPAAction Custom Resource Parameters

Specify parameters in the format described below.

| Custom resource spec   | Default | Change effect                                                                                                                                                                                                                                                                                                                               |
|------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.targetClusterName |         | Must specify target FEP Cluster name within namespace mentioned in metadata.                                                                                                                                                                                                                                                                |
| spec.targetPgpool2Name |         | Must specify target FEPPgpool2 name within namespace mentioned in metadata when using pgpool2_restart.                                                                                                                                                                                                                                      |
| spec.fepAction.type    |         | Must specify action type.<br><br>Supported action types are:<br>restart<br>pod_restart<br>reload<br>list<br>switchover<br>failover<br>pgpool2_restart<br>backup<br>open_tde_masterkey<br>create_extension<br>alter_extension<br>update_admin_password<br>backup_expire<br>promote_standby<br>update_multi_master_replication<br>fixed_stats |
| spec.fepAction.args    |         | Must specify arguments needed for given action. For details of args corresponding to each action refer to " <a href="#">1.2.10.1 FEPAAction Specific Operation Details</a> ".                                                                                                                                                               |

| Custom resource spec            | Default | Change effect                                                                                                                                                                                                                                                                                                    |
|---------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepAction.backupType       | full    | Options<br>If you specify backup for fepAction.type, the type of backup is used.<br><br>full : Performs a full backup (backs up the contents of the database cluster).<br><br>incr : Perform an incremental backup (Back up only the database cluster files that were changed during the last backup migration). |
| spec.fepAction.backupRepo       | 1       | Options<br>Gets a backup in the specified repository.<br><br>The range is 1 to 256.                                                                                                                                                                                                                              |
| spec.sysExtraLogging            |         | To turn extra debugging on, set value to true.<br>It can be turned on/off at any time.                                                                                                                                                                                                                           |
| spec.args.targetReplicationName |         | Options<br>Specify the replication name to modify. If not specified, attempts will be made to modify all replicas defined in the bidirectional replication definition file.                                                                                                                                      |

After execution of FEPAAction CR, status is reflected in fepStatus field that is dynamically inserted in current FEPAAction CR as needed. fepStatus field used for FEPAAction CR are described here

| fepStatus ( with possible values )    | Remarks                                                                                                                                              |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| fepActionStatus:                      | fepStatus is inserted at the top of FEPAAction CR                                                                                                    |
| fepActionCondition: Success   Failure | This flag is inserted in fepAction CR to reflect success or failure of requested action                                                              |
| fepActionResult: ><br>"details"       | The result contains verbose details corresponding to the specific action been executed. Should be noted that it is either plain text of HTTP output. |
| processedTimestamp: <time stamp>      | Denotes time of action execution by the Operator                                                                                                     |

```

apiVersion: fep.fujitsu.io/v1
kind: FEPAAction
fepActionStatus:
  fepActionCondition: Success
metadata:
  name: new-fep-reload-action
  namespace: myns
spec:
  fepAction:
    args:
      - new-fep-sts-0
      - new-fep-sts-1
    type: reload
  sysExtraLogging: false
  targetClusterName: new-fep

```



## Note

- Please do not use the FEPAAction to perform a switchover or restart while executing backup. Failed to get the backup.

- You must create a new FEPAAction custom resource for each operation.

### 1.2.10.1 FEPAAction Specific Operation Details

#### Action type - reload

The reload action will manually reload the FEP database on the targeted FEPCluster.

"reload" action type expects users to specify the name of individual FEP pods that they want to run the database reload operation on. They specify that in the args section under the FEPAAction CR spec as below :

```
spec:
  fepAction:
    args:
      - nf-131851-sts-0
      - nf-131851-sts-1
    type: reload
  targetClusterName: nf-131851
```

#### Action type - restart

The restart action will manually restart the FEP database on the targeted FEPCluster.

"restart" action type expects users to specify the name of individual FEP pods that they want to run the database restart operation on. They specify that in the args section under the FEPAAction CR spec as below:

```
spec:
  fepAction:
    args:
      - nf-131851-sts-0
      - nf-131851-sts-1
    type: restart
  targetClusterName: nf-131851
```

#### Action type - pod\_restart

The pod\_restart action will restart specified list of POD for given target cluster. User can specify key word 'ALL' under 'args' section to restart all pods in target cluster. Alternatively, user can give the list of pods to be started in target cluster. User should either give ALL or the list of the pods.

This action restarts the replica pods first. Once all replicas have been restarted, it switches over the mastership to one of the replica before restarting old master pod. If it is a single node cluster, master will be restarted in its current state. This action is automatically created to restart pods when image or machine specs are changed for fep or backup container depending on autoPodRestart flag in FEPCluster CR (Refer to ["1.2.1 FEPCluster Custom Resource Parameters"](#) for details.):

```
spec:
  fepAction:
    args:
      - nf-131851-sts-0
      - nf-131851-sts-1
    type: pod_restart
  targetClusterName: nf-131851
```

#### Action type - list

The list action will return the status of the targeted FEPCluster.

"list" action type expects users to specify just the target cluster name to list the details of the same. Looks like below:

```
spec:
  fepAction:
    type: list
  targetClusterName: nf-131851
```

## Action type - switchover

The switchover action performs a manually switchover of the current leader/primary database from one pod to another pod of the targeted FEPCluster.

"switchover" action type expects users to specify the name of the target cluster that they want to perform switchover. args section is not required for switchover as FEPACTION operator code will internally find it and promote new master. FEPACTION CR spec as below:

```
spec:
  fepAction:
    type: switchover
    targetClusterName: nf-131851
```

## Action type - failover

The failover action performs a manually failover of the current primary database from one pod to another pod of the targeted FEPCluster. The difference between switchover and failover is that, switchover expects the primary database is running at the time whereas failover can force switchover of primary role from a non-responding pod to another pod. Note that failover is a disruptive action and may cause data lost.

"failover" action type expects users to specify the names of the candidate pods that they want to failover to. They specify that in the args section under the FEPACTION CR spec as below:

```
spec:
  fepAction:
    args:
      - nf-131851-sts-1
      - nf-131851-sts-2
    type: failover
    targetClusterName: nf-131851
```

Here, nf-131851-sts-1 and nf-131851-2 are the candidate pods to failover to. In this example, the current primary pod would be nf-131851-sts-0.

## Action type - pgpool2\_restart

"pgpool2\_restart" action type expects users to specify the name of individual FEPPgpool2 resource that they want to restart operation on. They specify that in the targetPgpool2Name section under the FEPACTION CR spec as below:

```
spec:
  fepAction:
    type: pgpool2_restart
    targetPgpool2Name: nf-131851-pgpool2
```

## Action type - backup

The "backup" action performs a backup on the target FEPCluster.

The "backup" action type requires you to specify the type of backup and the repository in which to store the data.

In the fepAction section of the FEPACTION custom resource specification, specify the following:.

```
spec:
  targetClusterName: new-fep
  fepAction:
    type: backup
    backupType: full
    backupRepo: 1
```



### Note

- Regardless of how the backup was performed (scheduled or FEPACTION), if backups were performed at the same time by the same FEPCluster, subsequent backups will fail.

- If the backup repository Retention Option is specified in the FEPCluster custom resource spec.fepChildCrVal.backup.pgbackrestParams, the backup files obtained by the FEPAAction are also deleted as specified by the option.

### Action type - open\_tde\_masterkey

The open\_tde\_masterkey action opens a keystore for a TDE-enabled target cluster.

The "open\_tde\_masterkey" action type requires the user to specify the name of the target cluster on which the keystore will be opened. The args section is not required.

Specify the following:

```
spec:
  targetClusterName: nf-131851
  fepAction:
    type: open_tde_masterkey
```

### Action type - create\_extension

The create\_extension action executes "CREATE EXTENSION" on the target FEPCluster and installs the extension.

In fepAction.args, specify the "extension name, version", "database", "schema", and "apply CASCADE options" to be installed.

| Parameters specified by args | Description                                                                                                                            |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| extension                    | Required<br>Specifies the extension and version to be installed.                                                                       |
| version                      | Option<br>Specifies the version of the extension to be specified for the VARSION option.<br>If omitted, the VARSION option is omitted. |
| database                     | Option<br>Specifies the database to install. If omitted, install in the "postgres" database.                                           |
| schema                       | Option<br>Specifies the schema to be installed, which is specified in the SCHEMA option.<br>If omitted, the SCHEMA option is omitted.  |
| cascade                      | Option<br>true or false<br>Enables or disables the CASCADE option for CREATE EXTENSION.<br>If omitted, false.                          |

An example specification is shown below.

```
spec:
  targetClusterName: new-fep
  fepAction:
    type: create_extension
    args:
      extension: "vci"
      version: "2.0"
      database: "mydb"
      schema: "public"
      cascade: "true"
```

### Action type - alter\_extension

The alter\_extension action executes "ALTER EXTENSION" on the target FEPCluster to change the definition of the extension.

You can execute ALTER EXTENSION on the specified FEPCluster container by applying `fepAction.args.version` with the version to be updated.

| Parameters specified by args | Description                                                                                                                                  |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| extension                    | Required<br>Specifies the installed extensions whose definition you want to change.                                                          |
| database                     | Option<br>Specifies the database whose extension you want to change. If omitted it will be installed into the "postgres" database.           |
| version                      | Option<br>Specifies the version of the installed extension to update. If omitted, it is updated to the latest version available at the time. |

Here is an example of a FEPAction custom resource that updates the version of `pg_stat_statements`:. When a custom resource is applied, the version of `pg_stat_statements` is updated to the specified version.

```
spec:
  targetClusterName: new-fep
  fepAction:
    type: alter_extension
    args:
      extension:pg_stat_statements
      version:1.8
      database:sample
```

### Action type - update\_admin\_password

The `update_admin_password` action redefines the password for SUPERUSER "postgres" on the target FEPCluster with a random value. This action will be executed when the FEPCluster custom resource `spec.fepChildCrVal.sysUsers.pgAdminPassword` is not defined. An example specification is shown below.

```
spec:
  fepAction:
    type: update_admin_password
    targetClusterName: new-fep
```

### Action type - backup\_expire

You can run the "pgbackrest expire" command on the FEPPod to remove expired backups. The "pgbackrest expire" command is normally run automatically upon a successful backup, but it can be run by the user, for example, when the definition of the number of generations to retain for a backup is reduced, and the backup data can be deleted so that the number of retained generations conforms to the changed definition. If you want to reduce the number of backup retention generations and free up disk space, apply "backup\_expire" in the FEPAction after changing the retention setting for backup data under the FEPCluster custom resource `fepChildCrVal.backup.pgbackrestParams`. You can specify the repository from which to remove the backup by specifying `args.repo`.

| Parameters specified by args | Description                                                                                                                                                                  |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| repo                         | Options<br>Specified value: integer<br>Specifies the number of the repository from which to remove the backup.<br>If omitted, delete the backup for all backup repositories. |



## Note

The number of the backup repository must be N for repoN-type, as defined in the FEPCluster custom resource spec.fepChildCrVal.backup.pgbackrestParams.

The following is an example of changing the retention setting for backup data in a FEPCluster custom resource.

You want to reduce the number of backup generations stored in S3.

```
spec:
  fepChildCrVal:
    backup:
      pgbackrestParams:
        repo2-type=s3
        repo2-retention-full=5    # Change it to the number of generations you want to keep
        repo2-retention-full-time
```

The following is an example of a FEPACTION custom resource that reduces the number of backup generations:

Since the backup repository for s3 is specified as repo2-type in pgbackrestParams, specify 2 for spec.fepAction.repo.

```
apiVersion: fep.fujitsu.io/v1
kind: FEPACTION
metadata:
  name: backup-expire-action
spec:
  targetCluster: new-fep
  fepAction:
    type: backup_expire
    args:
      repo: 2
```

## Action type - promote\_standby

promote\_standby promotes the FEP database in the disaster recovery environment from Standby DB to Primary DB. You must specify the DB cluster to be promoted.

The following shows a specification example.

```
spec:
  fepAction:
    type: promote_standby
    targetClusterName: my-fep
```

## Action type - update\_multi\_master\_replication

The update\_multi\_master\_replication action updates the bidirectional replication definition according to changes in the bidirectional replication definition specified in the ConfigMap referenced by the spec.fep.multiMasterReplication.configMapName field of the target FEPCluster custom resource.

## Action type - fixed\_stats

The fixed\_stats action performs a statistics operation (pg\_dbms\_stats) on the target FEPCluster.

The fixed\_stats action must specify the operations that can be performed by pg\_dbms\_stats. Specify fixedStatsType: < operation type > in spec.fepAction.args. Depending on the operation type, there are additional required and optional arguments. Refer to the table below.

Table 1.1 Operation Types and Arguments

| Operation Type | Required Arguments                                             | Optional Argument                                                             |
|----------------|----------------------------------------------------------------|-------------------------------------------------------------------------------|
| backup         | None<br><br>All databases are backed up with statistics. Also, | targetDb: Target database<br>fixedObject: Name of the object after the schema |

| Operation Type | Required Arguments                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Optional Argument                                                                                                                                                                                      |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | if an identifying comment is omitted, "FEPAAction" is assigned as the comment.                                                                                                                                                                                                                                                                                                                                                                                     | Example)Target specific columns<br>fixedObject: myschema.mytable.myclomun<br><br>comment: "XXX"                                                                                                        |
| restore        | targetDb: Target database<br><br>backupId: Backup ID<br>or<br>timestamp: timestamp<br>The data type is timestampz.<br><br>The statistics are pinned using the specified backup ID or the most recent backup before the specified time.                                                                                                                                                                                                                             | Only when timestamp is defined can a post-schema object be specified.<br>fixedObject: Name of the object after the schema<br>Example)Target specific columns<br>fiexdObject: myschema.mytable.myclomun |
| purge          | backupId: Backup ID<br>targetDb: Target data base<br><br>Erases backups before the specified backup ID for the database specified in targetDb.                                                                                                                                                                                                                                                                                                                     | You can specify a delete flag.<br>force: true<br>force: false<br>If omitted, it will be executed as false.                                                                                             |
| lock           | targetDb: Target data base<br><br>Fix statistics for the specified database.                                                                                                                                                                                                                                                                                                                                                                                       | fixedObject: Name of the object after the schema<br><br>Example)Target specific columns<br>fixedObject: myschema.mytable.myclomun                                                                      |
| unlock         | targetDb: Target data base<br><br>Unpin statistics performed on the specified database.                                                                                                                                                                                                                                                                                                                                                                            | fixedObject: Name of the object after the schema<br><br>Example)Target specific columns<br>fixedObject: myschema.mytable.myclomun                                                                      |
| cleanup        | targetDb: Target data base<br><br>Performs a statistics cleanup on the specified database.                                                                                                                                                                                                                                                                                                                                                                         | None                                                                                                                                                                                                   |
| import         | targetDb: Target data base<br><br>Fixes statistics from a binary file for the database specified in targetDb.<br><br>The file is imported from the fep.fixedStats.endpoint.protocol information defined in the FEPCluster custom resource. protocol changes the required arguments. See <a href="#">"Table 1.2 Required Arguments Per Protocol"</a> .                                                                                                              | fixedObject: Name of the object after the schema                                                                                                                                                       |
| export         | targetDb: Target data base<br><br>targetStats: Valid and regular statistics<br>Which to export (effective or plain)<br><br>Exports the currently valid or canonical statistics for the database specified in targetDb.<br>The file export destination uses the fep.fixedStats.endpoint. protocol information defined in the FEPCluster custom resource. protocol changes the required arguments. See <a href="#">"Table 1.2 Required Arguments Per Protocol"</a> . | fixedObject: Name of the object after the schema                                                                                                                                                       |

Table 1.2 Required Arguments Per Protocol

| Protocol | Required Arguments | Description                                                                 |
|----------|--------------------|-----------------------------------------------------------------------------|
| s3, gcs  | url                | URL of object storage                                                       |
| blob     | azureBlobName      | BLOB name of the statistics binary file                                     |
|          | azureContainerName | Container name of the Azure storage account                                 |
| local    | file               | Specify the name of the file to which statistics will be exported/imported. |

The following shows a specification example.

```
apiVersion: fep.fujitsu.io/v1
kind: FEPAction
metadata:
  name: fep-action-firxdStats
spec:
  fepAction:
    targetClusterName: new-fep
    type: fixed_stats
    args:
      fixedStatsType: backup
      targetDb: mydb
      fixedObject: schema.table.attaname
      comment: "xyzyzz"
```

### 1.2.11 FEPExporter Custom Resource

| Field                               | Default           | Details                                                                                                                                                                                                                     |
|-------------------------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| apiVersion                          | fep.fujitsu.io/v1 | Mandatory as it is                                                                                                                                                                                                          |
| kind                                | FEPExporter       | Mandatory as it is                                                                                                                                                                                                          |
| metadata.name                       | fep-monitor       | Name of FEPExporter CR - must be unique in namespace                                                                                                                                                                        |
| metadata.namespace                  | fep-ns            | Namespace - OCP populates it as current                                                                                                                                                                                     |
| spec.prometheus                     |                   | Optional<br>Prometheus MTLS spec section                                                                                                                                                                                    |
| spec.prometheus.tls                 |                   |                                                                                                                                                                                                                             |
| spec.prometheus.tls.certificateName |                   | Optional<br>This points to Kubernetes TLS secret that contains the certificate of Prometheus ServiceMonitor. FEPExporter will use this for certificate authentication. The certificate itself is stored in the key tls.crt. |
| spec.prometheus.tls.caName          |                   | Optional<br>This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt.                                                              |
| spec.fep.remoteLogging.enable       |                   | Set to true to forward logs from fluentbit to fluentd                                                                                                                                                                       |
| spec.fep.remoteLogging.image        |                   | Optional<br>Fluentbit image to be used. If not specified, Operator will use the latest version that is supported by the Operator.                                                                                           |
| spec.fep.remoteLogging.pullPolicy   | IfNotPresent      | Optional                                                                                                                                                                                                                    |

| Field                                                              | Default | Details                                                                                                                                                                                                        |
|--------------------------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepExporter.                                                  |         | Exporter spec section                                                                                                                                                                                          |
| spec.fepExporter.authSecret                                        |         | Optional<br>Base Authentication secret to provide username & encrypted password of user                                                                                                                        |
| spec.fepExporter.authSecret.secretName                             |         | Secret name                                                                                                                                                                                                    |
| spec.fepExporter.authSecret.usernameKey                            |         | Key of username in specified secret                                                                                                                                                                            |
| spec.fepExporter.authSecret.passwordKey                            |         | Key of password in specified secret                                                                                                                                                                            |
| spec.fepExporter.customLabel                                       |         | Custom label to be added to Prometheus ServiceMonitor                                                                                                                                                          |
| spec.fepExporter.tls                                               |         | FEPEXporter MTLS specs                                                                                                                                                                                         |
| spec.fepExporter.tls.certificateName                               |         | Optional<br>This point to Kubernetes TLS secret that contains the certificate of FepExporter. Prometheus will use this for certificate authentication. The certificate itself is stored in the key tls.crt.    |
| spec.fepExporter.tls.caName                                        |         | Optional<br>This points to Kubernetes configmap that contains additional CA the client use to verify a server certificate. The CA is stored in the key ca.crt.                                                 |
| spec.fepExporter.option.measurement.recallForVector.enable         | false   | Optional<br>true: Enables the repeatability measurement feature.                                                                                                                                               |
| spec.fepExporter.option.measurement.recallForVector.alertThreshold | 0       | Optional<br>If the recall falls below this threshold, an alert is issued to the AlertManager. The value can be between 0 and 1. If 0 is specified, no alert is created.                                        |
| spec.fepExporter.disableDefaultQueries                             | false   | Optional<br>Not defined or set to false => Create default queries<br>Defined and set to true => Do not create default queries.                                                                                 |
| spec.fepExporter.disableDefaultAlertRules                          | false   | Optional<br>Not defined or set to false => Create default alert rules<br>Defined and set to true => Do not create default alert rules.<br>If Default queries are disabled => Do not create default alert rule. |
| spec.fepExporter.exporterLogLevel                                  | error   | Set logging level: one of debug, info, warn, error                                                                                                                                                             |
| spec.fepExporter.fepClusterList                                    |         | Array of FEPCluster to monitor                                                                                                                                                                                 |
| spec.fepExporter.image.image                                       |         | quay.io/fujitsu/fujitsu-enterprise-postgres-exporter:ubi9-18-1.0<br>Optional<br>If not specified; image name is picked up from operator environment variable                                                   |

| Field                                    | Default                    | Details                                                                                                                                                                                                                                    |
|------------------------------------------|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepExporter.image.pullPolicy        | IfNotPresent               | Always or IfNotPresent                                                                                                                                                                                                                     |
| spec.fepExporter.mcSpec.limits           | cpu: 500m<br>memory: 700Mi | Max CPU allocated to exporter container<br>Max memory allocated to exporter container                                                                                                                                                      |
| spec.fepExporter.mcSpec.requests         | cpu: 200m<br>memory: 512Mi | CPU allocation at start for exporter container<br>memory allocation at start for exporter container                                                                                                                                        |
| spec.fepExporter.scrapeInterval          | 30s                        | Optional<br>This parameter may be specified to change statistics scraping frequency. If specified, Prometheus will poll FEPEXporter at given interval.<br>CHANGE THIS PARAMETER ONLY IF REALLY REQUIRED                                    |
| spec.fepExporter.scrapeTimeout           | 30s                        | Optional<br>This parameter may be specified to change statistics scraping timeout. If specified, Prometheus will wait for FEPEXporter for maximum this given period to return statistics.<br>CHANGE THIS PARAMETER ONLY IF REALLY REQUIRED |
| spec.fepExporter.sysExtraLogging         | true                       | To turn on extra debugging messages for operator, set value to true<br><i>It can be turned on/off at any time</i>                                                                                                                          |
| spec.fepExporter.sysExtraEvent           |                            | Optional.<br>To turn on event notification for custom resource changes, set the value to true. Can be turned on or off at any time.                                                                                                        |
| spec.fepExporter.restartRequired         | false                      | true: To restart FEPEXporter, when there is any change found in CR or FEPCluster<br>false: Will not restart FEPEXporter                                                                                                                    |
| spec.fepExporter.userCustomQueries       |                            | Optional Section<br>Example user's custom query to extract additional metrics.                                                                                                                                                             |
| spec.fepExporter.fepExporterGlobalEnvSec |                            | Specifies the name of a Kubernetes secret that contains key/value pairs common to all containers running in the FEPEXporter definition. When FEPCluster automatically creates a FEPEXporter, it is copied from FEPCluster.                 |
| spec.fepExporter.fepExporterEnvSec       |                            | Specifies the name of the Kubernetes secret that contains key-value pairs specific to the prometheus-fep-exporter container. When FEPCluster automatically creates a FEPEXporter, it is copied from FEPCluster.                            |

```

usr_example:
  query: "SELECT EXTRACT(EPOCH FROM (now() - pg_last_xact_replay_timestamp())) as lag"
  master: true
  metrics:
    - lag:
        usage: "GAUGE"
        description: "Replication lag behind master in seconds"

```

## 1.2.12 FEPAutoscale Custom Resource

When FEPClusterCR is defined, FEPAutoscaleCR is defined.

The parameters are as follows:

Configuration changes are made in FEPClusterCR.

| Field                                        | Default                                      | Details                                                                                                                                                                   |
|----------------------------------------------|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| apiVersion                                   | fep.fujitsu.io/v1                            | Fixed                                                                                                                                                                     |
| kind                                         | FEPAutoscale                                 | Fixed                                                                                                                                                                     |
| metadata.name                                | Same as FEPClusterCR                         | Fixed                                                                                                                                                                     |
| metadata.namespace                           | Same as FEPClusterCR                         | Fixed                                                                                                                                                                     |
| spec.scaleout.policy                         | off                                          | [cpu_utilization/connection_number/off]                                                                                                                                   |
| spec.scaleout.threshold                      | cpu_utilization: 40<br>connection_number: 40 | Threshold                                                                                                                                                                 |
| spec.scaleout.metricName                     | pg_capacity_connection_aver<br>age           | Specify this parameter if policy is connection_number.<br>The custom metrics server must publish the average<br>number of connections in the FEP cluster under this name. |
| spec.scaleout.stabilizationWind<br>owSeconds | 0                                            | If the duration (seconds) threshold of this parameter has<br>been exceeded continuously, a scale out is performed.                                                        |
| spec.limits.maxReplicas                      | 2                                            | Maximum number of replicas (0 to 15)<br><br>If the value is out of range, no automatic scale out is<br>performed.                                                         |

## 1.2.13 FEPUgrade Custom Resource

If "spec.fepChildCrVal.upgrade" is defined for the FEPCluster custom resource, the FEPUgrade custom resource is defined.

The parameters are as follows:

| Field                        | Default                    | Details                                                                                                  |
|------------------------------|----------------------------|----------------------------------------------------------------------------------------------------------|
| apiVersion                   | fep.fujitsu.io/v1          | Fixed                                                                                                    |
| kind                         | FEPUgrade                  | Fixed                                                                                                    |
| metadata.name                | Same as FEPClusterCR       | Fixed                                                                                                    |
| metadata.namespace           | Same as FEPClusterCR       | Fixed                                                                                                    |
| spec.upgrade                 |                            |                                                                                                          |
| spec.upgrade.sourceCluster   |                            | Specifies the FEPClusterCR name from which to migrate<br>data.<br>Required.                              |
| spec.upgrade.mcSpec.limits   | cpu: 200m<br>memory: 300Mi | Optional<br>Specifies the maximum number of resources to allocate to<br>the upgrade execution container. |
| spec.upgrade.mcSpec.requests | cpu: 100m<br>memory: 200Mi | Optional<br>Specifies the lower limit of resources allocated to the<br>upgrade execution container.      |
| spec.upgrade.image           |                            | Optional                                                                                                 |

| Field                                               | Default       | Details                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------------------------------------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                     |               | If omitted, the URL for image is obtained from the operator container environment.                                                                                                                                                                                                                                                                                                                                                     |
| spec.upgrade.imagePullPolicy                        | IfNotPresent  | Optional<br>Specifies the pull policy for the container image.<br>- Always<br>- IfNotPresent<br>- Never                                                                                                                                                                                                                                                                                                                                |
| spec.upgrade.source.pgAdminTls.certificateName      |               | Optional<br>If you do not define spec.fepChildCrVal.sysUsers.pgAdminTls.certificateName for the data source, it points to the Kubernetes TLS secret that contains the certificate for the Postgres user "postgres" in the data source.<br>If the data source FEP has set the authentication method for the upgrade execution container to "cert", then the upgrade execution container uses the certificate defined as secret.         |
| spec.upgrade.destination.pgAdminTls.certificateName |               | Optional<br>If you have not defined the spec.fepChildCrVal.sysUsers.pgAdminTls.certificateName of the newly created FEPCluster, it points to the Kubernetes TLS secret that contains the certificate of the Postgres user "postgres" in the data source.<br>If you create a new FEP with the "cert" authentication method for the upgrade execution container, the upgrade execution container uses the certificate defined as secret. |
| spec.upgrade.storage                                |               | Optional<br>Defines the storage for storing dump files.                                                                                                                                                                                                                                                                                                                                                                                |
| spec.upgrade.storage.storageClass                   |               | Optional<br>If omitted, the default storage class for your environment is used.                                                                                                                                                                                                                                                                                                                                                        |
| spec.upgrade.storage.size                           | 2Gi           | Optional<br>Specifies the size of the storage to store the dump file.                                                                                                                                                                                                                                                                                                                                                                  |
| spec.upgrade.storage.accessModes                    | ReadWriteOnce | Optional<br>accessModes for store the dump file<br>Specified as an array of accessModes<br>e.g. [ReadWriteMany]<br>If omitted, it will be treated as [ReadWriteOnce]                                                                                                                                                                                                                                                                   |

## 1.2.14 FEPLoggng Custom Resources

The fepLogging section needs to be added under spec to define required parameters for FEPLoggng configuration.

Following is a sample template :

```
spec:
  fepLogging:
    elastic:
```

```

authSecret:
  secretName: elastic-auth
  passwordKey: password
  userKey: username
host: elastic-passthrough.apps.openshift.com
logstashPrefix: postgres
port: 443
scheme: https
sslVerify: true
tls:
  certificateName: elastic-cert
  caName: elastic-cacert
image:
  pullPolicy: IfNotPresent
mcSpec:
  limits:
    cpu: 500m
    memory: 700Mi
  requests:
    cpu: 200m
    memory: 512Mi
restartRequired: false
sysExtraLogging: false
scrapeInterval: 30s
scrapeTimeout: 30s
tls:
  certificateName: fluentd-cert
  caName: cacert
prometheus:
...

```

Below is the list of all parameters defined in the fepLogging section, along with their brief description

| Custom Resource spec                   | Required/<br>Optional | Change Effect                                                                                                                | Updating<br>value<br>allowed |
|----------------------------------------|-----------------------|------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| spec.fepLogging.image.image            | Optional              | Fluentd Image of FEPLogging                                                                                                  | Yes                          |
| spec.fepLogging.image.pullPolicy       | Required              | Fluentd Image pull policy of FEPLogging                                                                                      | Yes                          |
| spec.fepLogging.mcSpec.limits.cpu      | Required              | Max CPU allocated to fluentd container                                                                                       | Yes                          |
| spec.fepLogging.mcSpec.limits.memory   | Required              | Max memory allocated to fluentd container                                                                                    | Yes                          |
| spec.fepLogging.mcSpec.requests.cpu    | Required              | CPU allocation at start for fluentd container                                                                                | Yes                          |
| spec.fepLogging.mcSpec.requests.memory | Required              | Memory allocation at start for fluentd container                                                                             | Yes                          |
| spec.fepLogging.sysExtraLogging        | Required              | To turn on extra debugging messages for operator, set value to true. It can be turned on/off at any time                     | Yes                          |
| spec.fepLogging.sysExtraEvent          | Optional              | To turn on event notification for changes to custom resources, set the value to true. You can turn it on or off at any time. | Yes                          |
| spec.fepLogging.restartRequired        | Required              | To restart FEPLogging instance for applying any new configuration for example after certificate rotation                     | Yes                          |
| spec.fepLogging.scrapeInterval         | Optional              | Scrape interval for Prometheus to fetch metrics from FEPLogging instance                                                     | Yes                          |

| Custom Resource spec                           | Required/<br>Optional | Change Effect                                                                                             | Updating<br>value<br>allowed |
|------------------------------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------|------------------------------|
| spec.fepLogging.scrapeTimeout                  | Optional              | Scrape Timeout for Prometheus to fetch metrics from FEPLogging instance                                   | Yes                          |
| spec.fepLogging.elastic.host                   | Optional              | Target Elasticsearch host name                                                                            | Yes                          |
| spec.fepLogging.elastic.port                   | Optional              | Target Elasticsearch port number                                                                          | Yes                          |
| spec.fepLogging.elastic.authSecret.secretName  | Optional              | Secret name which contains Elasticsearch authentication username & password                               | Yes                          |
| spec.fepLogging.elastic.authSecret.userKey     | Optional              | Username key specified in Elasticsearch authentication secret                                             | Yes                          |
| spec.fepLogging.elastic.authSecret.passwordKey | Optional              | Password key specified in Elasticsearch authentication secret                                             | Yes                          |
| spec.fepLogging.elastic.logstashPrefix         | Optional              | Logstash prefix to differentiate index pattern in elastic search. Default value is postgres               | Yes                          |
| spec.fepLogging.elastic.auditLogstashPrefix    | Optional              | Logstash prefix to differentiate index pattern in elastic search for auditlog. Default value is postgres  | Yes                          |
| spec.fepLogging.elastic.scheme                 | Optional              | Connection scheme between FEPLogging & Elasticsearch. Possible options http & https                       | Yes                          |
| spec.fepLogging.elastic.sslVerify              | Optional              | Set to true if you want to verify ssl certificate. If set to false then will not consider TLS certificate | Yes                          |
| spec.fepLogging.elastic.tls.certificateName    | Optional              | Kubernetes secret name which holds fluentd certificate                                                    | Yes                          |
| spec.fepLogging.elastic.tls.caName             | Optional              | Kubernetes configmap which holds cacert of Elasticsearch to verify Elasticsearch TLS connection           | Yes                          |
| spec.fepLogging.tls.certificateName            | Optional              | Kubernetes secret name which holds Fluentd certificate                                                    | Yes                          |
| spec.fepLogging.tls.caName                     | Optional              | Kubernetes configmap which holds cacert of Fluentd to configure MTLS between FEPLogging & Prometheus      | Yes                          |
| spec.prometheus.tls.certificateName            | Optional              | Kubernetes secret name which holds Prometheus certificate                                                 | Yes                          |
| spec.prometheus.tls.caName                     | Optional              | Kubernetes configmap which holds cacert of Fluentd to configure MTLS between FEPLogging & Prometheus      | Yes                          |

### 1.2.15 FEP Custom Resources - spec.fep.pgBadger

| Custom Resource spec             | Change Effect                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------|
| pgBadger.schedules.create        | The 'create' schedule to create report and upload it to endpoint                      |
| pgBadger.schedules.cleanup       | The 'cleanup' schedule to delete the report left in container                         |
| pgBadger.options.incremental     | Default: false; When set to true: create incremental report in pgbadger               |
| pgBadger.endpoint.authentication | a secret to contain authentication info to access endpoint<br>support basic auth only |

| Custom Resource spec                    | Change Effect                                                          |
|-----------------------------------------|------------------------------------------------------------------------|
| pgBadger.endpoint.customCertificateName | Client certificate reference in customCertificate CR                   |
| pgBadger.endpoint.fileUploadParameter   | The file upload parameter defined by the web server<br>Default: 'file' |
| pgBadger.endpoint.insecure              | equivalent to curl -insecure option, default to false                  |
| pgBadger.endpoint.url                   | Web server url to upload the report file                               |

## 1.2.16 FEP Custom Resources - spec.fep.pgAuditLog

### 1.2.16.1 Details of pgAuditLog.endpoint.authentication

| Protocol              | Required key               | Description                                  |
|-----------------------|----------------------------|----------------------------------------------|
| 'http' or not defined | basic_auth                 | The basic authentication for http web server |
| 's3'                  | aws_access_key             | AWS access key                               |
|                       | aws_secret_key             | AWS secret key                               |
| 'blob'                | azure_storage_account_name | Azure storage account name                   |
|                       | azure_storage_account_key  | Azure storage account key                    |

The Operator creates a default secret with keys for all the protocols with empty values when "pgAuditLog.endpoint.authentication" is not defined or empty.

The default secret is a template which the end user can update its proper values. The following is its content:

| Default Authentication Secret                                                                                                                                                                                                                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> kind: Secret apiVersion: v1 metadata:   name: [FEPCluster name]-pgauditlog-auth   namespace: [FEPCluster namespace] type: Opaque data:    basic_auth: ""   aws_access_key: ""   aws_access_secret: ""    azure_storage_account_name: ""   azure_storage_account_key: "" </pre> |

When the default secret is created, the Operator also updates the created secret name in the FEPCluster CR:

| FEPCluster                                                                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> spec.fep pgAuditLog:   enable: 'true'   endpoint:     protocol: 's3'     authentication: '[FEPCluster name]-pgauditlog-auth' ... </pre> |

The Operator uses the default secret but the upload feature will fail as the secret does not contain correct values. So the end user needs to update the values of the default secret to use upload feature properly.



## Note

- The Operator does not own - user specified secret because it is created by the end user. Only the default secret created by operator is owned by the cluster.
- When the FEPCluster has been delete, this secret will remain.

### 1.2.16.2 CR example for customized pgaudit ConfigMap

- Enable pgAudit
  - The pgAudit extension will be enabled.
- Use custom pgAudit config file
  - The pgAudit log will be output based on custom configuration

| FEPCluster                                                                                                                                               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>spec.fep pgAuditLog:   enable: 'true'   config: my-pgaudit-conf   endpoint: ... .. # fepChildCrVal.customPgAudit will be ignored in this case</pre> |

| ConfigMap - Name: my-pgaudit-conf                                                                                                                                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>data: pgaudit.conf:     [output]   logger = 'auditlog'   log_directory = '/database/log/audit'   [rule]   audit_role='jason'   database='demo'   class='READ, WRITE'   [option]</pre> |

### 1.2.16.3 CR example when uploading logs to Azure Blob

Use Azure blob as an endpoint to upload pgAudit file

| FEPCluster (using Azue blob as endpoint)                                                                                                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>spec.fep pgAuditLog:   enable: 'true'   endpoint:     protocol: 'blob'     authentication: my-azure-blob-secret     azureContainerName: cluster1     azureBlobName: pgaudit-log-1   schedules:     upload: '30 * * * *'</pre> |

| Secret - Name: my-azure-blob-secret                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------|
| <pre>data:   azure_storage_account_name: cG9zdGdyZXM=   azure_storage_account_key: ZnNcG9zdGads3cGzdGdyZXMyZXMlcA==</pre> |

#### 1.2.16.4 CR example for uploading logs to S3

Use AWS S3 as an endpoint to upload pgAudit file

- The pgAudit log will be uploaded to AWS s3 storage based on the provided schedule.

| FEPCluster (using S3 as endpoint)                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>spec.fep pgAuditLog:   enable: 'true'   endpoint:     url: 's3://pgaudit1/cluster1'     protocol: 's3'     authentication: my-aws-s3-secret   schedules:     upload: '30 * * * *'</pre> |

| Secret - Name: my-aws-s3-secret                                                       |
|---------------------------------------------------------------------------------------|
| <pre>data:   aws_access_key: cG9zdGdyZXM=   aws_access_secret: ZnNlcAznNlcA3A==</pre> |

## Appendix A Default Metrics Queries

```
pg_capacity_connection:
  query: |
    select sys, idle, idleintx, idleintx10min, idleintx1hour, idleintx1day, idleintx1week,
    (curr.idle + curr.idleintx + curr.active) total, s.setting "max" from
    (
      select
        count(CASE WHEN a.state is null THEN 1 END) sys,
        count(CASE WHEN a.state='idle' THEN 1 END) idle,
        count(CASE WHEN a.state='idle in transaction' OR a.state='idle in transaction (aborted)' THEN
1 END) idleintx,
        count(CASE WHEN (a.state='idle in transaction' OR a.state='idle in transaction (aborted)') AND
age(now(), state_change) > interval '10 min' THEN 1 END) idleintx10min,
        count(CASE WHEN (a.state='idle in transaction' OR a.state='idle in transaction (aborted)') AND
age(now(),state_change) > interval '1 hour' THEN 1 END) idleintx1hour,
        count(CASE WHEN (a.state='idle in transaction' OR a.state='idle in transaction (aborted)') AND
age(now(),state_change) > interval '1 day' THEN 1 END) idleintx1day,
        count(CASE WHEN (a.state='idle in transaction' OR a.state='idle in transaction (aborted)') AND
age(now(),state_change) > interval '1 week' THEN 1 END) idleintx1week,
        count(CASE WHEN a.state='active' THEN 1 END) active
      from pg_stat_activity a
    ) curr, pg_settings s where name = 'max_connections'
  master: true
  metrics:
    - sys:
        usage: 'GAUGE'
        description: 'Number of system connections.'
    - idle:
        usage: 'GAUGE'
        description: 'Number of idle connections.'
    - idleintx:
        usage: 'GAUGE'
        description: 'Number of idle in transaction connections.'
    - idleintx10min:
        usage: 'GAUGE'
        description: 'Number of idle in transaction connections running longer than 10 min.'
    - idleintx1hour:
        usage: 'GAUGE'
        description: 'Number of idle in transaction connections running longer than 1 hour.'
    - idleintx1day:
        usage: 'GAUGE'
        description: 'Number of idle in transaction connections running longer than 1 day.'
    - idleintx1week:
        usage: 'GAUGE'
        description: 'Number of idle in transaction connections running longer than 1 week.'
    - total:
        usage: 'GAUGE'
        description: 'Number of total connections.'
    - max:
        usage: 'GAUGE'
        description: 'Max number of connections.'

pg_capacity_schema:
  query: |
    SELECT current_database() AS database_name, table_schema,
    COALESCE(SUM(pg_total_relation_size(''||table_schema||'."'||table_name||'')), 0) AS size
    FROM information_schema.tables GROUP BY table_schema
  master: true
  metrics:
    - database_name:
        usage: 'LABEL'
```

```

        description: 'Database name.'
    - table_schema:
        usage: 'LABEL'
        description: 'Table schema name.'
    - size:
        usage: 'GAUGE'
        description: 'Disk space of schema.'

pg_capacity_tblspace:
    query: |
        SELECT pg_tablespace.spcname AS tablespace_name, pg_tablespace_size(pg_tablespace.spcname) AS
tablespace_size FROM pg_tablespace
    master: true
    metrics:
    - tablespace_name:
        usage: 'LABEL'
        description: 'Table space name.'
    - tablespace_size:
        usage: 'GAUGE'
        description: 'Disk space of table space.'

pg_capacity_tblvacuum:
    query: |
        SELECT current_database() datname, t.table_schema, count(t.table_name) table_count
        FROM information_schema.tables t
        INNER JOIN pg_catalog.pg_stat_user_tables tu on t.table_schema::text=tu.schemaname::text and
t.table_name::text=tu.relname::text
        and
        age(now(),greatest(COALESCE(last_vacuum, '1970-01-01Z'), COALESCE(last_autovacuum,
'1970-01-01Z')))) > interval '1 day'
        GROUP BY t.table_schema
    master: true
    metrics:
    - datname:
        usage: 'LABEL'
        description: 'Database name.'
    - table_schema:
        usage: 'LABEL'
        description: 'Table schema name.'
    - table_count:
        usage: 'GAUGE'
        description: 'Number of tables without vacuum for more than a day.'

pg_capacity_longtx:
    query: |
        with xact_count as (
            SELECT COALESCE(datname, '') datname, count(1)
            FROM pg_stat_activity
            where backend_type='client backend' and age(now(), COALESCE(xact_start, '1970-01-01Z')) >
interval '5 minutes'
            group by datname
        )
        select d.datname, coalesce(xc.count, 0) as count from pg_database d left join xact_count xc on
d.datname=xc.datname
    master: true
    metrics:
    - datname:
        usage: 'LABEL'
        description: 'Database name.'
    - count:
        usage: 'GAUGE'
        description: 'Number of transactions running longer than 5 minutes.'

```

```

pg_capacity_tblbloat:
query: |
    SELECT DISTINCT
        current_database() as datname, schemaname, tablename as relname, /*reltuples::bigint,
relpages::bigint, otta,*/
        CASE WHEN relpages < otta THEN 0 ELSE bs*(sml.relpages-otta)::BIGINT END AS wastedbytes
    FROM (
        SELECT
            schemaname, tablename, cc.reltuples, cc.relpages, bs,
            CEIL((cc.reltuples*((datahdr+ma-
                (CASE WHEN datahdr%ma=0 THEN ma ELSE datahdr%ma END))+nullhdr2+4))/(bs-20::float)) AS otta,
            COALESCE(c2.relname,'?') AS iname, COALESCE(c2.reltuples,0) AS ituples, COALESCE(c2.relpages,
0) AS ipages,
            COALESCE(CEIL((c2.reltuples*(datahdr-12))/(bs-20::float)),0) AS iotta -- very rough
approximation, assumes all cols

        FROM (
            SELECT
                ma,bs,schemaname,tablename,
                (datawidth+(hdr+ma-(case when hdr%ma=0 THEN ma ELSE hdr%ma END))):numeric AS datahdr,
                (maxfracsum*(nullhdr+ma-(case when nullhdr%ma=0 THEN ma ELSE nullhdr%ma END))) AS nullhdr2
            FROM (
                SELECT
                    schemaname, tablename, hdr, ma, bs,
                    SUM((1-null_frac)*avg_width) AS datawidth,
                    MAX(null_frac) AS maxfracsum,
                    hdr+(
                        SELECT 1+count(*)/8
                        FROM pg_stats s2
                        WHERE null_frac<>0 AND s2.schemaname = s.schemaname AND s2.tablename = s.tablename
                    ) AS nullhdr
                FROM pg_stats s, (
                    SELECT
                        (SELECT current_setting('block_size')::numeric) AS bs,
                        CASE WHEN substring(v,12,3) IN ('8.0','8.1','8.2') THEN 27 ELSE 23 END AS hdr,
                        CASE WHEN v ~ 'mingw32' THEN 8 ELSE 4 END AS ma
                        FROM (SELECT version() AS v) AS foo
                    ) AS constants
                GROUP BY 1,2,3,4,5
            ) AS foo
        ) AS rs
        JOIN pg_class cc ON cc.relname = rs.tablename
        JOIN pg_namespace nn ON cc.relnamespace = nn.oid AND nn.nsname = rs.schemaname AND nn.nsname
<> 'information_schema'
        LEFT JOIN pg_index i ON indrelid = cc.oid
        LEFT JOIN pg_class c2 ON c2.oid = i.indexrelid
    ) AS sml
    ORDER BY wastedbytes DESC
master: true
metrics:
- datname:
    usage: 'LABEL'
    description: 'Database name.'
- schemaname:
    usage: 'LABEL'
    description: 'Schema name.'
- relname:
    usage: 'LABEL'
    description: 'Name of this table.'
- wastedbytes:
    usage: 'GAUGE'
    description: 'Number of bytes wasted for table.'

```

pg\_performance\_locking\_detail:

```
query: |
    SELECT blocked_locks.pid AS blocked_pid,
           blocked_activity.username AS blocked_user,
           blocking_locks.pid AS blocking_pid,
           blocking_activity.username AS blocking_user,
           blocked_activity.query AS blocked_statement,
           1 locks
    FROM pg_catalog.pg_locks blocked_locks
    JOIN pg_catalog.pg_stat_activity blocked_activity ON blocked_activity.pid = blocked_locks.pid
    JOIN pg_catalog.pg_locks blocking_locks
    ON blocking_locks.locktype = blocked_locks.locktype
    AND blocking_locks.DATABASE IS NOT DISTINCT FROM blocked_locks.DATABASE
    AND blocking_locks.relation IS NOT DISTINCT FROM blocked_locks.relation
    AND blocking_locks.page IS NOT DISTINCT FROM blocked_locks.page
    AND blocking_locks.tuple IS NOT DISTINCT FROM blocked_locks.tuple
    AND blocking_locks.virtualxid IS NOT DISTINCT FROM blocked_locks.virtualxid
    AND blocking_locks.transactionid IS NOT DISTINCT FROM blocked_locks.transactionid
    AND blocking_locks.classid IS NOT DISTINCT FROM blocked_locks.classid
    AND blocking_locks.objid IS NOT DISTINCT FROM blocked_locks.objid
    AND blocking_locks.objsubid IS NOT DISTINCT FROM blocked_locks.objsubid
    AND blocking_locks.pid != blocked_locks.pid
    JOIN pg_catalog.pg_stat_activity blocking_activity ON blocking_activity.pid = blocking_locks.pid
    WHERE NOT blocked_locks.GRANTED
```

master: true

metrics:

- blocked\_pid:
  - usage: 'LABEL'
  - description: 'Blocked process id.'
- blocked\_user:
  - usage: 'LABEL'
  - description: 'Blocked user.'
- blocking\_pid:
  - usage: 'LABEL'
  - description: 'Blocking process id.'
- blocking\_user:
  - usage: 'LABEL'
  - description: 'Blocking user.'
- blocked\_statement:
  - usage: 'LABEL'
  - description: 'Blocked statement.'
- locks:
  - usage: 'GAUGE'
  - description: 'Number of processes in blocked state.'

pg\_performance\_locking:

```
query: |
    WITH
    locks as (
        SELECT blocked_locks.DATABASE, count(blocked_locks.pid) locks
        FROM pg_catalog.pg_locks blocked_locks
        JOIN pg_catalog.pg_stat_activity blocked_activity ON blocked_activity.pid = blocked_locks.pid
        JOIN pg_catalog.pg_locks blocking_locks
        ON blocking_locks.locktype = blocked_locks.locktype
        AND blocking_locks.DATABASE IS NOT DISTINCT FROM blocked_locks.DATABASE
        AND blocking_locks.relation IS NOT DISTINCT FROM blocked_locks.relation
        AND blocking_locks.page IS NOT DISTINCT FROM blocked_locks.page
        AND blocking_locks.tuple IS NOT DISTINCT FROM blocked_locks.tuple
        AND blocking_locks.virtualxid IS NOT DISTINCT FROM blocked_locks.virtualxid
        AND blocking_locks.transactionid IS NOT DISTINCT FROM blocked_locks.transactionid
        AND blocking_locks.classid IS NOT DISTINCT FROM blocked_locks.classid
        AND blocking_locks.objid IS NOT DISTINCT FROM blocked_locks.objid
        AND blocking_locks.objsubid IS NOT DISTINCT FROM blocked_locks.objsubid
```

```

        AND blocking_locks.pid != blocked_locks.pid
        JOIN pg_catalog.pg_stat_activity blocking_activity ON blocking_activity.pid =
blocking_locks.pid
        WHERE NOT blocked_locks.GRANTED group by blocked_locks.DATABASE
    ),
    dbs as (
        select * from pg_catalog.pg_database
    )
    select dbs.datname, coalesce(locks.locks, 0) locks from dbs left join locks on dbs.oid=DATABASE
master: true
metrics:
  - datname:
      usage: 'LABEL'
      description: 'Database name'
  - locks:
      usage: 'GAUGE'
      description: 'Number of processes in blocked state.'

pg_replication:
  query: |
    SELECT CASE WHEN pg_last_wal_receive_lsn() = pg_last_wal_replay_lsn() THEN 0 ELSE GREATEST (0,
EXTRACT(EPOCH FROM (now() - pg_last_xact_replay_timestamp())) END AS lag
  master: true
  metrics:
    - lag:
        usage: "GAUGE"
        description: "Replication lag behind master in seconds"

pg_postmaster:
  query: |

    SELECT pg_postmaster_start_time as start_time_seconds from pg_postmaster_start_time()
  master: true
  metrics:
    - start_time_seconds:
        usage: "GAUGE"
        description: "Time at which postmaster started"

pg_stat_user_tables:
  query: |
    SELECT
      current_database() datname,
      schemaname,
      relname,
      seq_scan,
      seq_tup_read,
      idx_scan,
      idx_tup_fetch,
      n_tup_ins,
      n_tup_upd,
      n_tup_del,
      n_tup_hot_upd,
      n_live_tup,
      n_dead_tup,
      n_mod_since_analyze,
      last_vacuum,
      last_autovacuum,
      last_analyze,
      last_autoanalyze,
      vacuum_count,
      autovacuum_count,
      analyze_count,
      autoanalyze_count

```

```

FROM
    pg_stat_user_tables
master: true
metrics:
  - datname:
      usage: "LABEL"
      description: "Name of current database"
  - schemaname:
      usage: "LABEL"
      description: "Name of the schema that this table is in"
  - relname:
      usage: "LABEL"
      description: "Name of this table"
  - seq_scan:
      usage: "COUNTER"
      description: "Number of sequential scans initiated on this table"
  - seq_tup_read:
      usage: "COUNTER"
      description: "Number of live rows fetched by sequential scans"
  - idx_scan:
      usage: "COUNTER"
      description: "Number of index scans initiated on this table"
  - idx_tup_fetch:
      usage: "COUNTER"
      description: "Number of live rows fetched by index scans"
  - n_tup_ins:
      usage: "COUNTER"
      description: "Number of rows inserted"
  - n_tup_upd:
      usage: "COUNTER"
      description: "Number of rows updated"
  - n_tup_del:
      usage: "COUNTER"
      description: "Number of rows deleted"
  - n_tup_hot_upd:
      usage: "COUNTER"
      description: "Number of rows HOT updated (i.e., with no separate index update required)"
  - n_live_tup:
      usage: "GAUGE"
      description: "Estimated number of live rows"
  - n_dead_tup:
      usage: "GAUGE"
      description: "Estimated number of dead rows"
  - n_mod_since_analyze:
      usage: "GAUGE"
      description: "Estimated number of rows changed since last analyze"
  - last_vacuum:
      usage: "GAUGE"
      description: "Last time at which this table was manually vacuumed (not counting VACUUM FULL)"
  - last_autovacuum:
      usage: "GAUGE"
      description: "Last time at which this table was vacuumed by the autovacuum daemon"
  - last_analyze:
      usage: "GAUGE"
      description: "Last time at which this table was manually analyzed"
  - last_autoanalyze:
      usage: "GAUGE"
      description: "Last time at which this table was analyzed by the autovacuum daemon"
  - vacuum_count:
      usage: "COUNTER"
      description: "Number of times this table has been manually vacuumed (not counting VACUUM
FULL)"
  - autovacuum_count:

```

```

        usage: "COUNTER"
        description: "Number of times this table has been vacuumed by the autovacuum daemon"
    - analyze_count:
        usage: "COUNTER"
        description: "Number of times this table has been manually analyzed"
    - autoanalyze_count:
        usage: "COUNTER"
        description: "Number of times this table has been analyzed by the autovacuum daemon"

pg_statio_user_tables:
    query: |
        SELECT current_database() datname, schemaname, relname, heap_blks_read, heap_blks_hit,
        idx_blks_read, idx_blks_hit, toast_blks_read, toast_blks_hit, tidx_blks_read, tidx_blks_hit FROM
        pg_statio_user_tables
    metrics:
        - datname:
            usage: "LABEL"
            description: "Name of current database"
        - schemaname:
            usage: "LABEL"
            description: "Name of the schema that this table is in"
        - relname:
            usage: "LABEL"
            description: "Name of this table"
        - heap_blks_read:
            usage: "COUNTER"
            description: "Number of disk blocks read from this table"
        - heap_blks_hit:
            usage: "COUNTER"
            description: "Number of buffer hits in this table"
        - idx_blks_read:
            usage: "COUNTER"
            description: "Number of disk blocks read from all indexes on this table"
        - idx_blks_hit:
            usage: "COUNTER"
            description: "Number of buffer hits in all indexes on this table"
        - toast_blks_read:
            usage: "COUNTER"
            description: "Number of disk blocks read from this table's TOAST table (if any)"
        - toast_blks_hit:
            usage: "COUNTER"
            description: "Number of buffer hits in this table's TOAST table (if any)"
        - tidx_blks_read:
            usage: "COUNTER"
            description: "Number of disk blocks read from this table's TOAST table indexes (if any)"
        - tidx_blks_hit:
            usage: "COUNTER"
            description: "Number of buffer hits in this table's TOAST table indexes (if any)"

pg_database:
    query: |

        SELECT pg_database.datname, pg_database_size(pg_database.datname) as size_bytes FROM pg_database
    master: true
    cache_seconds: 30
    metrics:
        - datname:
            usage: "LABEL"
            description: "Name of the database"
        - size_bytes:
            usage: "GAUGE"
            description: "Disk space used by the database"

```

```

pg_stat_statements:
  query: |
    SELECT t2.rolname, t3.datname, queryid, calls, total_plan_time / 1000 as
total_plan_time_seconds, total_exec_time / 1000 as total_exec_time_seconds, min_plan_time / 1000 as
min_plan_time_seconds, min_exec_time / 1000 as min_exec_time_seconds, max_plan_time / 1000 as
max_plan_time_seconds, max_exec_time / 1000 as max_exec_time_seconds, mean_plan_time / 1000 as
mean_plan_time_seconds, mean_exec_time / 1000 as mean_exec_time_seconds, stddev_plan_time / 1000 as
stddev_plan_time_seconds, stddev_exec_time / 1000 as stddev_exec_time_seconds, rows, shared_blks_hit,
shared_blks_read, shared_blks_dirtied, shared_blks_written, local_blks_hit, local_blks_read,
local_blks_dirtied, local_blks_written, temp_blks_read, temp_blks_written, blk_read_time / 1000 as
blk_read_time_seconds, blk_write_time / 1000 as blk_write_time_seconds FROM pg_stat_statements t1
JOIN pg_roles t2 ON (t1.userid=t2.oid) JOIN pg_database t3 ON (t1.dbid=t3.oid) WHERE t2.rolname !=
'rdsadmin'
  master: true
  metrics:
    - rolname:
        usage: "LABEL"
        description: "Name of user"
    - datname:
        usage: "LABEL"
        description: "Name of database"
    - queryid:
        usage: "LABEL"
        description: "Query ID"
    - calls:
        usage: "COUNTER"
        description: "Number of times executed"
    - total_plan_time_seconds:
        usage: "COUNTER"
        description: "Total plan time spent in the statement, in milliseconds"
    - total_exec_time_seconds:
        usage: "COUNTER"
        description: "Total exec time spent in the statement, in milliseconds"
    - min_plan_time_seconds:
        usage: "GAUGE"
        description: "Minimum plan time spent in the statement, in milliseconds"
    - min_exec_time_seconds:
        usage: "GAUGE"
        description: "Minimum exec time spent in the statement, in milliseconds"
    - max_plan_time_seconds:
        usage: "GAUGE"
        description: "Maximum plan time spent in the statement, in milliseconds"
    - max_exec_time_seconds:
        usage: "GAUGE"
        description: "Maximum exec time spent in the statement, in milliseconds"
    - mean_plan_time_seconds:
        usage: "GAUGE"
        description: "Mean plan time spent in the statement, in milliseconds"
    - mean_exec_time_seconds:
        usage: "GAUGE"
        description: "Mean exec time spent in the statement, in milliseconds"
    - stddev_plan_time_seconds:
        usage: "GAUGE"
        description: "Population standard deviation of plan time spent in the statement, in
milliseconds"
    - stddev_exec_time_seconds:
        usage: "GAUGE"
        description: "Population standard deviation of exec time spent in the statement, in
milliseconds"
    - rows:
        usage: "COUNTER"
        description: "Total number of rows retrieved or affected by the statement"
    - shared_blks_hit:

```

```

        usage: "COUNTER"
        description: "Total number of shared block cache hits by the statement"
- shared_blks_read:
    usage: "COUNTER"
    description: "Total number of shared blocks read by the statement"
- shared_blks_dirtied:
    usage: "COUNTER"
    description: "Total number of shared blocks dirtied by the statement"
- shared_blks_written:
    usage: "COUNTER"
    description: "Total number of shared blocks written by the statement"
- local_blks_hit:
    usage: "COUNTER"
    description: "Total number of local block cache hits by the statement"
- local_blks_read:
    usage: "COUNTER"
    description: "Total number of local blocks read by the statement"
- local_blks_dirtied:
    usage: "COUNTER"
    description: "Total number of local blocks dirtied by the statement"
- local_blks_written:
    usage: "COUNTER"
    description: "Total number of local blocks written by the statement"
- temp_blks_read:
    usage: "COUNTER"
    description: "Total number of temp blocks read by the statement"
- temp_blks_written:
    usage: "COUNTER"
    description: "Total number of temp blocks written by the statement"
- blk_read_time_seconds:
    usage: "COUNTER"
    description: "Total time the statement spent reading blocks, in milliseconds (if
track_io_timing is enabled, otherwise zero)"
- blk_write_time_seconds:
    usage: "COUNTER"
    description: "Total time the statement spent writing blocks, in milliseconds (if
track_io_timing is enabled, otherwise zero)"

```

pg\_password\_valid:

```

query: |
    SELECT
        rolname,
        TRUNC (EXTRACT (EPOCH FROM (rolvaliduntil - now())) / (60*60*24)) AS days,
        EXTRACT (EPOCH FROM (rolvaliduntil - now())) AS seconds,
        cast(rolvaliduntil AS TEXT) AS date
    FROM
        pg_roles
    WHERE
        rolvaliduntil!='infinity' AND rolvaliduntil is not null

```

master: true

metrics:

- rolname:
  - usage: "LABEL"
  - description: "Name of user"
- date:
  - usage: "LABEL"
  - description: "Password Expiration Date"
- days:
  - usage: "GAUGE"
  - description: "Number of days remaining before password expires."
- seconds:
  - usage: "GAUGE"
  - description: "Number of seconds remaining before password expires."

```

pg_not_set_password_valid:
query: |
    SELECT
        COUNT(CASE WHEN a.rolvaliduntil is null AND a.rolcanlogin='t' THEN 1 END) null_count,
        COUNT(CASE WHEN a.rolvaliduntil='infinity' AND a.rolcanlogin='t' THEN 1 END) infinity_count,
        COUNT(CASE WHEN (a.rolvaliduntil is null OR a.rolvaliduntil='infinity') AND a.rolcanlogin='t'
THEN 1 END) all_count
    FROM pg_roles a
master: true
metrics:
  - null_count:
      usage: "GAUGE"
      description: "Number of days remaining before password valid is null."
  - infinity_count:
      usage: "GAUGE"
      description: "Number of days remaining before password valid is infinity."
  - all_count:
      usage: "GAUGE"
      description: "Number of days remaining before password valid is null or infinity."

pg_tde_encrypted:
query: |
    SELECT
        current_database() datname,
        ts.oid AS tablespace_oid,
        ts.spcname AS tablespace_name,
        tsx.spcencalgo AS encryption_algorithm,
        coalesce(t.count, 0) AS objs
    FROM
        pg_tablespace ts
    JOIN pgx_tablespace tsx ON ts.oid = tsx.spctablespace
    LEFT OUTER JOIN (
        SELECT
            CASE WHEN c.reltablespace <> 0
            THEN c.reltablespace
            ELSE (select dattablespace from pg_database where datname = current_database())
            END AS reltablespaceid,
            count(*) AS count
        FROM pg_class c
        LEFT JOIN pg_namespace n ON n.oid = c.relnamespace
        WHERE c.relkind = ANY (ARRAY['r'::"char", 'm'::"char", 'p'::"char", 'i'::"char"])
        AND (n.nspname <> ALL (ARRAY['pg_toast'::name, 'pg_catalog'::name,
'information_schema'::name]))
        GROUP BY c.reltablespace
    ) t ON t.reltablespaceid = ts.oid
master: true
metrics:
  - datname:
      usage: 'LABEL'
      description: "Database name."
  - tablespace_oid:
      usage: 'LABEL'
      description: "oid of the tablespace to check."
  - tablespace_name:
      usage: 'LABEL'
      description: "Name of the tablespace to check."
  - encryption_algorithm:
      usage: 'LABEL'
      description: "Algorithm used for encryption."
  - objs:
      usage: 'GAUGE'
      description: "Number of tables and indexes in the tablespace."

```

```

pg_user_profile:
  query: |
    SELECT
      COUNT(*) AS total_roles,
      SUM(CASE WHEN userprfpasswordstatus = 'o' AND userprfaccountlock = 0 THEN 1 ELSE 0 END) AS
valid_roles,
      SUM(CASE WHEN userprfpasswordstatus = 'g' AND userprfaccountlock = 0 THEN 1 ELSE 0 END) AS
grace_time_roles,
      SUM(CASE WHEN userprfpasswordstatus = 'e' AND userprfaccountlock = 0 THEN 1 ELSE 0 END) AS
expired_roles,
      SUM(CASE WHEN userprfpasswordstatus = 'o' AND userprfaccountlock IN (1, 2) THEN 1 ELSE 0 END)
AS locked_roles
    FROM pgx_user_profile;
  metrics:
    - total_roles:
        usage: "GAUGE"
        description: "number of roles"
    - valid_roles:
        usage: "GAUGE"
        description: "number of valid roles"
    - grace_time_roles:
        usage: "GAUGE"
        description: "number of grace time roles"
    - expired_roles:
        usage: "GAUGE"
        description: "number of expired roles"
    - locked_roles:
        usage: "GAUGE"
        description: "number of locked roles"

pg_txid:
  query: |
    SELECT max(age(datfrozenxid)) AS usage from pg_database where dataallowconn = true
  metrics:
    - usage:
        usage: 'GAUGE'
        description: 'Cumulative number of transaction ID'

```

## Appendix B Default Alert Rules

```
apiVersion: monitoring.coreos.com/v1
kind: PrometheusRule
metadata:
  name: {{ ansible_operator_meta.name }}-{{ item.name }}-alertrules
  namespace: {{ ansible_operator_meta.namespace }}
  labels:
    app: prometheus-postgres-exporter-alertrules
    name: {{ ansible_operator_meta.name }}-{{ item.name }}-alertrules
spec:
  groups:
    - name: fep-container
      rules:
        - alert: ContainerDisappeared
          annotations:
            description: {{ 'Container {{$labels.container}}/{{$labels.pod}} from
{{$labels.namespace}} has been disappeared' }}
            summary: Container Pod disappeared.
            expr: time() -
              container_last_seen{ container="fep-patroni",
namespace="{{ ansible_operator_meta.namespace }}", pod=~"{{ item.name }}-sts-.*" } > 60
          labels:
            severity: warning
        - alert: ContainerHighCPUUsage
          annotations:
            description: {{ 'Container {{$labels.container}}/{{$labels.pod}} from
{{$labels.namespace}} has been high on CPU usage(>80%) for 5 mins' }}
            summary: High Container CPU usage.
            expr:
(sum(node_namespace_pod_container:container_cpu_usage_seconds_total:sum_rate{pod=~"{{ item.name }}-
sts.*", namespace="{{ ansible_operator_meta.namespace }}", container="fep-patroni"}) by
(pod,namespace,container)/sum(kube_pod_container_resource_limits_cpu_cores) by
(pod,namespace,container))*100 > 80
              for: 5m
          labels:
            severity: warning
        - alert: ContainerHighRAMUsage
          annotations:
            description: {{ 'Container {{$labels.container}}/{{$labels.pod}} from
{{$labels.namespace}} has been high on RAM usage(>80%) since 30 mins' }}
            summary: High container memory usage.
            expr: sum(container_memory_working_set_bytes{pod=~"{{ item.name }}-sts.*",
namespace="{{ ansible_operator_meta.namespace }}", container="fep-patroni"} /
container_spec_memory_limit_bytes * 100) by (pod, container, instance) > 80
              for: 30m
          labels:
            severity: warning
        - alert: PVCLowDiskSpace
          annotations:
            description: {{ 'Found low disk space on {{$labels.persistentvolumeclaim}} in
{{$labels.namespace}} namespace.' }}
            summary: {{ 'Found low disk space on {{$labels.persistentvolumeclaim}} in
{{$labels.namespace}} namespace.' }}
            expr:
kubelet_volume_stats_available_bytes{namespace="{{ ansible_operator_meta.namespace }}",
persistentvolumeclaim=~"fep.*{{ item.name }}.*"} / (kubelet_volume_stats_capacity_bytes) * 100 < 10
              for: 5m
          labels:
            severity: warning
    - name: postgres
      rules:
```

```

- alert: PostgresqlDown
  annotations:
    description: "Postgresql one or more instances are down in FEPCluster {{ item.name }} in
{{ ansible_operator_meta.namespace }} namespace. Please check the FEP pods in this cluster"
    summary: "Postgresql FEPCluster {{ item.name }} in {{ ansible_operator_meta.namespace }}
namespace is degraded"
    expr: count(pg_static{ namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*" }) <
{{ item.instances | length }}
    labels:
      severity: error
- alert: PostgresqlTooManyConnections
  annotations:
    description: {{ 'PostgreSQL instance has too many connections on server
{{ $labels.server }} in {{ $labels.namespace }} namespace.' }}
    summary: {{ 'Postgresql too many connections (FEPCluster server {{ $labels.server }})' }}
    expr: pg_capacity_connection_total{namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*"/
pg_settings_max_connections > 0.9
    labels:
      severity: warning
- alert: PostgresqlRolePasswordCloseExpierd
  annotations:
    description: "The Postgresql role's password expires in less than 7 days. Please update
the password."
    summary: "Postgresql Role Password expires in less than 7 days."
    expr: count(pg_password_valid_days{ namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*", rolname=~".*" }
< 8) > 0
    labels:
      severity: warning
- alert: PostgresqlRolePasswordExpired
  annotations:
    description: "The Postgresql role's password has already expired. Please update the
password."
    summary: "Postgresql Role Password has already expired. "
    expr: count(pg_password_valid_seconds{ namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*", rolname=~".*" }
< 0) > 0
    labels:
      severity: warning
- alert: PasswordIsGraceTimeByUserProfile
  annotations:
    description: The password for the role in the grace time exists. Please change your password.
    summary: There is a password in the grace time
    expr: grace_time_roles{ namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*" } > 0
    labels:
      severity: warning
- alert: PasswordExpiredByUserProfile
  annotations:
    description: Expired role password exists. Please change your password.
    summary: Expired role password exists
    expr: expired_roles{ namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*" } > 0
    labels:
      severity: warning
- alert: PasswordLockedByUserProfile
  annotations:
    description: There is a role with a password lock. Please confirm the role.
    summary: Password locked role exists
    expr: locked_roles{ namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*" } > 0

```

```
labels:
  severity: warning
- alert: PostgreSQLTooManyTxidUsage
  annotations:
    description: "Transaction ID usage has exceeded the value of autovacuum_freeze_max_age for
more than 24 hours. Consider periodic aggressive vacuuming."
    summary: "Transaction ID usage exceeds autovacuum_freeze_max_age"
    expr: pg_txid_usage{ namespace="{{ ansible_operator_meta.namespace }}",
service="{{ ansible_operator_meta.name }}-service", server=~"{{ item.name }}-sts.*" } >
pg_settings_autovacuum_freeze_max_age
for: 24h
labels:
  severity: warning
```

## Appendix C Operator Operation Event Notification

### C.1 FEPCluster Event Notification on Custom Resource Changes

When "spec.fep.sysExtraEvent" is true, event notification of operator actions occurs when you change the value of the following fields defined in the FEPCluster custom resource.

| Field Whose Value You Want to Change | Notification Timing                                       | Notification Custom Resources | Notification Message                                                    |
|--------------------------------------|-----------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------|
| spec.fep.image.image                 | Start Change                                              | FEPCluster                    | Started patching fep-patroni spec.fep.image.image                       |
|                                      | Change Successful                                         | FEPCluster                    | Successfully patching fep-patroni spec.fep.image.image                  |
|                                      | Change Failed                                             | FEPCluster                    | Error/Failure in patching fep-patroni spec.fep.image.image              |
|                                      | FEPAction Successfully Inherits Action to Custom Resource | FEPCluster                    | Successfully creating FEPActionCR for restart so check FEPAction result |
|                                      | Fail to inherit processing to FEPAction custom resource   | FEPCluster                    | Error/Failure in creating FEPActionCR for restart                       |
|                                      | Start Reflection                                          | FEPAction                     | Started restart Action for ALL Pods                                     |
|                                      | reflection success                                        | FEPAction                     | Successfully Restart Action for ALL Pods                                |
|                                      | Reflection failed                                         | FEPAction                     | Error/Failure Restart Action for ALL Pods                               |
| spec.fep.mcSpec                      | Start Change                                              | FEPCluster                    | Started patching fep-patroni spec.fep.mcSpec                            |
|                                      | Change Successful                                         | FEPCluster                    | Successfully patching fep-patroni spec.fep.mcSpec                       |
|                                      | Change Failed                                             | FEPCluster                    | Error/Failure in patching fep-patroni spec.fep.mcSpec                   |
|                                      | FEPAction Successfully Inherits Action to Custom Resource | FEPCluster                    | Successfully creating FEPActionCR for restart so check FEPAction result |
|                                      | Fail to inherit processing to FEPAction custom resource   | FEPCluster                    | Error/Failure in creating FEPActionCR for restart                       |
|                                      | Start Reflection                                          | FEPAction                     | Started restart Action for ALL Pods                                     |
|                                      | 1.2.14reflection success                                  | FEPAction                     | Successfully Restart Action for ALL Pods                                |
|                                      | Reflection failed                                         | FEPAction                     | Error/Failure Restart Action for ALL Pods                               |
| spec.fep.instances (Scale in)        | Start Change                                              | FEPCluster                    | Started scale in FEP Cluster                                            |
|                                      | Change Successful                                         | FEPCluster                    | Successfully scale in FEP Cluster                                       |
|                                      | Change Failed                                             | FEPCluster                    | Error/Failure in scale in FEP Cluster                                   |
| spec.fep.instances (Scale out)       | Start Change                                              | FEPCluster                    | Started scale out FEP Cluster                                           |
|                                      | Change Successful                                         | FEPCluster                    | Successfully scale out FEP Cluster                                      |

| Field Whose Value You Want to Change | Notification Timing                                             | Notification Custom Resources | Notification Message                                                |
|--------------------------------------|-----------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------|
|                                      | Change Failed                                                   | FEPCluster                    | Error/Failure in scale out FEP Cluster                              |
| spec.fep.pgBadger                    | Start Change                                                    | FEPCluster                    | Started update FEPConfig CR                                         |
|                                      | Succeeded in inheriting processing to FEPConfig custom resource | FEPCluster                    | Successfully updateing FEPConfig CR with current values             |
|                                      | Fail to inherit processing to FEPConfig custom resource         | FEPCluster                    | Error/Failure in updateing FEPConfig CR with current values         |
|                                      | Start Reflection                                                | FEPConfig                     | Started patching spec.fep.pgBadger                                  |
|                                      | reflection success                                              | FEPConfig                     | Successfully patching spec.fep.pgAuditLog and spec.fep.pgBadger     |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in patching spec.fep.pgAuditLog and spec.fep.pgBadger |
| spec.fep.pgBadger.schedule.create    | reflection success                                              | FEPConfig                     | Successfully updating spec.fep.pgBadger.schedules.create            |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in updating spec.fep.pgBadger.schedules.create        |
| spec.fep.pgBadger.schedule.cleanup   | reflection success                                              | FEPConfig                     | Successfully updating spec.fep.pgBadger.schedules.cleanup           |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in updating spec.fep.pgBadger.schedules.cleanup       |
| spec.fep.replicationSlots            | Start Change                                                    | FEPCluster                    | Started update FEPConfig CR                                         |
|                                      | Succeeded in inheriting processing to FEPConfig custom resource | FEPCluster                    | Successfully updateing FEPConfig CR with current values             |
|                                      | Fail to inherit processing to FEPConfig custom resource         | FEPCluster                    | Error/Failure in updateing FEPConfig CR with current values         |
|                                      | Start Reflection                                                | FEPConfig                     | Started patching spec.fepChildCrVal.replicationSlots                |
|                                      | reflection success                                              | FEPConfig                     | Successfully patching spec.fepChildCrVal.replicationSlots           |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in patching spec.fepChildCrVal.replicationSlots       |
| spec.fep.pgAuditLog                  | Start Change                                                    | FEPCluster                    | Started update FEPConfig CR                                         |
|                                      | Succeeded in inheriting processing to FEPConfig custom resource | FEPCluster                    | Successfully updateing FEPConfig CR with current values             |

| Field Whose Value You Want to Change | Notification Timing                                             | Notification Custom Resources | Notification Message                                                          |
|--------------------------------------|-----------------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------|
| spec.fep.pgAuditLog                  | Fail to inherit processing to FEPConfig custom resource         | FEPCluster                    | Error/Failure in updateing FEPConfig CR with current values                   |
|                                      | Start Reflection                                                | FEPConfig                     | Started patching spec.fep.pgAuditLog                                          |
|                                      | reflection success                                              | FEPConfig                     | Successfully patching spec.fep.pgAuditLog and spec.fep.pgBadger               |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in patching spec.fep.pgAuditLog and spec.fep.pgBadger           |
| spec.fep.pgAuditLog.auditLogPath     | Start Reflection                                                | FEPConfig                     | Started patching spec.fep.pgAuditLog                                          |
|                                      | reflection success                                              | FEPConfig                     | Successfully patching spec.fep.pgAuditLog                                     |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in patching spec.fep.pgAuditLog                                 |
| spec.fepChildCrVal.customPgAudit     | Start Change                                                    | FEPCluster                    | Started update FEPConfig CR                                                   |
|                                      | Succeeded in inheriting processing to FEPConfig custom resource | FEPCluster                    | Successfully updateing FEPConfig CR with current values                       |
|                                      | Fail to inherit processing to FEPConfig custom resource         | FEPCluster                    | Error/Failure in updateing FEPConfig CR with current values                   |
|                                      | Start Reflection                                                | FEPConfig                     | Started patching spec.fepChildCrVal.customPgAudit                             |
|                                      | reflection success                                              | FEPConfig                     | Successfully patching spec.fepChildCrVal.customPgAudit so restart DB          |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in patching fepStatus to patch spec.fepChildCrVal.customPgAudit |
| spec.fepChildCrVal.customPgHba       | Start Change                                                    | FEPCluster                    | Started update FEPConfig CR                                                   |
|                                      | Succeeded in inheriting processing to FEPConfig custom resource | FEPCluster                    | Successfully updateing FEPConfig CR with current values                       |
|                                      | Fail to inherit processing to FEPConfig custom resource         | FEPCluster                    | Error/Failure in updateing FEPConfig CR with current values                   |
|                                      | Start Reflection                                                | FEPConfig                     | Started patching spec.fepChildCrVal.customPgHba                               |
|                                      | reflection success                                              | FEPConfig                     | Successfully patching spec.fepChildCrVal.customPgHba                          |
|                                      | Reflection failed                                               | FEPConfig                     | Error/Failure in patching spec.fepChildCrVal.customPgHba                      |
| spec.fepChildCrVal.customPgParams    | Start Change                                                    | FEPCluster                    | Started update FEPConfig CR                                                   |

| Field Whose Value You Want to Change          | Notification Timing                                              | Notification Custom Resources | Notification Message                                                |
|-----------------------------------------------|------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------|
|                                               | Succeeded in inheriting processing to FEPCConfig custom resource | FEPCluster                    | Successfully updateing FEPCConfig CR with current values            |
|                                               | Fail to inherit processing to FEPCConfig custom resource         | FEPCluster                    | Error/Failure in updateing FEPCConfig CR with current values        |
|                                               | Start Reflection                                                 | FEPCConfig                    | Started patching spec.fepChildCrVal.customPgParams                  |
|                                               | reflection success                                               | FEPCConfig                    | Successfully patching spec.fepChildCrVal.customPgParams             |
|                                               | Reflection failed                                                | FEPCConfig                    | Error/Failure in patching spec.fepChildCrVal.customPgParams         |
| spec.fepChildCrVal.backup.image               | Start Change                                                     | FEPCluster                    | Started patching spec.fepChildCrVal.backup.image                    |
|                                               | Change Successful                                                | FEPCluster                    | Successfully patching febackup spec.fepChildCrVal.backup.image      |
|                                               | Change Failed                                                    | FEPCluster                    | Error/Failure in patching febackup spec.fepChildCrVal.backup.image  |
| spec.fepChildCrVal.backup.mcSpec              | Start Change                                                     | FEPCluster                    | Started patching febackup spec.fepChildCrVal.backup.mcSpec          |
|                                               | Change Successful                                                | FEPCluster                    | Successfully patching febackup spec.fepChildCrVal.backup.mcSpec     |
|                                               | Change Failed                                                    | FEPCluster                    | Error/Failure in patching febackup spec.fepChildCrVal.backup.mcSpec |
| spec.fepChildCrVal.backup.schedule.num        | Start Change                                                     | FEPCluster                    | Started patching spec.fepChildCrVal.backup.schedule.num             |
|                                               | Change Successful                                                | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup                     |
|                                               | Change Failed                                                    | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup                 |
| spec.fepChildCrVal.backup.pgbackrestKeyParams | Start Change                                                     | FEPCluster                    | Started patching spec.fepChildCrVal.backup.pgbackrestKeyParams      |
|                                               | Change Successful                                                | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup                     |
|                                               | Change Failed                                                    | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup                 |
| spec.fepChildCrVal.backup.pgbackrestParams    | Start Change                                                     | FEPCluster                    | Started patching spec.fepChildCrVal.backup.pgbackrestParams         |
|                                               | Change Successful                                                | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup                     |
|                                               | Change Failed                                                    | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup                 |
| spec.fepChildCrVal.backup.schedule1           | Start Change                                                     | FEPCluster                    | Started patching spec.fepChildCrVal.backup.schedule1                |

| Field Whose Value You Want to Change | Notification Timing | Notification Custom Resources | Notification Message                                                |
|--------------------------------------|---------------------|-------------------------------|---------------------------------------------------------------------|
|                                      | Change Successful   | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup.schedule1           |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup.schedule1       |
| spec.fepChildCrVal.backup.schedule2  | Start Change        | FEPCluster                    | Started patching spec.fepChildCrVal.backup.schedule2                |
|                                      | Change Successful   | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup.schedule2           |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup.schedule2       |
| spec.fepChildCrVal.backup.schedule3  | Start Change        | FEPCluster                    | Started patching spec.fepChildCrVal.backup.schedule3                |
|                                      | Change Successful   | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup.schedule3           |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup.schedule3       |
| spec.fepChildCrVal.backup.schedule4  | Start Change        | FEPCluster                    | Started patching spec.fepChildCrVal.backup.schedule4                |
|                                      | Change Successful   | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup.schedule4           |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup.schedule4       |
| spec.fepChildCrVal.backup.schedule5  | Start Change        | FEPCluster                    | Started patching spec.fepChildCrVal.backup.schedule5                |
|                                      | Change Successful   | FEPCluster                    | Successfully patching spec.fepChildCrVal.backup.schedule5           |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.backup.schedule5       |
| spec.fepChildCrVal.autoscale         | Start Change        | FEPCluster                    | Started patching spec.fepChildCrVal.autoscale                       |
|                                      | Change Successful   | FEPCluster                    | Successfully patching spec.fepChildCrVal.autoscale                  |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.autoscale              |
| spec.fepChildCrVal.storage           | Start Change        | FEPCluster                    | Started patching FEPVolume CR                                       |
|                                      | Change Successful   | FEPCluster                    | Successfully patching FEPVolume CR with current values              |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching FEPVolume CR with current values          |
| spec.fepChildCrVal.sysUsers          | Start Change        | FEPCluster                    | Started patching spec.fepChildCrVal.sysUsers passwords              |
|                                      | Change Successful   | FEPCluster                    | Successfully patching spec.fepChildCrVal.sysUsers in FEPCluster     |
|                                      | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepChildCrVal.sysUsers in FEPCluster |

| Field Whose Value You Want to Change          | Notification Timing | Notification Custom Resources | Notification Message                                                                                                                        |
|-----------------------------------------------|---------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| spec.fepChildCrVal.sysUsers.pgMetricsPassword | Start Change        | FEPCluster                    | Started setting spec.fepChildCrVal.sysUsers.pgMetricsPassword to FEPUserCR where spec.fepChildCrVal.sysUsers.pgMetricsPassword is undefined |
|                                               | Change Successful   | FEPCluster                    | Successfully setting spec.fepChildCrVal.sysUsers.pgMetricsPassword                                                                          |
|                                               | Change Failed       | FEPCluster                    | Error/Failure in Setting spec.fepChildCrVal.sysUsers.pgMetricsPassword                                                                      |
| spec.fepChildCrVal.sysUsers.pgMetricsUserTls  | Start Change        | FEPCluster                    | Started setting spec.fepChildCrVal.sysUsers.pgMetricsUserTls to FEPUserCR where spec.fepChildCrVal.sysUsers.pgMetricsUserTls is undefined   |
|                                               | Change Successful   | FEPCluster                    | Successfully setting spec.fepChildCrVal.sysUsers.pgMetricsUserTls                                                                           |
|                                               | Change Failed       | FEPCluster                    | Error/Failure in setting spec.fepChildCrVal.sysUsers.pgMetricsUserTls                                                                       |
| spec.fepChildCrVal.sysUsers.pgMetricsUser     | Start Change        | FEPCluster                    | Started delete spec.fepChildCrVal.sysUsers.pgMetricsUser                                                                                    |
|                                               | Change Successful   | FEPCluster                    | Successfully setting spec.fepChildCrVal.sysUsers.pgMetricsUser or spec.fepChildCrVal.sysUsers.pgMetricsUserTls                              |
|                                               | Change Failed       | FEPCluster                    | Error/Failure in setting spec.fepChildCrVal.sysUsers.pgMetricsUser or spec.fepChildCrVal.sysUsers.pgMetricsUserTls                          |
| spec.fepChildCrVal.sysUsers.pgMetricsUserTls  | Start Change        | FEPCluster                    | Started delete spec.fepChildCrVal.sysUsers.pgMetricsUserTls                                                                                 |
| spec.fepChildCrVal.sysUsers.pgMetricsUserTls  | Start Change        | FEPCluster                    | Successfully setting spec.fepChildCrVal.sysUsers.pgMetricsUser or spec.fepChildCrVal.sysUsers.pgMetricsUserTls                              |
|                                               | Change Successful   | FEPCluster                    | Error/Failure in setting spec.fepChildCrVal.sysUsers.pgMetricsUser or spec.fepChildCrVal.sysUsers.pgMetricsUserTls                          |
| spec.sysTde.tdek.targetKeyId                  | Change Failed       | FEPCluster                    | Started patching spec.sysTde.tdek.targetKeyId                                                                                               |
|                                               | Start Change        | FEPCluster                    | Successfully patching spec.sysTde.tdek.targetKeyId                                                                                          |
|                                               | Change Successful   | FEPCluster                    | Error/Failure in patching spec.sysTde.tdek.targetKeyId                                                                                      |
| spec.sysTde.tdek.kmsDefinition.sslpassphrase  | Change Failed       | FEPCluster                    | Started patching spec.sysTde.tdek.kmsDefinition.sslpassphrase                                                                               |
|                                               | Start Change        | FEPCluster                    | Successfully patching spec.sysTde.tdek.kmsDefinition.sslpassphrase                                                                          |
|                                               | Change Successful   | FEPCluster                    | Error/Failure in patching spec.sysTde.tdek.kmsDefinition.sslpassphrase                                                                      |

| Field Whose Value You Want to Change             | Notification Timing | Notification Custom Resources | Notification Message                                                                                                  |
|--------------------------------------------------|---------------------|-------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| spec.remoteLogging.image                         | Change Failed       | FEPCluster                    | Started patching fep-logging-fluent-bit spec.remoteLogging.image                                                      |
|                                                  | Start Change        | FEPCluster                    | Successfully patching fep-logging-fluent-bit spec.remoteLogging.image                                                 |
|                                                  | Change Successful   | FEPCluster                    | Error/Failure in patching patching fep-logging-fluent-bit spec.remoteLogging                                          |
| spec.monitoring.fepExporter.authSecret (new)     | Change Failed       | FEPCluster                    | Started patching FEPEXporter CR because spec.fepExporter.authSecret or spec.fepExporter.tls details are newly defined |
|                                                  | Start Change        | FEPCluster                    | Successfully patching FEPEXporter CR for spec.fepExporter.authSecret or spec.fepExporter.tls details                  |
|                                                  | Start Change        | FEPCluster                    | Error/Failure in patching FEPEXporter CR for spec.fepExporter.authSecret or spec.fepExporter.tls details              |
| spec.monitoring.fepExporter.tls (new)            | Change Successful   | FEPCluster                    | Started patching FEPEXporter CR because spec.fepExporter.authSecret or spec.fepExporter.tls details are newly defined |
|                                                  | Change Failed       | FEPCluster                    | Successfully patching FEPEXporter CR for spec.fepExporter.authSecret or spec.fepExporter.tls details                  |
| spec.monitoring.fepExporter.tls (new)            | Change Failed       | FEPCluster                    | Error/Failure in patching FEPEXporter CR for spec.fepExporter.authSecret or spec.fepExporter.tls details              |
| spec.monitoring.fepExporter.authSecret (removed) | Start Change        | FEPCluster                    | Started patching FEPEXporter CR because spec.fepExporter.authSecret details are deleted                               |
|                                                  | Change Successful   | FEPCluster                    | Successfully patching spec.fepExporter.authSecret                                                                     |
|                                                  | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepExporter.authSecret                                                                 |
| spec.monitoring.fepExporter.tls (removed)        | Start Change        | FEPCluster                    | Started patching FEPEXporter CR because spec.fepExporter.tls details are deleted                                      |
|                                                  | Change Successful   | FEPCluster                    | Successfully patching spec.fepExporter.tls                                                                            |
|                                                  | Change Failed       | FEPCluster                    | Error/Failure in patching spec.fepExporter.tls                                                                        |
| spec.monitoring.fepExporter                      | Start Change        | FEPCluster                    | Started creating FEPEXporter CR                                                                                       |
|                                                  | Change Successful   | FEPCluster                    | Successfully creating FEPEXporter CR                                                                                  |
|                                                  | Change Failed       | FEPCluster                    | Error/Failure in Creating FEPEXporter CR                                                                              |

## C.2 FEPEXporter Event Notification on Custom Resource Changes

When "spec.fepExporter.sysExtraEvent" is true, provides event notification of operator actions when the value of the following fields defined in the FEPEXporter custom resource are changed.

| Field Whose Value You Want to Change | Notification Timing | Notification Custom Resources | Notification Message                                         |
|--------------------------------------|---------------------|-------------------------------|--------------------------------------------------------------|
| spec.fepExporter.restartRequired     | Start Change        | FEPExporter                   | Started patching spec.fepExporter.restartRequired            |
|                                      | Change Successful   | FEPExporter                   | Successfully patching spec.fepExporter.restartRequired       |
|                                      | Change Failed       | FEPExporter                   | Error/Failure in patching spec.fepExporter.restartRequired   |
| spec.fepExporter.userCustomQueries   | Start Change        | FEPExporter                   | Started patching spec.fepExporter.userCustomQueries          |
|                                      | Change Successful   | FEPExporter                   | Successfully patching spec.fepExporter.userCustomQueries     |
|                                      | Change Failed       | FEPExporter                   | Error/Failure in patching spec.fepExporter.userCustomQueries |

## C.3 Event Notification When FEPLogging Custom Resource Changes

When "spec.fepLogging.sysExtraEvent" is true, provides event notification of operator actions when you change the value of the following fields defined in the FEPLogging custom resource.

| Field Whose Value You Want to Change                            | Notification Timing | Notification Custom Resources | Notification Message                                                                       |
|-----------------------------------------------------------------|---------------------|-------------------------------|--------------------------------------------------------------------------------------------|
| spec.fepLogging.restartRequired                                 | Start Change        | FEPLogging                    | Started patching spec.fepLogging.restartRequired                                           |
| spec.fepLogging.restartRequired                                 | Change Successful   | FEPLogging                    | Successfully patching spec.fepLogging.restartRequired                                      |
| spec.fepLogging.restartRequired                                 | Change Failed       | FEPLogging                    | Error/Failure in patching spec.fepLogging.restartRequired                                  |
| spec.fepLogging.scrapeInterval<br>spec.fepLogging.scrapeTimeout | Start Change        | FEPLogging                    | Started patching spec.fepLogging.scrapeInterval and spec.fepLogging.scrapeTimeout          |
| spec.fepLogging.scrapeInterval<br>spec.fepLogging.scrapeTimeout | Change Successful   | FEPLogging                    | Successfully patching spec.fepLogging.scrapeInterval and spec.fepLogging.scrapeTimeout     |
| spec.fepLogging.scrapeInterval<br>spec.fepLogging.scrapeTimeout | Change Failed       | FEPLogging                    | Error/Failure in patching spec.fepLogging.scrapeInterval and spec.fepLogging.scrapeTimeout |
| spec.fepLogging.restartRequired                                 | Start Change        | FEPLogging                    | Started patching spec.fepLogging.restartRequired                                           |